


### Phase Control Thyristors (Stud Version), 110 A



TO-209AC (TO-94)

#### FEATURES

- High current and high surge ratings
- Hermetic ceramic housing
- RoHS compliant
- Designed and qualified for industrial level



#### TYPICAL APPLICATIONS

- DC motor controls
- Controlled DC power supplies
- AC controllers

#### PRODUCT SUMMARY

|             |       |
|-------------|-------|
| $I_{T(AV)}$ | 110 A |
|-------------|-------|

#### MAJOR RATINGS AND CHARACTERISTICS

| PARAMETER         | TEST CONDITIONS | VALUES      | UNITS             |
|-------------------|-----------------|-------------|-------------------|
| $I_{T(AV)}$       |                 | 110         | A                 |
|                   | $T_C$           | 90          | °C                |
| $I_{T(RMS)}$      |                 | 172         | A                 |
| $I_{TSM}$         | 50 Hz           | 2080        | A                 |
|                   | 60 Hz           | 2180        |                   |
| $I^2t$            | 50 Hz           | 21.7        | kA <sup>2</sup> s |
|                   | 60 Hz           | 19.8        |                   |
| $V_{DRM}/V_{RRM}$ |                 | 400 to 1200 | V                 |
| $t_q$             | Typical         | 110         | μs                |
| $T_J$             |                 | - 40 to 140 | °C                |

#### ELECTRICAL SPECIFICATIONS

##### VOLTAGE RATINGS

| TYPE NUMBER | VOLTAGE CODE | $V_{DRM}/V_{RRM}$ , MAXIMUM REPETITIVE PEAK AND OFF-STATE VOLTAGE<br>V | $V_{RSM}$ , MAXIMUM NON-REPETITIVE PEAK VOLTAGE<br>V | $I_{DRM}/I_{RRM}$ MAXIMUM AT $T_J = T_J$ MAXIMUM<br>mA |
|-------------|--------------|------------------------------------------------------------------------|------------------------------------------------------|--------------------------------------------------------|
| 110/111RKI  | 40           | 400                                                                    | 500                                                  | 20                                                     |
|             | 80           | 800                                                                    | 900                                                  |                                                        |
|             | 120          | 1200                                                                   | 1300                                                 |                                                        |

| ABSOLUTE MAXIMUM RATINGS                             |                     |                                                                                                          |                                  |                                                                       |        |                    |
|------------------------------------------------------|---------------------|----------------------------------------------------------------------------------------------------------|----------------------------------|-----------------------------------------------------------------------|--------|--------------------|
| PARAMETER                                            | SYMBOL              | TEST CONDITIONS                                                                                          |                                  |                                                                       | VALUES | UNITS              |
| Maximum average on-state current at case temperature | I <sub>T(AV)</sub>  | 180° conduction, half sine wave                                                                          |                                  |                                                                       | 110    | A                  |
|                                                      |                     |                                                                                                          |                                  |                                                                       | 90     | °C                 |
| Maximum RMS on-state current                         | I <sub>T(RMS)</sub> | DC at 83 °C case temperature                                                                             |                                  |                                                                       | 172    | A                  |
| Maximum peak, one-cycle non-repetitive surge current | I <sub>TSM</sub>    | t = 10 ms                                                                                                | No voltage reapplied             | Sinusoidal half wave, initial T <sub>J</sub> = T <sub>J</sub> maximum | 2080   | A                  |
|                                                      |                     | t = 8.3 ms                                                                                               |                                  |                                                                       | 2180   |                    |
|                                                      |                     | t = 10 ms                                                                                                | 100 % V <sub>RRM</sub> reapplied |                                                                       | 1750   |                    |
|                                                      |                     | t = 8.3 ms                                                                                               |                                  |                                                                       | 1830   |                    |
| Maximum I <sup>2</sup> t for fusing                  | I <sup>2</sup> t    | t = 10 ms                                                                                                | No voltage reapplied             |                                                                       | 21.7   | kA <sup>2</sup> s  |
|                                                      |                     | t = 8.3 ms                                                                                               |                                  |                                                                       | 19.8   |                    |
|                                                      |                     | t = 10 ms                                                                                                | 100 % V <sub>RRM</sub> reapplied |                                                                       | 15.3   |                    |
|                                                      |                     | t = 8.3 ms                                                                                               |                                  |                                                                       | 14.0   |                    |
| Maximum I <sup>2</sup> √t for fusing                 | I <sup>2</sup> √t   | t = 0.1 to 10 ms, no voltage reapplied                                                                   |                                  |                                                                       | 217    | kA <sup>2</sup> √s |
| Low level value of threshold voltage                 | V <sub>T(TO)1</sub> | (16.7 % × π × I <sub>T(AV)</sub> < I < π × I <sub>T(AV)</sub> ), T <sub>J</sub> = T <sub>J</sub> maximum |                                  |                                                                       | 0.82   | V                  |
| High level value of threshold voltage                | V <sub>T(TO)2</sub> | (I > π × I <sub>T(AV)</sub> ), T <sub>J</sub> = T <sub>J</sub> maximum                                   |                                  |                                                                       | 1.02   |                    |
| Low level value of on-state slope resistance         | r <sub>t1</sub>     | (16.7 % × π × I <sub>T(AV)</sub> < I < π × I <sub>T(AV)</sub> ), T <sub>J</sub> = T <sub>J</sub> maximum |                                  |                                                                       | 2.16   | mΩ                 |
| High level value of on-state slope resistance        | r <sub>t2</sub>     | (I > π × I <sub>T(AV)</sub> ), T <sub>J</sub> = T <sub>J</sub> maximum                                   |                                  |                                                                       | 1.70   |                    |
| Maximum on-state voltage                             | V <sub>TM</sub>     | I <sub>pk</sub> = 350 A, T <sub>J</sub> = T <sub>J</sub> maximum, t <sub>p</sub> = 10 ms sine pulse      |                                  |                                                                       | 1.57   | V                  |
| Maximum holding current                              | I <sub>H</sub>      | T <sub>J</sub> = 25 °C, anode supply 6 V resistive load                                                  |                                  |                                                                       | 200    | mA                 |
| Typical latching current                             | I <sub>L</sub>      |                                                                                                          |                                  |                                                                       | 400    |                    |

| SWITCHING                                                |         |                                                                                                            |        |       |
|----------------------------------------------------------|---------|------------------------------------------------------------------------------------------------------------|--------|-------|
| PARAMETER                                                | SYMBOL  | TEST CONDITIONS                                                                                            | VALUES | UNITS |
| Maximum non-repetitive rate of rise of turned-on current | $di/dt$ | Gate drive 20 V, 20 Ω, $t_r \leq 1$ μs<br>$T_J = T_J$ maximum, anode voltage $\leq 80$ % $V_{DRM}$         | 300    | A/μs  |
| Typical delay time                                       | $t_d$   | Gate current 1 A, $di_g/dt = 1$ A/μs<br>$V_d = 0.67$ % $V_{DRM}$ , $T_J = 25$ °C                           | 1.0    | μs    |
| Typical turn-off time                                    | $t_q$   | $I_{TM} = 50$ A, $T_J = T_J$ maximum, $di/dt = -5$ A/μs,<br>$V_R = 50$ V, $dV/dt = 20$ V/μs; gate 0 V 25 Ω | 110    |       |

| BLOCKING                                           |                          |                                                      |        |       |
|----------------------------------------------------|--------------------------|------------------------------------------------------|--------|-------|
| PARAMETER                                          | SYMBOL                   | TEST CONDITIONS                                      | VALUES | UNITS |
| Maximum critical rate of rise of off-state voltage | $dV/dt$                  | $T_J = T_J$ maximum linear to 80 % rated $V_{DRM}$   | 500    | V/μs  |
| Maximum peak reverse and off-state leakage current | $I_{RRM}$ ,<br>$I_{DRM}$ | $T_J = T_J$ maximum, rated $V_{DRM}/V_{RRM}$ applied | 20     | mA    |



| TRIGGERING                          |                    |                                                                |                                                                                                                                                                   |        |      |       |
|-------------------------------------|--------------------|----------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|------|-------|
| PARAMETER                           | SYMBOL             | TEST CONDITIONS                                                |                                                                                                                                                                   | VALUES |      | UNITS |
|                                     |                    |                                                                |                                                                                                                                                                   | TYP.   | MAX. |       |
| Maximum peak gate power             | P <sub>GM</sub>    | T <sub>J</sub> = T <sub>J</sub> maximum, t <sub>p</sub> ≤ 5 ms |                                                                                                                                                                   | 12     |      | W     |
| Maximum average gate power          | P <sub>G(AV)</sub> | T <sub>J</sub> = T <sub>J</sub> maximum, f = 50 Hz, d% = 50    |                                                                                                                                                                   | 3.0    |      |       |
| Maximum peak positive gate current  | I <sub>GM</sub>    | T <sub>J</sub> = T <sub>J</sub> maximum, t <sub>p</sub> ≤ 5 ms |                                                                                                                                                                   | 3.0    |      | A     |
| Maximum peak positive gate voltage  | +V <sub>GM</sub>   | T <sub>J</sub> = T <sub>J</sub> maximum, t <sub>p</sub> ≤ 5 ms |                                                                                                                                                                   | 20     |      | V     |
| Maximum peak negative gate voltage  | -V <sub>GM</sub>   |                                                                |                                                                                                                                                                   | 10     |      |       |
| DC gate current required to trigger | I <sub>GT</sub>    | T <sub>J</sub> = - 40 °C                                       | Maximum required gate trigger/<br>current/voltage are the lowest<br>value which will trigger all units<br>12 V anode to cathode applied                           | 180    | -    | mA    |
|                                     |                    | T <sub>J</sub> = 25 °C                                         |                                                                                                                                                                   | 80     | 120  |       |
|                                     |                    | T <sub>J</sub> = 140 °C                                        |                                                                                                                                                                   | 40     | -    |       |
| DC gate voltage required to trigger | V <sub>GT</sub>    | T <sub>J</sub> = - 40 °C                                       |                                                                                                                                                                   | 2.5    | -    | V     |
|                                     |                    | T <sub>J</sub> = 25 °C                                         |                                                                                                                                                                   | 1.6    | 2    |       |
|                                     |                    | T <sub>J</sub> = 140 °C                                        |                                                                                                                                                                   | 1      | -    |       |
| DC gate current not to trigger      | I <sub>GD</sub>    | T <sub>J</sub> = T <sub>J</sub> maximum                        | Maximum gate current/voltage<br>not to trigger is the maximum<br>value which will not trigger any<br>unit with rated V <sub>DRM</sub> anode to<br>cathode applied | 6.0    |      | mA    |
| DC gate voltage not to trigger      | V <sub>GD</sub>    |                                                                |                                                                                                                                                                   | 0.25   |      | V     |

| THERMAL AND MECHANICAL SPECIFICATIONS        |            |                                               |                  |                     |
|----------------------------------------------|------------|-----------------------------------------------|------------------|---------------------|
| PARAMETER                                    | SYMBOL     | TEST CONDITIONS                               | VALUES           | UNITS               |
| Maximum operating junction temperature range | $T_J$      |                                               | - 40 to 140      | °C                  |
| Maximum storage temperature range            | $T_{Stg}$  |                                               | - 40 to 150      |                     |
| Maximum thermal resistance, junction to case | $R_{thJC}$ | DC operation                                  | 0.27             | K/W                 |
| Maximum thermal resistance, case to heatsink | $R_{thCS}$ | Mounting surface, smooth, flat and greased    | 0.1              |                     |
| Mounting torque, $\pm 10$ %                  |            | Non-lubricated threads                        | 15.5<br>(137)    | N · m<br>(lbf · in) |
|                                              |            | Lubricated threads                            | 14<br>(120)      |                     |
| Approximate weight                           |            |                                               | 130              | g                   |
| Case style                                   |            | See dimensions - link at the end of datasheet | TO-209AC (TO-94) |                     |

| $\Delta R_{thJC}$ CONDUCTION |                       |                        |                     |       |
|------------------------------|-----------------------|------------------------|---------------------|-------|
| CONDUCTION ANGLE             | SINUSOIDAL CONDUCTION | RECTANGULAR CONDUCTION | TEST CONDITIONS     | UNITS |
| 180°                         | 0.043                 | 0.031                  | $T_J = T_J$ maximum | K/W   |
| 120°                         | 0.052                 | 0.053                  |                     |       |
| 90°                          | 0.066                 | 0.071                  |                     |       |
| 60°                          | 0.096                 | 0.101                  |                     |       |
| 30°                          | 0.167                 | 0.169                  |                     |       |

**Note**

- The table above shows the increment of thermal resistance  $R_{thJC}$  when devices operate at different conduction angles than DC




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - On-State Power Loss Characteristics




Fig. 4 - On-State Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - On-State Voltage Drop Characteristics





Fig. 8 - Thermal Impedance  $Z_{thJC}$  Characteristics

Vishay High Power Products Phase Control Thyristors  
(Stud Version), 110 A

- 1** -  $I_{T(AV)}$  rated average output current (rounded/10)
- 2** - 0 = Eyelet terminals (gate and auxiliary cathode leads)  
1 = Fast-on terminals (gate and auxiliary cathode leads)
- 3** - Thyristor
- 4** - Voltage code x 10 =  $V_{RRM}$  (see Voltage Ratings table)

| LINKS TO RELATED DOCUMENTS |                                                                               |
|----------------------------|-------------------------------------------------------------------------------|
| Dimensions                 | <a href="http://www.vishay.com/doc?95003">http://www.vishay.com/doc?95003</a> |



### Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.



## О компании

ООО "ТрейдЭлектроникс" - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Наличие собственной эффективной системы логистики обеспечивает надежную поставку продукции по конкурентным ценам в точно указанные сроки.

Срок поставки со стоков в **Европе и Америке – от 3 до 14 дней.**

Срок поставки из **Азии – от 10 дней.**

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Предоставляем спец цены на элементы для создания инженерных сэмплов.

**Упорный труд, качественный результат дают нам право быть уверенными в себе и надежными для наших клиентов.**

### Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование

Наша организация особенно сильна в поставках модулей, микросхем, пассивных компонентов, ксайленсах (XC), EPF, EPM и силовой электроники.

Большой выбор предлагаемой продукции, различные виды оплаты и доставки, позволят Вам сэкономить время и получить максимум выгоды от сотрудничества с нами!

## Перечень производителей, продукцию которых мы поставляем на российский рынок





Trade Electronics.ru

гарантия бесперебойности производства и  
качества выпускаемой продукции

С удовольствием будем прорабатывать для Вас поставки всех необходимых компонентов по текущим запросам для скорейшего выявления групп элементов, по которым сотрудничество именно с нашей компанией будет для Вас максимально выгодным!

С уважением,

Менеджер отдела продаж ООО

«Трейд Электроникс»

Шишлаков Евгений

8 (495)668-30-28 доб 169

manager28@tradeelectronics.ru

<http://www.tradeelectronics.ru/>