AZ970/AZ971

40 AMP AUTOMOTIVE RELAY

FEATURES

- Up to 40 Amp switching capability in a compact size
- Open, covered or sealed
- Coils to 24 VDC
- Small footprint
- 1 Form A, B and C contacts available
- Vibration and shock resistant
- ISO/TS 16949, ISO14001
- Tested in accordance with SAE J2544
- Cost effective
- Designed for high in-rush applications



CONTACTS

Arrangement	SPST (1 Form A) SPST (1 Form B) SPDT (1 Form C)
Ratings	Resistive load: Max. switched power: Form A: 560 W Form B: 420 W Form C: 420W Max. switched current: Form A: 40 A Form B: 30 A Form C: 30A Max. switched voltage: 150* VDC * If switching voltage is greater than 30 VDC, special precautions must be taken. Please contact the factory.
Material	Silver tin oxide
Resistance	< 100 milliohms initially (24 V, 1 A voltage drop method)

COIL

Power	
At Pickup Voltage (typical)	514 mW (12 and 24 VDC coil) 573 mW (6 VDC coil)
Max. Continuous Dissipation	5.3 W 20°C (68°F) ambient (AZ970) 4.6 W 20°C (68°F) ambient (AZ971)
Temperature Rise	56°C (101°F) nominal coil VDC (AZ970) 59°C (106°F) nominal coil VDC (AZ971)
Max. Temperature	155°C (311°F)

GENERAL DATA

Life Expectancy **Mechanical** **Electrical**	Minimum operations 5 x 10^6 operations 1 x 10^5 40 A 14 VDC Res.
Operate Time (typical)	5 ms at nominal coil voltage
Release Time (typical)	3 ms at nominal coil voltage (with no coil suppression)
Dielectric Strength (at sea level for 1 min.)	500 VDC coil to contact 500 VDC between open contacts
Insulation Resistance	100 megohms min. at 20°C, 500 VDC, 50% RH
Dropout	Greater than 6% of nominal coil voltage
Ambient Temperature	At nominal coil voltage
AZ970 Operating **AZ970 Storage**	-40°C (-40°F) to 110°C (230°F) -40°C (-40°F) to 155°C (311°F)
AZ971 Operating **AZ971 Storage**	-40°C (-40°F) to 105°C (221°F) -40°C (-40°F) to 155°C (311°F)
Vibration	0.062" DA at 10–55 Hz
Shock	10 g
Enclosure	P.B.T. polyester
Terminals	Tinned copper alloy, P.C.
Max. Solder Temp.	270°C (518°F)
Max. Solder Time	5 seconds
Max. Solvent Temp.	80°C (176°F)
Max. Immersion Time	30 seconds
Weight	20 grams

NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than "Must Operate" value.
3. Specifications subject to change without notice.

AMERICAN ZETTLER, INC. *www.azettler.com*

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM

5/23/07W

AZ970/AZ971

RELAY ORDERING DATA — AZ970 — Open Style

COIL SPECIFICATIONS				ORDER NUMBER		
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance ±10%	Form A (SPST)	Form B (SPST)	Form C (SPDT)
6	3.3	9.8	19.0	AZ970–1A–6D	AZ970–1B–6D	AZ970–1C–6D
9	5.1	15.9	50.0	AZ970–1A–9D	AZ970–1B–9D	AZ970–1C–9D
12	6.8	21.3	90.0	AZ970–1A–12D	AZ970–1B–12D	AZ970–1C–12D
24	13.9	42.7	362.0	AZ970–1A–24D	AZ970–1B–24D	AZ970–1C–24D


RELAY ORDERING DATA — AZ971 — With Dust Cover


COIL SPECIFICATIONS				ORDER NUMBER*		
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Coil Resistance ±10%	Form A (SPST)	Form B (SPST)	Form C (SPDT)
6	3.3	9.4	19.0	AZ971–1A–6D	AZ971–1B–6D	AZ971–1C–6D
9	5.1	15.2	50.0	AZ971–1A–9D	AZ971–1B–9D	AZ971–1C–9D
12	6.8	20.4	90.0	AZ971–1A–12D	AZ971–1B–12D	AZ971–1C–12D
24	13.9	41.0	362.0	AZ971–1A–24D	AZ971–1B–24D	AZ971–1C–24D

*Add suffix “E” for epoxy sealed version.

MECHANICAL DATA


AZ970 Outline Dimensions and PCB Layout






Viewed towards terminals

AZ971 Outline Dimensions and PCB Layout






Viewed towards terminals

Terminal Dimensions

Term.	Dimensions
3,5	.041 [1.02] x .03 [0.76]
1,2	.041 [1.02] x .018 [0.46]
4	.041 [1.02] x .062 [1.57]

Wiring Diagrams



Viewed towards terminals

Dimensions in inches with metric equivalents in parentheses. Tolerance: ±0.010"

AMERICAN ZETTLER, INC. www.azettler.com

75 COLUMBIA • ALISO VIEJO, CA 92656 • PHONE: (949) 831-5000 • FAX: (949) 831-8642 • E-MAIL: SALES@AZETTLER.COM

TradeElectronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

О компании

ООО "ТрейдЭлектроникс" - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Наличие собственной эффективной системы логистики обеспечивает надежную поставку продукции по конкурентным ценам в точно указанные сроки.

Срок поставки со стоков в **Европе и Америке – от 3 до 14 дней.**

Срок поставки из **Азии – от 10 дней.**

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Предоставляем спец цены на элементы для создания инженерных сэмплов.

Упорный труд, качественный результат дают нам право быть уверенными в себе и надежными для наших клиентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование

Наша организация особенно сильна в поставках модулей, микросхем, пассивных компонентов, ксайленсах (XC), EPF, EPM и силовой электроники.

Большой выбор предлагаемой продукции, различные виды оплаты и доставки, позволят Вам сэкономить время и получить максимум выгоды от сотрудничества с нами!

Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

Перечень производителей, продукцию которых мы поставляем на российский рынок



Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

С удовольствием будем прорабатывать для Вас поставки всех необходимых компонентов по текущим запросам для скорейшего выявления групп элементов, по которым сотрудничество именно с нашей компанией будет для Вас максимально выгодным!

С уважением,

Менеджер отдела продаж ООО

«Трейд Электроникс»

Шишлаков Евгений

8 (495)668-30-28 доб 169

manager28@tradeelectronics.ru

http://www.tradeelectronics.ru/