USBF TV


USB Connection System for Harsh Environment



Description

USB Field allows you to use a standard USB connection in harsh environments :
- Sealed against fluids and dusts (IP67)
- Shock, Vibration and Traction resistant
- No cabling operation in field and no tools required
- Mechanical Coding / Polarization (2 positions)
- Improved EMI protection

With USB Field, you can insert **a standard USB cordset** into a metallic plug which will protect it from shocks, dust and fluids.
No hazardous in-field cabling and grounding !



Transform your USB cordset into a Harsh Environment Connector !

This metallic plug is connected into a receptacle, using a Tri Start Thread coupling mechanism (MIL-DTL-38999 series III type) with anti-decoupling device for high vibrations.
On the receptacle side, one A USB receptacle is soldered onto a PCB allowing for the following back terminations :
- another A USB receptacle
- solder : 4 tined holes on the PCB to solder your wires

The USB cordset shielding is transmitted to the USB receptacle through grounding fingers.
For an outstanding EMI protection, the conductive plated shells (Ni, Cd) with metallized receptacle inserts, transmit the shielding to the connector shells and finally to the panel.

Applications

- Embedded Computers
- Data Acquisition and Transmission in harsh environment

For :
- Railways
- Battelfield Communication Systems
- Navy Systems

DOC-000046-ANG-B Nov. 2004

Amphenol ®

Amphenol Socapex Promenade de l'Arve -B.P.29 - 74311 THYEZ – F
Tel. :+ 33 (0) 4 50 89 28 00 - Fax : + 33 (0) 4 50 96 29 75
www.usbfield.com

Main Characteristics

Data Transmission

• USB Specification Revision 1.1

Data Rate : 1,5 to 12 Mb/s for Full Speed USB

Mechanical

• Tri Start Thread coupling mechanism (MIL-DTL-38999 series III type) with anti-decoupling device

• 2 mechanical Coding / Polarization possibilities by the user (receptacle insert rotation)

• USBF TV plug retent° in the receptacle : 100 N in the axis

• Mating cycles : 500 to 1500

Environmental Protection

• Sealing (when mated) : IP67 (Temporary immersion)

• Salt Spray : 48 h with Nickel plating

> 500 h with Olive Drab Cadmium

• Fire Retardant / Low Smoke : UL94 V0 and NF F 16 101 & 16 102

• Vibrations : 10 – 500 Hz, 10 g, 3 axes : no discontinuity > 1micro s

• Shocks : IK06 : weight of 250 g drop from 40 cm [15.75 in] onto connectors (mated pair)

• Humidity : 21 days, 43°C, 98% humidity

• Temperature Range : - 55°C / +85°C

Can be used with most of the USB cordset Brands : <u>No tools required</u>


Assembly Instructions

Plug Assembly


1. Only if you need a full sealing (IP67) : Install the white sticker around the plug, covering the 4 little holes of the overmolding
2. Insert the black O Ring around the front face of the USB A plug. This O Ring will ensure the connection sealing.
3. Insert the USB cordset into the metallic backshell
4. Insert laterally to the cable the retention spacer (this spacer is soft, in order to adapt to different shapes of overmolding) and slide the overmolding of the USB-A plug into this retention spacer
5. Insert laterally to the cable the the friction ring
6. Choose the right coding (2 positions) and insert the USB-A plug into the protective plug. Reference is main key.
7. Screw the backshell on the plug body. A spanner can be necessary to fully screw it, and the connection to the receptacle can help.

Important Note : The connection sealing is not done by the black retention spacer (which is sloted), but by the front face ORing (see 2.)

















Receptacle Assembly

Insert the USB module **from the rear**. Reference is main key.

Beware to have a coding compatible with the coding you used for the plug : on front view, the **white shapes** in the USBs **must be on the same side.**




To remove the USB module, insert the removal tool USBF ODE from the Front, and push back the module.







Amphenol Socapex Promenade de l'Arve -B.P.29 - 74311 THYEZ – F
Tel. :+ 33 (0) 4 50 89 28 00 - Fax : + 33 (0) 4 50 96 29 75
www.usbfield.com

Amphenol ®

Plug :

« 6 » Shell








Receptacles :

« 2 » Shell

Square Flange










Panel Drilling

« 7 » Shell

Jam Nut









Panel Drilling

« 2PE » and « 7PE » Shells


with Backshell to protect Backtermination from dust, shocks and vibration. Not sealed.



Back Terminations :




Type 1 : USB-A Receptacle



Type 2 : Solder

4 Tined holes to solder your cable



View of the PCB of the Type 2 version with 4 tined holes for solder termination

Amphenol Socapex Promenade de l'Arve -B.P.29 - 74311 THYEZ – F
Tel. :+ 33 (0) 4 50 89 28 00 - Fax : + 33 (0) 4 50 96 29 75
www.usbfield.com

Amphenol ®

Part Number Code

USBF TV	2	1	G

USB Field TV

Shell Type
6 : Plug
2 : Square Flange Receptacle
2PE : Square Flange Receptacle with backshell
7 : Jam Nut Receptacle
7PE : Jam Nut Receptacle with backshell

Back Terminations (Receptacles only)
1 : USB-A receptacle
2 : Solder (4 tined holes)

Shells Plating
N : Nickel
G : Olive Drab Cadmium

Examples :
- **Olive Drab Cadmium Plug : USBF TV 6G**
- **Olive Drab Cadmium Square Flange Receptacle, USB-A back terminat° : USBF TV 21G**
- **Olive Drab Cadmium Jam Nut Receptacle, USB-A receptacle back terminat° : USBF TV 71G**
- **Nickel Jam Nut Receptacle, solder termination : USBF TV 72N**

Square flange receptacle with Self Closing Cap (cap with a spring inside) :

New!







USBF 21N SCC (*)
Nickel and metallized inserts (EMI)

USBF 21B SCC (*)
Black and blank insert

(*) This P/N includes the square flange receptacle and the self closing cap

Note : Panel gasket to use with this version only : **JE18**






Acces

- **Metallic Caps**

USBF TVC	2	G

Connector Type
6 : Plug
2 : Square Flange Receptacle
7 : Jam Nut Receptacle

Protection de surface
N : Nickel
G : Olive Drab Cadmium




Plug Cap



Receptacle Cap



Plug Cap end



Square flange receptacle cap end



Jam Nut receptacle cap end

- **Panel Gasket for square flange receptacle (Thickness : 0,8 mm [.031]) : JE15**
- **Receptacle Insert removal tool : USBF ODE**



Amphenol Socapex Promenade de l'Arve -B.P.29 - 74311 THYEZ – F
Tel. :+ 33 (0) 4 50 89 28 00 - Fax : + 33 (0) 4 50 96 29 75
www.usbfield.com

Amphenol ®

TradeElectronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

О компании

ООО "ТрейдЭлектроникс" - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Наличие собственной эффективной системы логистики обеспечивает надежную поставку продукции по конкурентным ценам в точно указанные сроки.

Срок поставки со стоков в **Европе и Америке – от 3 до 14 дней.**

Срок поставки из **Азии – от 10 дней.**

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Предоставляем спец цены на элементы для создания инженерных сэмплов.

Упорный труд, качественный результат дают нам право быть уверенными в себе и надежными для наших клиентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование

Наша организация особенно сильна в поставках модулей, микросхем, пассивных компонентов, ксайленсах (XC), EPF, EPM и силовой электроники.

Большой выбор предлагаемой продукции, различные виды оплаты и доставки, позволят Вам сэкономить время и получить максимум выгоды от сотрудничества с нами!

Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

Перечень производителей, продукцию которых мы поставляем на российский рынок



Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

С удовольствием будем прорабатывать для Вас поставки всех необходимых компонентов по текущим запросам для скорейшего выявления групп элементов, по которым сотрудничество именно с нашей компанией будет для Вас максимально выгодным!

С уважением,

Менеджер отдела продаж ООО

«Трейд Электроникс»

Шишлаков Евгений

8 (495)668-30-28 доб 169

manager28@tradeelectronics.ru

http://www.tradeelectronics.ru/