FAIRCHILD SEMICONDUCTOR™

February 2002
Revised February 2002

FIN1002
LVDS 1-Bit High Speed Differential Receiver

General Description

This single receiver is designed for high speed interconnects utilizing Low Voltage Differential Signaling (LVDS) technology. The receiver translates LVDS levels, with a typical differential input threshold of 100 mV, to LVTTL signal levels. LVDS provides low EMI at ultra low power dissipation even at high frequencies. This device is ideal for high speed transfer of clock or data.

The FIN1002 can be paired with its companion driver, the FIN1001, or with any other LVDS driver.

Features

- Greater than 400Mbs data rate
- 3.3V power supply operation
- 0.4ns maximum pulse skew
- 2.5ns maximum propagation delay
- Bus pin ESD (HBM) protection exceeds 10kV
- Power-Off over voltage tolerant input and output
- Fail safe protection for open-circuit and non-driven, shorted or terminated conditions
- High impedance output at V_{CC} < 1.5V
- Meets or exceeds the TIA/EIA-644 LVDS standard
- 5-Lead SOT23 package saves space

Ordering Code:


Order Number	Package Number	Package Description
FIN1002M5	MA05B	5-Lead SOT23, JEDEC MO-178, 1.6mm [250 Units on Tape and Reel]
FIN1002M5X	MA05B	5-Lead SOT23, JEDEC MO-178, 1.6mm [3000 Units on Tape and Reel]

Pin Descriptions

Pin Name	Description
R_{OUT}	LVTTL Data Output
R_{IN+}	Non-inverting Driver Input
R_{IN-}	Inverting Driver Input
V_{CC}	Power Supply
GND	Ground
NC	No Connect

Connection Diagram

Pin Assignment for SOT package



Top View

Function Table

Input		Outputs
R_{IN+}	R_{IN-}	R_{OUT}
L	H	L
H	L	H
Fail Safe Condition		H

H = HIGH Logic Level
L = LOW Logic Level
Fail Safe = Open, Shorted, Terminated

© 2002 Fairchild Semiconductor Corporation

Absolute Maximum Ratings(Note 1)

Supply Voltage (V_{CC})	−0.5V to +4.6V
DC Input Voltage (R_{IN+}, R_{IN-})	−0.5V to +4.6V
DC Output Voltage (D_{OUT})	−0.5V to +6V
DC Output Current (I_O)	16 mA
Storage Temperature Range (T_{STG})	−65°C to +150°C
Max Junction Temperature (T_J)	150°C
Lead Temperature (T_L)	
(Soldering, 10 seconds)	260°C

Recommended Operating Conditions

Supply Voltage (V_{CC})	3.0V to 3.6V
Input Voltage (V_{IN})	0 to V_{CC}
Magnitude of Differential	
Voltage ($\|V_{ID}\|$)	100mV to V_{CC}
Common-mode Input	
Voltage (V_{IC})	(0V + $\|V_{ID}\|$ /2) to (2.4 − $\|V_{ID}\|$/2)
Operating Temperature (T_A)	−40°C to +85°C
ESD (Human Body Model)	
All Pins	8kV
LVDS pins to GND	10kV
ESD (Machine Model)	400V

Note 1: The "Absolute Maximum Ratings": are those values beyond which damage to the device may occur. The databook specifications should be met, without exception, to ensure that the system design is reliable over its power supply, temperature and output/input loading variables. Fairchild does not recommend operation of circuits outside databook specification.

DC Electrical Characteristics

Over supply voltage and operating temperature ranges, unless otherwise specified

Symbol	Parameter	Test Conditions	Min	Typ (Note 2)	Max	Units
V_{TH}	Differential Input Threshold HIGH	See Figure 1; V_{IC} = +0.05V, 1.2V, or 2.35V			100	mV
V_{TL}	Differential Input Threshold LOW	See Figure 1; V_{IC} = +0.05V, 1.2V, or 2.35V	−100			mV
I_{IN}	Input Current	V_{IN} = 0V or V_{CC}			±20	µA
$I_{I(OFF)}$	Power-OFF Input Current	V_{CC} = 0V, V_{IN} = 0V or 3.6V			±20	µA
V_{OH}	Output HIGH Voltage	I_{OH} = −100 µA	V_{CC} − 0.2	3.3		V
		I_{OH} = −8 mA	2.4	3.1		
V_{OL}	Output LOW Voltage	I_{OH} = 100 µA		0.0	0.2	V
		I_{OL} = 8 mA		0.16	0.5	
V_{IK}	Input Clamp Voltage	I_{IK} = −18 mA	−1.5	0.8		V
I_{CC}	Power Supply Current	(R_{IN+} = 1V and R_{IN-} = 1.4V), or (R_{IN+} = 1.4V and R_{IN-} = 1V)		4	7	mA
C_{IN}	Input Capacitance	V_{CC} = 3.3V		2.3		pF
C_{OUT}	Output Capacitance	V_{CC} = 0V		2.8		pF

Note 2: All typical values are at T_A = 25°C and with V_{CC} = 3.3V.


AC Electrical Characteristics

Over supply voltage and operating temperature ranges, unless otherwise specified

Symbol	Parameter	Test Conditions	Min	Typ (Note 3)	Max	Units
t_{PLH}	Propagation Delay LOW-to-HIGH	$\|V_{ID}\|$ = 400 mV, C_L = 10 pF See Figure 1 and Figure 2	0.9	1.5	2.5	ns
t_{PHL}	Propagation Delay HIGH-to-LOW		0.9	1.5	2.5	ns
t_{TLH}	Output Rise Time (20% to 80%)			0.6		ns
t_{THL}	Output Fall Time (80% to 20%)			0.5		ns
$t_{SK(P)}$	Pulse Skew $\|t_{PLH} - t_{PHL}\|$			0.02	0.4	ns
$t_{SK(PP)}$	Part-to-Part Skew (Note 4)				1.0	ns

Note 3: All typical values are at T_A = 25°C and with V_{CC} = 3.3V.

Note 4: $t_{SK(PP)}$ is the magnitude of the difference in propagation delay times between any specified terminals of two devices switching in the same direction (either LOW-to-HIGH or HIGH-to-LOW) when both devices operate with the same supply voltage, same temperature, and have identical test circuits.



Note A: All input pulses have frequency = 10MHz, t_R or t_F = 1ns
Note B: C_L includes all probe and fixture capacitances

FIGURE 1. Differential Receiver Voltage Definitions and Propagation Delay and Transition Time Test Circuit




FIGURE 2. LVDS Input to LVTTL Output AC Waveforms

DC / AC Typical Performance Curves




FIGURE 3. Output High Voltage vs. Power Supply Voltage




FIGURE 4. Output Low Voltage vs. Power Supply Voltage




FIGURE 5. Output Short Circuit Current vs. Power Supply Voltage




FIGURE 6. Power Supply Current vs. Frequency




FIGURE 7. Power Supply Current vs. Ambient Temperature




FIGURE 8. Differential Propagation Delay Power Supply Voltage

DC / AC Typical Performance Curves (Continued)




FIGURE 9. Differential Propagation Delay vs. Ambient Temperature




FIGURE 10. Differential Skew vs. Power Supply Voltage




FIGURE 11. Differential Skew vs. Ambient Temperature




FIGURE 12. Differential Propagation Delay vs. Differential Input Voltage




FIGURE 13. Differential Propagation Delay vs. Common-Mode Voltage




FIGURE 14. Transition Time vs. Power Supply Voltage

DC / AC Typical Performance Curves (Continued)




FIGURE 15. Transition Time vs. Ambient Temperature




FIGURE 16. Differential Propagation Delay vs. Load




FIGURE 17. Differential Propagation Delay vs. Load




FIGURE 18. Transition Time vs. Load




FIGURE 19. Transition Time vs. Load





FIGURE 20. Power Supply Current vs. Power Supply Voltage

Physical Dimensions inches (millimeters) unless otherwise noted



5-Lead SOT23, JEDEC MO-178, 1.6mm
Package Number MA05B

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com

TradeElectronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

О компании

ООО "ТрейдЭлектроникс" - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Наличие собственной эффективной системы логистики обеспечивает надежную поставку продукции по конкурентным ценам в точно указанные сроки.

Срок поставки со стоков в **Европе и Америке – от 3 до 14 дней.**

Срок поставки из **Азии – от 10 дней.**

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Предоставляем спец цены на элементы для создания инженерных сэмплов.

Упорный труд, качественный результат дают нам право быть уверенными в себе и надежными для наших клиентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование

Наша организация особенно сильна в поставках модулей, микросхем, пассивных компонентов, ксайленсах (XC), EPF, EPM и силовой электроники.

Большой выбор предлагаемой продукции, различные виды оплаты и доставки, позволят Вам сэкономить время и получить максимум выгоды от сотрудничества с нами!

Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

Перечень производителей, продукцию которых мы поставляем на российский рынок



Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

С удовольствием будем прорабатывать для Вас поставки всех необходимых компонентов по текущим запросам для скорейшего выявления групп элементов, по которым сотрудничество именно с нашей компанией будет для Вас максимально выгодным!

С уважением,

Менеджер отдела продаж ООО

«Трейд Электроникс»

Шишлаков Евгений

8 (495)668-30-28 доб 169

manager28@tradeelectronics.ru

http://www.tradeelectronics.ru/