



# 1316 Magnet Tape

## Product Data Sheet

Updated : March 1996  
Supersedes : September 1995

### Product Description

3M Magnet Tape is a flexible, polymer bonded product coated on one side with the pressure sensitive adhesive. The magnetic material is made using a special process that orients barium ferrite crystals in the polymer binder during manufacture. This orientation process yields a magnet with excellent magnetic properties.

The high energy magnet tape is then permanently magnetised with multiple north and south poles along its length, providing a minimum holding force of 16 ounces per square inch.

The strong holding power of 3M Magnet Tape allows its use in relatively narrow widths where it combines economy with exceptional performance capabilities.

3M Magnet Tape can be bent, twisted and flexed without loss of magnetic energy. The product conforms readily to irregular surfaces without cracking. It will not lose its magnetic strength when dropped or struck. 3M Magnet Tape is, indeed permanently magnetic.

3M Magnet Tape has a high-tack pressure-sensitive adhesive layer on one side, protected by a peel-away backing. The adhesive will adhere to a wide variety of surfaces including most plastics, wood and metal. The non-adhesive side may be used to hold small ferrous objects such as screw drivers and other tools. The product also saves time by holding small parts during assembly. 3M Magnet Tape is a versatile holding material, which can be used effectively on both metal and non-metal surfaces.

### Physical Properties

Not for specification purposes

<b>Adhesive Type</b>	Rubber	<b>3M ref :</b>
<b>Thickness</b> (ASTM D-3652)	0.84 mm	
<b>Shelf Life</b>	12 months from date of despatch by 3M when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity	

### Performance Characteristics

Not for specification purposes

<b>Magnetic Holding Force</b>	16 oz/in <sup>2</sup> (70 g/cm <sup>2</sup> ) to bare steel.	
<b>Adhesion to Stainless Steel</b> (Peel)	7.6 N/10mm 60 oz/in	
<b>Sliding Force</b>	8 oz/in <sup>2</sup> (35g/cm <sup>2</sup> ) to polished steel.	

Date : March 1996  
1316 Magnet Tape

**Performance  
Characteristics Cont...**  
Not for specification purposes

<b>Flexibility</b>	0.84 mm thick - Bend around 3.2mm diameter mandrel.	
<b>Temperature Performance</b>	- 40°C to + 71°C (- 40°F to + 160°F)	
<b>Chemical Resistance</b>	Weather Water Ozone Dilute Acids Dilute Bases Oils & Common Solvents	Excellent Excellent Excellent Good Good Poor

**Additional Product  
Information**

**Temperature Resistance**

3M Magnet Tape retains its flexibility even in cold weather. The product performs well indoors or out, in hot or cold climates. Extensive testing in 3M laboratories at temperatures ranging from - 40°C to + 71°C (- 40°F to + 160°F) has documented the broad range of capability of both the adhesive and the magnetic holding force.

**Clean, Safe Handling**

The magnetic side of 3M Magnet Tape is specially coated to ensure clean attachment. This coating also resists the external physical conditions that might otherwise result in adhesive bonding between magnet and application surface. Newly painted surfaces should be allowed adequate drying time before application of magnet tape.

**Application**

3M Magnet Tape is easily cut with scissors or a knife. Adhesive mounting surfaces should be free of dirt, grease, oil and solvent. Following placement, the magnet tape should be pressed down firmly with a roller.

**Application Techniques**

1. Bond strength is dependent upon the amount of adhesive-to-surface contact developed. Firm application pressure develops better adhesive contact & thus improves bond strength.

2. To obtain optimum adhesion, the bonding

surfaces must be clean dry and well unified. A typical surface cleaning solvent is isopropyl alcohol & water. Use proper safety precautions for handling solvents.

3. Ideal tape application temperature range is 21°C to 38°C (70°F to 100°F).

Initial tape application to surfaces at temperatures below 10°C (50°F) is not recommended because the adhesive becomes too firm to adhere readily. However once properly applied low temperature holding is generally satisfactory.

3M is a trademark of the 3M Company.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.



**Specialty Tapes & Adhesives**

© 3M United Kingdom PLC 1996

3M United Kingdom PLC  
3M House,  
28 Great Jackson Street,  
Manchester,  
M15 4PA

Customer Service :  
Tel 0161 236 8500  
Fax 0161 237 1105

3M Ireland  
3M House, Adelphi Centre,  
Upper Georges Street,  
Dun Laoghaire, Co. Dublin,  
Ireland

Customer Service :  
Tel (01) 280 3555  
Fax (01) 280 3509



## О компании

ООО "ТрейдЭлектроникс" - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Наличие собственной эффективной системы логистики обеспечивает надежную поставку продукции по конкурентным ценам в точно указанные сроки.

Срок поставки со стоков в **Европе и Америке – от 3 до 14 дней.**

Срок поставки из **Азии – от 10 дней.**

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Предоставляем спец цены на элементы для создания инженерных сэмплов.

**Упорный труд, качественный результат дают нам право быть уверенными в себе и надежными для наших клиентов.**

### Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование

Наша организация особенно сильна в поставках модулей, микросхем, пассивных компонентов, ксайленсах (XC), EPF, EPM и силовой электроники.

Большой выбор предлагаемой продукции, различные виды оплаты и доставки, позволят Вам сэкономить время и получить максимум выгоды от сотрудничества с нами!

## Перечень производителей, продукцию которых мы поставляем на российский рынок





Trade Electronics.ru

гарантия бесперебойности производства и  
качества выпускаемой продукции

С удовольствием будем прорабатывать для Вас поставки всех необходимых компонентов по текущим запросам для скорейшего выявления групп элементов, по которым сотрудничество именно с нашей компанией будет для Вас максимально выгодным!

С уважением,

Менеджер отдела продаж ООО

«Трейд Электроникс»

Шишлаков Евгений

8 (495)668-30-28 доб 169

manager28@tradeelectronics.ru

<http://www.tradeelectronics.ru/>