# DATA SHEET

# 74HC14; 74HCT14
## Hex inverting Schmitt trigger

Product specification
Supersedes data of 1997 Aug 26

2003 Oct 30

Philips
Semiconductors

PHILIPS

## FEATURES

- Applications:
  - Wave and pulse shapers
  - Astable multivibrators
  - Monostable multivibrators.
- Complies with JEDEC standard no. 7A
- ESD protection:
  HBM EIA/JESD22-A114-A exceeds 2000 V
  MM EIA/JESD22-A115-A exceeds 200 V.
- Specified from –40 to +85 °C and –40 to +125 °C.

## DESCRIPTION

The 74HC14 and 74HCT14 are high-speed Si-gate CMOS devices and are pin compatible with low power Schottky TTL (LSTTL). They are specified in compliance with JEDEC standard no. 7A.

The 74HC14 and 74HCT14 provide six inverting buffers with Schmitt-trigger action. They are capable of transforming slowly changing input signals into sharply defined, jitter-free output signals.

## QUICK REFERENCE DATA

GND = 0 V; $T_{amb}$ = 25 °C; $t_r = t_f$ = 6 ns

| SYMBOL | PARAMETER | CONDITIONS | TYPICAL | | UNIT |
|---|---|---|---|---|---|
| | | | HC | HCT | |
| $t_{PHL}/t_{PLH}$ | propagation delay nA to nY | $C_L$ = 15 pF; $V_{CC}$ = 5 V | 12 | 17 | ns |
| $C_I$ | input capacitance | | 3.5 | 3.5 | pF |
| $C_{PD}$ | power dissipation capacitance per gate | notes 1 and 2 | 7 | 8 | pF |

### Notes

1. $C_{PD}$ is used to determine the dynamic power dissipation ($P_D$ in μW):
   $P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o)$ where:
   $f_i$ = input frequency in MHz;
   $f_o$ = output frequency in MHz;
   $C_L$ = output load capacitance in pF;
   $V_{CC}$ = supply voltage in Volts;
   N = total load switching outputs;
   $\Sigma(C_L \times V_{CC}^2 \times f_o)$ = sum of the outputs.
2. For type 74HC14 the condition is $V_I$ = GND to $V_{CC}$.
   For type 74HCT14 the condition is $V_I$ = GND to $V_{CC}$ – 1.5 V.

## FUNCTION TABLE

| INPUT | OUTPUT |
|---|---|
| **nA** | **nY** |
| L | H |
| H | L |

**Note**

1. H = HIGH voltage level;
   L = LOW voltage level.

## ORDERING INFORMATION

| TYPE NUMBER | PACKAGE | | | | |
|---|---|---|---|---|---|
| | TEMPERATURE RANGE | PINS | PACKAGE | MATERIAL | CODE |
| 74HC14D | –40 to +125 °C | 14 | SO14 | plastic | SOT108-1 |
| 74HCT14D | –40 to +125 °C | 14 | SO14 | plastic | SOT108-1 |
| 74HC14DB | –40 to +125 °C | 14 | SSOP14 | plastic | SOT337-1 |
| 74HCT14DB | –40 to +125 °C | 14 | SSOP14 | plastic | SOT337-1 |
| 74HC14N | –40 to +125 °C | 14 | DIP14 | plastic | SOT27-1 |
| 74HCT14N | –40 to +125 °C | 14 | DIP14 | plastic | SOT27-1 |
| 74HC14PW | –40 to +125 °C | 14 | TSSOP14 | plastic | SOT402-1 |
| 74HCT14PW | –40 to +125 °C | 14 | TSSOP14 | plastic | SOT402-1 |
| 74HC14BQ | –40 to +125 °C | 14 | DHVQFN14 | plastic | SOT762-1 |
| 74HCT14BQ | –40 to +125 °C | 14 | DHVQFN14 | plastic | SOT762-1 |

## PINNING

| PIN | SYMBOL | DESCRIPTION |
|---|---|---|
| 1 | 1A | data input |
| 2 | 1Y | data output |
| 3 | 2A | data input |
| 4 | 2Y | data output |
| 5 | 3A | data input |
| 6 | 3Y | data output |
| 7 | GND | ground (0 V) |
| 8 | 4Y | data output |
| 9 | 4A | data input |
| 10 | 5Y | data output |
| 11 | 5A | data input |
| 12 | 6Y | data output |
| 13 | 6A | data input |
| 14 | $V_{CC}$ | supply voltage |






Fig.1 Pin configuration.




(1) The die substrate is attached to this pad using conductive die attach material. It can not be used as a supply pin or input.

Fig.2 Pin configuration DHVQFN14.





Fig.3 Logic symbol.





Fig.4 IEC logic symbol.





Fig.5 Functional diagram.





Fig.6 Logic diagram (one Schmitt trigger).

**RECOMMENDED OPERATING CONDITIONS**

| SYMBOL | PARAMETER | CONDITIONS | 74HC14 | | | 74HCT14 | | | UNIT |
|---|---|---|---|---|---|---|---|---|---|
| | | | MIN. | TYP. | MAX. | MIN. | TYP. | MAX. | |
| $V_{CC}$ | supply voltage | | 2.0 | 5.0 | 6.0 | 4.5 | 5.0 | 5.5 | V |
| $V_I$ | input voltage | | 0 | – | $V_{CC}$ | 0 | – | $V_{CC}$ | V |
| $V_O$ | output voltage | | 0 | – | $V_{CC}$ | 0 | – | $V_{CC}$ | V |
| $T_{amb}$ | operating ambient temperature | see DC and AC characteristics per device | –40 | +25 | +85 | –40 | +25 | +85 | °C |
| | | | –40 | – | +125 | –40 | – | +125 | °C |

**LIMITING VALUES**

In accordance with the Absolute Maximum System (IEC 60134); voltages are referenced to GND (ground = 0 V).

| SYMBOL | PARAMETER | CONDITIONS | MIN. | MAX. | UNIT |
|---|---|---|---|---|---|
| $V_{CC}$ | supply voltage | | –0.5 | +7 | V |
| $I_{IK}$ | input diode current | $V_I < -0.5$ V or $V_I > V_{CC} + 0.5$ V | – | ±20 | mA |
| $I_{OK}$ | output diode current | $V_O < -0.5$ V or $V_O > V_{CC} + 0.5$ V | – | ±20 | mA |
| $I_O$ | output source or sink current | $-0.5$ V $< V_O < V_{CC} + 0.5$ V | – | ±25 | mA |
| $I_{CC}$; $I_{GND}$ | $V_{CC}$ or GND current | | – | 50 | mA |
| $T_{stg}$ | storage temperature | | –65 | +150 | °C |
| $P_{tot}$ | power dissipation | $T_{amb}$ = –40 to +125 °C | | | |
| | | DIP14 packages; note 1 | – | 750 | mW |
| | | Other packages; note 2 | – | 500 | mW |

**Notes**

1. For DIP14 packages: above 70 °C the value of $P_D$ derates linearly with 12 mW/K.
2. For SO14 packages: above 70 °C the value of $P_D$ derates linearly with 8 mW/K.
   For (T)SSOP14 packages: above 60 °C the value of $P_D$ derates linearly with 5.5 mW/K.
   For DHVQFN14 packages: above 60 °C the value of $P_D$ derates linearly with 4.5 mW/K.

## DC CHARACTERISTICS

### Type 74HC14

At recommended operating conditions; voltages are referenced to GND (ground = 0 V).

| SYMBOL | PARAMETER | TEST CONDITIONS | | MIN. | TYP.(1) | MAX. | UNIT |
|---|---|---|---|---|---|---|---|
| | | OTHER | $V_{CC}$ (V) | | | | |
| **$T_{amb}$ = 25 °C** | | | | | | | |
| $V_{OH}$ | HIGH-level output voltage | $V_I = V_{IH}$ or $V_{IL}$ | | | | | |
| | | $I_O$ = –20 μA | 2.0 | 1.9 | 2.0 | – | V |
| | | $I_O$ = –20 μA | 4.5 | 4.4 | 4.5 | – | V |
| | | $I_O$ = –20 μA | 6.0 | 5.9 | 6.0 | – | V |
| | | $I_O$ = –4.0 mA | 4.5 | 3.98 | 4.32 | – | V |
| | | $I_O$ = –5.2 mA | 6.0 | 5.48 | 5.81 | – | V |
| $V_{OL}$ | LOW-level output voltage | $V_I = V_{IH}$ or $V_{IL}$ | | | | | |
| | | $I_O$ = 20 μA | 2.0 | – | 0 | 0.1 | V |
| | | $I_O$ = 20 μA | 4.5 | – | 0 | 0.1 | V |
| | | $I_O$ = 20 μA | 6.0 | – | 0 | 0.1 | V |
| | | $I_O$ = 4.0 mA | 4.5 | – | 0.15 | 0.26 | V |
| | | $I_O$ = 5.2 mA | 6.0 | – | 0.16 | 0.26 | V |
| $I_{LI}$ | input leakage current | $V_I = V_{CC}$ or GND | 6.0 | – | – | 0.1 | μA |
| $I_{CC}$ | quiescent supply current | $V_I = V_{CC}$ or GND; $I_O$ = 0 | 6.0 | – | – | 2.0 | μA |
| **$T_{amb}$ = –40 to +85 °C** | | | | | | | |
| $V_{OH}$ | HIGH-level output voltage | $V_I = V_{IH}$ or $V_{IL}$ | | | | | |
| | | $I_O$ = –20 μA | 2.0 | 1.9 | – | – | V |
| | | $I_O$ = –20 μA | 4.5 | 4.4 | – | – | V |
| | | $I_O$ = –20 μA | 6.0 | 5.9 | – | – | V |
| | | $I_O$ = –4.0 mA | 4.5 | 3.84 | – | – | V |
| | | $I_O$ = –5.2 mA | 6.0 | 5.34 | – | – | V |
| $V_{OL}$ | LOW-level output voltage | $V_I = V_{IH}$ or $V_{IL}$ | | | | | |
| | | $I_O$ = 20 μA | 2.0 | – | – | 0.1 | V |
| | | $I_O$ = 20 μA | 4.5 | – | – | 0.1 | V |
| | | $I_O$ = 20 μA | 6.0 | – | – | 0.1 | V |
| | | $I_O$ = 4.0 mA | 4.5 | – | – | 0.33 | V |
| | | $I_O$ = 5.2 mA | 6.0 | – | – | 0.33 | V |
| $I_{LI}$ | input leakage current | $V_I = V_{CC}$ or GND | 6.0 | – | – | 1.0 | μA |
| $I_{CC}$ | quiescent supply current | $V_I = V_{CC}$ or GND; $I_O$ = 0 | 6.0 | – | – | 20 | μA |

| SYMBOL | PARAMETER | TEST CONDITIONS | | MIN. | TYP.(1) | MAX. | UNIT |
|---|---|---|---|---|---|---|---|
| | | OTHER | $V_{CC}$ (V) | | | | |
| **$T_{amb}$ = −40 to +125 °C** | | | | | | | |
| $V_{OH}$ | HIGH-level output voltage | $V_I = V_{IH}$ or $V_{IL}$ | | | | | |
| | | $I_O$ = −20 μA | 2.0 | 1.9 | – | – | V |
| | | $I_O$ = −20 μA | 4.5 | 4.4 | – | – | V |
| | | $I_O$ = −20 μA | 6.0 | 5.9 | – | – | V |
| | | $I_O$ = −4.0 mA | 4.5 | 3.7 | – | – | V |
| | | $I_O$ = −5.2 mA | 6.0 | 5.2 | – | – | V |
| $V_{OL}$ | LOW-level output voltage | $V_I = V_{IH}$ or $V_{IL}$ | | | | | |
| | | $I_O$ = 20 μA | 2.0 | – | – | 0.1 | V |
| | | $I_O$ = 20 μA | 4.5 | – | – | 0.1 | V |
| | | $I_O$ = 20 μA | 6.0 | – | – | 0.1 | V |
| | | $I_O$ = 4.0 mA | 4.5 | – | – | 0.4 | V |
| | | $I_O$ = 5.2 mA | 6.0 | – | – | 0.4 | V |
| $I_{LI}$ | input leakage current | $V_I = V_{CC}$ or GND | 6.0 | – | – | 1.0 | μA |
| $I_{CC}$ | quiescent supply current | $V_I = V_{CC}$ or GND; $I_O$ = 0 | 6.0 | – | – | 40 | μA |

**Note**

1. All typical values are measured at $T_{amb}$ = 25 °C.

**Type 74HCT14**

At recommended operating conditions; voltages are referenced to GND (ground = 0 V).

| SYMBOL | PARAMETER | TEST CONDITIONS | | MIN. | TYP.(1) | MAX. | UNIT |
|---|---|---|---|---|---|---|---|
| | | OTHER | $V_{CC}$ (V) | | | | |
| **$T_{amb}$ = 25 °C** | | | | | | | |
| $V_{OH}$ | HIGH-level output voltage | $V_I = V_{IH}$ or $V_{IL}$ | | | | | |
| | | $I_O$ = –20 μA | 4.5 | 4.4 | 4.5 | – | V |
| | | $I_O$ = –4.0 mA | 4.5 | 3.98 | 4.32 | – | V |
| $V_{OL}$ | LOW-level output voltage | $V_I = V_{IH}$ or $V_{IL}$ | | | | | |
| | | $I_O$ = 20 μA | 4.5 | – | 0 | 0.1 | V |
| | | $I_O$ = 4.0 mA | 4.5 | – | 0.15 | 0.26 | V |
| $I_{LI}$ | input leakage current | $V_I = V_{CC}$ or GND | 5.5 | – | – | 0.1 | μA |
| $I_{CC}$ | quiescent supply current | $V_I = V_{CC}$ or GND; $I_O$ = 0 | 5.5 | – | – | 2.0 | μA |
| $\Delta I_{CC}$ | additional supply current per input | $V_I = V_{CC}$ – 2.1 V; $I_O$ = 0 | 4.5 to 5.5 | – | 30 | 108 | μA |
| **$T_{amb}$ = –40 to +85 °C** | | | | | | | |
| $V_{OH}$ | HIGH-level output voltage | $V_I = V_{IH}$ or $V_{IL}$ | | | | | |
| | | $I_O$ = –20 μA | 4.5 | 4.4 | – | – | V |
| | | $I_O$ = –4.0 mA | 4.5 | 3.84 | – | – | V |
| $V_{OL}$ | LOW-level output voltage | $V_I = V_{IH}$ or $V_{IL}$ | | | | | |
| | | $I_O$ = 20 μA | 4.5 | – | – | 0.1 | V |
| | | $I_O$ = 4.0 mA | 4.5 | – | – | 0.33 | V |
| $I_{LI}$ | input leakage current | $V_I = V_{CC}$ or GND | 5.5 | – | – | 1.0 | μA |
| $I_{CC}$ | quiescent supply current | $V_I = V_{CC}$ or GND; $I_O$ = 0 | 5.5 | – | – | 20 | μA |
| $\Delta I_{CC}$ | additional supply current per input | $V_I = V_{CC}$ – 2.1 V; $I_O$ = 0 | 4.5 to 5.5 | – | – | 135 | μA |
| **$T_{amb}$ = –40 to +125 °C** | | | | | | | |
| $V_{OH}$ | HIGH-level output voltage | $V_I = V_{IH}$ or $V_{IL}$ | | | | | |
| | | $I_O$ = –20 μA | 4.5 | 4.4 | – | – | V |
| | | $I_O$ = –4.0 mA | 4.5 | 3.7 | – | – | V |
| $V_{OL}$ | LOW-level output voltage | $V_I = V_{IH}$ or $V_{IL}$ | | | | | |
| | | $I_O$ = 20 μA | 4.5 | – | – | 0.1 | V |
| | | $I_O$ = 4.0 mA | 4.5 | – | – | 0.4 | V |
| $I_{LI}$ | input leakage current | $V_I = V_{CC}$ or GND | 5.5 | – | – | 1.0 | μA |
| $I_{CC}$ | quiescent supply current | $V_I = V_{CC}$ or GND; $I_O$ = 0 | 5.5 | – | – | 40 | μA |
| $\Delta I_{CC}$ | additional supply current per input | $V_I = V_{CC}$ – 2.1 V; $I_O$ = 0 | 4.5 to 5.5 | – | – | 147 | μA |

**Note**

1. All typical values are measured at $T_{amb}$ = 25 °C.

## TRANSFER CHARACTERISTICS

### Type 74HC

At recommended operating conditions; voltages are referenced to GND (ground = 0 V).

| SYMBOL | PARAMETER | TEST CONDITIONS | | MIN. | TYP. | MAX. | UNIT |
|---|---|---|---|---|---|---|---|
| | | WAVEFORMS | $V_{CC}$ (V) | | | | |
| **$T_{amb}$ = 25 °C;** note 1 | | | | | | | |
| $V_{T+}$ | positive-going threshold | Figs 7 and 8 | 2.0 | 0.7 | 1.18 | 1.5 | V |
| | | | 4.5 | 1.7 | 2.38 | 3.15 | V |
| | | | 6.0 | 2.1 | 3.14 | 4.2 | V |
| $V_{T-}$ | negative-going threshold | Figs 7 and 8 | 2.0 | 0.3 | 0.52 | 0.90 | V |
| | | | 4.5 | 0.9 | 1.40 | 2.00 | V |
| | | | 6.0 | 1.2 | 1.89 | 2.60 | V |
| $V_H$ | hysteresis ($V_{T+} - V_{T-}$) | Figs 7 and 8 | 2.0 | 0.2 | 0.66 | 1.0 | V |
| | | | 4.5 | 0.4 | 0.98 | 1.4 | V |
| | | | 6.0 | 0.6 | 1.25 | 1.6 | V |
| **$T_{amb}$ = −40 to +85 °C** | | | | | | | |
| $V_{T+}$ | positive-going threshold | Figs 7 and 8 | 2.0 | 0.7 | – | 1.5 | V |
| | | | 4.5 | 1.7 | – | 3.15 | V |
| | | | 6.0 | 2.1 | – | 4.2 | V |
| $V_{T-}$ | negative-going threshold | Figs 7 and 8 | 2.0 | 0.3 | – | 0.90 | V |
| | | | 4.5 | 0.90 | – | 2.00 | V |
| | | | 6.0 | 1.20 | – | 2.60 | V |
| $V_H$ | hysteresis ($V_{T+} - V_{T-}$) | Figs 7 and 8 | 2.0 | 0.2 | – | 1.0 | V |
| | | | 4.5 | 0.4 | – | 1.4 | V |
| | | | 6.0 | 0.6 | – | 1.6 | V |
| **$T_{amb}$ = −40 to +125 °C** | | | | | | | |
| $V_{T+}$ | positive-going threshold | Figs 7 and 8 | 2.0 | 0.7 | – | 1.5 | V |
| | | | 4.5 | 1.7 | – | 3.15 | V |
| | | | 6.0 | 2.1 | – | 4.2 | V |
| $V_{T-}$ | negative-going threshold | Figs 7 and 8 | 2.0 | 0.30 | – | 0.90 | V |
| | | | 4.5 | 0.90 | – | 2.00 | V |
| | | | 6.0 | 1.2 | – | 2.60 | V |
| $V_H$ | hysteresis ($V_{T+} - V_{T-}$) | Figs 7 and 8 | 2.0 | 0.2 | – | 1.0 | V |
| | | | 4.5 | 0.4 | – | 1.4 | V |
| | | | 6.0 | 0.6 | – | 1.6 | V |

**Note**

1. All typical values are measured at $T_{amb}$ = 25 °C.

**Family 74HCT**

At recommended operating conditions: voltages are referenced to GND (ground = 0 V)

| SYMBOL | PARAMETER | TEST CONDITIONS | | MIN. | TYP. | MAX. | UNIT |
|---|---|---|---|---|---|---|---|
| | | WAVEFORMS | $V_{CC}$ (V) | | | | |
| **$T_{amb}$ = 25 °C;** note 1 | | | | | | | |
| $V_{T+}$ | positive-going threshold | Figs 7 and 8 | 4.5 | 1.2 | 1.41 | 1.9 | V |
| | | | 5.5 | 1.4 | 1.59 | 2.1 | V |
| $V_{T-}$ | negative-going threshold | Figs 7 and 8 | 4.5 | 0.5 | 0.85 | 1.2 | V |
| | | | 5.5 | 0.6 | 0.99 | 1.4 | V |
| $V_H$ | hysteresis ($V_{T+} - V_{T-}$) | Figs 7 and 8 | 4.5 | 0.4 | 0.56 | – | V |
| | | | 5.5 | 0.4 | 0.60 | – | V |
| **$T_{amb}$ = −40 to +85 °C** | | | | | | | |
| $V_{T+}$ | positive-going threshold | Figs 7 and 8 | 4.5 | 1.2 | – | 1.9 | V |
| | | | 5.5 | 1.4 | – | 2.1 | V |
| $V_{T-}$ | negative-going threshold | Figs 7 and 8 | 4.5 | 0.5 | – | 1.2 | V |
| | | | 5.5 | 0.6 | – | 1.4 | V |
| $V_H$ | hysteresis ($V_{T+} - V_{T-}$) | Figs 7 and 8 | 4.5 | 0.4 | – | – | V |
| | | | 5.5 | 0.4 | – | – | V |
| **$T_{amb}$ = −40 to +125 °C** | | | | | | | |
| $V_{T+}$ | positive-going threshold | Figs 7 and 8 | 4.5 | 1.2 | – | 1.9 | V |
| | | | 5.5 | 1.4 | – | 2.1 | V |
| $V_{T-}$ | negative-going threshold | Figs 7 and 8 | 4.5 | 0.5 | – | 1.2 | V |
| | | | 5.5 | 0.6 | – | 1.4 | V |
| $V_H$ | hysteresis ($V_{T+} - V_{T-}$) | Figs 7 and 8 | 4.5 | 0.4 | – | – | V |
| | | | 5.5 | 0.4 | – | – | V |

**Note**

1. All typical values are measured at $T_{amb}$ = 25 °C.

## AC CHARACTERISTICS

### Type 74HC

GND = 0 V; $t_r = t_f$ = 6 ns; $C_L$ = 50 pF

| SYMBOL | PARAMETER | TEST CONDITIONS | | MIN. | TYP. | MAX. | UNIT |
|---|---|---|---|---|---|---|---|
| | | WAVEFORMS | $V_{CC}$ (V) | | | | |
| **$T_{amb}$ = 25 °C;** note 1 | | | | | | | |
| $t_{PHL}/t_{PLH}$ | propagation delay nA to nY | see Fig.9 | 2.0 | – | 41 | 125 | ns |
| | | | 4.5 | – | 15 | 25 | ns |
| | | | 6.0 | – | 12 | 21 | ns |
| $t_{THL}/t_{TLH}$ | output transition time | see Fig.9 | 2.0 | – | 19 | 75 | ns |
| | | | 4.5 | – | 7 | 15 | ns |
| | | | 6.0 | – | 6 | 13 | ns |
| **$T_{amb}$ = −40 to +85 °C** | | | | | | | |
| $t_{PHL}/t_{PLH}$ | propagation delay nA to nY | see Fig.9 | 2.0 | – | – | 155 | ns |
| | | | 4.5 | – | – | 31 | ns |
| | | | 6.0 | – | – | 26 | ns |
| $t_{THL}/t_{TLH}$ | output transition time | see Fig.9 | 2.0 | – | – | 95 | ns |
| | | | 4.5 | – | – | 19 | ns |
| | | | 6.0 | – | – | 15 | ns |
| **$T_{amb}$ = −40 to +125 °C** | | | | | | | |
| $t_{PHL}/t_{PLH}$ | propagation delay nA to nY | see Fig.9 | 2.0 | – | – | 190 | ns |
| | | | 4.5 | – | – | 38 | ns |
| | | | 6.0 | – | – | 32 | ns |
| $t_{THL}/t_{TLH}$ | output transition time | see Fig.9 | 2.0 | – | – | 110 | ns |
| | | | 4.5 | – | – | 22 | ns |
| | | | 6.0 | – | – | 19 | ns |

**Note**

1. All typical values are measured at $T_{amb}$ = 25 °C.

**Type 74HCT**

GND = 0 V; $t_r = t_f$ = 6 ns; $C_L$ = 50 pF

| SYMBOL | PARAMETER | TEST CONDITIONS | | MIN. | TYP. | MAX. | UNIT |
|---|---|---|---|---|---|---|---|
| | | WAVEFORMS | $V_{CC}$ (V) | | | | |
| **$T_{amb}$ = 25 °C;** note 1 | | | | | | | |
| $t_{PHL}/t_{PLH}$ | propagation delay nA to nY | see Fig.9 | 4.5 | – | 20 | 34 | ns |
| $t_{THL}/t_{TLH}$ | output transition time | see Fig.9 | 4.5 | – | 7 | 15 | ns |
| **$T_{amb}$ = −40 to +85 °C** | | | | | | | |
| $t_{PHL}/t_{PLH}$ | propagation delay nA to nY | see Fig.9 | 4.5 | 43 | – | – | ns |
| $t_{THL}/t_{TLH}$ | output transition time | see Fig.9 | 4.5 | 19 | – | – | ns |
| **$T_{amb}$ = −40 to +125 °C** | | | | | | | |
| $t_{PHL}/t_{PLH}$ | propagation delay nA to nY | see Fig.9 | 4.5 | – | – | 51 | ns |
| $t_{THL}/t_{TLH}$ | output transition time | see Fig.9 | 4.5 | – | – | 22 | ns |

**Note**

1. All typical values are measured at $T_{amb}$ = 25 °C.

**TRANSFER CHARACTERISTIC WAVEFORMS**







Fig.7 Transfer characteristic.





$V_{T+}$ and $V_{T-}$ are between limits of 20% and 70%.

Fig.8 The definitions of $V_{T+}$, $V_{T-}$ and $V_H$.





$V_{CC}$ = 2 V.

Fig.9 Typical 74HC14 transfer characteristics.





$V_{CC}$ = 4.5 V.

Fig.10 Typical 74HC14 transfer characteristics.





$V_{CC}$ = 6 V.

Fig.11 Typical 74HC14 transfer characteristics.




$V_{CC}$ = 4.5 V.


Fig.12 Typical 74HCT14 transfer characteristics.




$V_{CC}$ = 5.5 V.


Fig.13 Typical 74HCT14 transfer characteristics.

**AC WAVEFORMS**




74HC14: $V_M$ = 50%; $V_I$ = GND to $V_{CC}$.
74HCT14: $V_M$ = 1.3 V; $V_I$ = GND to 3.0 V.

Fig.14 The input (nA) to output (nY) propagation delays and output transitions times.




| TEST | S1 |
|---|---|
| $t_{PLH}/t_{PHL}$ | open |
| $t_{PLZ}/t_{PZL}$ | $V_{CC}$ |
| $t_{PHZ}/t_{PZH}$ | GND |

Definitions for test circuit:

$R_L$ = Load resistor.

$C_L$ = load capacitance including jig and probe capacitance.

$R_T$ = termination resistance should be equal to the output impedance $Z_o$ of the pulse generator.

Fig.15 Load circuitry for switching times.

## APPLICATION INFORMATION

The slow input rise and fall times cause additional power dissipation. This can be calculated using the following formula:

$P_{ad} = f_i \times (t_r \times I_{CC(AV)} + t_f \times I_{CC(AV)}) \times V_{CC}$.

Where:

$P_{ad}$ = additional power dissipation (μW);

$f_i$ = input frequency (MHz);

$t_r$ = input rise time (μs); 10% to 90%;

$t_f$ = input fall time (μs); 10% to 90%;


$I_{CC(AV)}$ = average additional supply current (μA).

$I_{CC(AV)}$ differs with positive or negative input transitions, as shown in Figs 16 and 17.

For 74HC/HCT14 used in a relaxation oscillator circuit, see Fig.18.


### Note to application information

All values given are typical unless otherwise specified.





Linear change of $V_I$ between $0.1V_{CC}$ to $0.9V_{CC}$

Fig.16 Average $I_{CC}$ for 74HC14 Schmitt trigger devices.




Linear change of $V_I$ between $0.1V_{CC}$ to $0.9V_{CC}$.

Fig.17 Average $I_{CC}$ for HCT Schmitt trigger devices.





$$74HC14 : f = \frac{1}{T} \approx \frac{1}{0.8\ RC}$$

$$74HCT14 : f = \frac{1}{T} \approx \frac{1}{0.67\ RC}$$

Fig.18 Relaxation oscillator using 74HC/HCT14.

## PACKAGE OUTLINES

**SO14: plastic small outline package; 14 leads; body width 3.9 mm** **SOT108-1**




**DIMENSIONS (inch dimensions are derived from the original mm dimensions)**


| UNIT | A max. | $A_1$ | $A_2$ | $A_3$ | $b_p$ | c | $D^{(1)}$ | $E^{(1)}$ | e | $H_E$ | L | $L_p$ | Q | v | w | y | $Z^{(1)}$ | θ |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| mm | 1.75 | 0.25<br>0.10 | 1.45<br>1.25 | 0.25 | 0.49<br>0.36 | 0.25<br>0.19 | 8.75<br>8.55 | 4.0<br>3.8 | 1.27 | 6.2<br>5.8 | 1.05 | 1.0<br>0.4 | 0.7<br>0.6 | 0.25 | 0.25 | 0.1 | 0.7<br>0.3 | $8^o$<br>$0^o$ |
| inches | 0.069 | 0.010<br>0.004 | 0.057<br>0.049 | 0.01 | 0.019<br>0.014 | 0.0100<br>0.0075 | 0.35<br>0.34 | 0.16<br>0.15 | 0.05 | 0.244<br>0.228 | 0.041 | 0.039<br>0.016 | 0.028<br>0.024 | 0.01 | 0.01 | 0.004 | 0.028<br>0.012 | |

**Note**

1. Plastic or metal protrusions of 0.15 mm (0.006 inch) maximum per side are not included.

| OUTLINE VERSION | REFERENCES | | | | EUROPEAN PROJECTION | ISSUE DATE |
|---|---|---|---|---|---|---|
| | IEC | JEDEC | JEITA | | | |
| SOT108-1 | 076E06 | MS-012 | | | | ~~99-12-27~~<br>03-02-19 |

**DIP14: plastic dual in-line package; 14 leads (300 mil)** **SOT27-1**




**DIMENSIONS (inch dimensions are derived from the original mm dimensions)**


| UNIT | A max. | $A_1$ min. | $A_2$ max. | b | $b_1$ | c | D (1) | E (1) | e | $e_1$ | L | $M_E$ | $M_H$ | w | Z (1) max. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| mm | 4.2 | 0.51 | 3.2 | 1.73<br>1.13 | 0.53<br>0.38 | 0.36<br>0.23 | 19.50<br>18.55 | 6.48<br>6.20 | 2.54 | 7.62 | 3.60<br>3.05 | 8.25<br>7.80 | 10.0<br>8.3 | 0.254 | 2.2 |
| inches | 0.17 | 0.02 | 0.13 | 0.068<br>0.044 | 0.021<br>0.015 | 0.014<br>0.009 | 0.77<br>0.73 | 0.26<br>0.24 | 0.1 | 0.3 | 0.14<br>0.12 | 0.32<br>0.31 | 0.39<br>0.33 | 0.01 | 0.087 |

**Note**

1. Plastic or metal protrusions of 0.25 mm (0.01 inch) maximum per side are not included.

| OUTLINE VERSION | REFERENCES | | | | EUROPEAN PROJECTION | ISSUE DATE |
|---|---|---|---|---|---|---|
| | IEC | JEDEC | JEIA | | | |
| SOT27-1 | 050G04 | MO-001 | SC-501-14 | | | ~~99-12-27~~<br>03-02-13 |

**TSSOP14: plastic thin shrink small outline package; 14 leads; body width 4.4 mm** **SOT402-1**




**DIMENSIONS (mm are the original dimensions)**


| UNIT | A max. | $A_1$ | $A_2$ | $A_3$ | $b_p$ | c | D (1) | E (2) | e | $H_E$ | L | $L_p$ | Q | v | w | y | Z (1) | θ |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| mm | 1.1 | 0.15<br>0.05 | 0.95<br>0.80 | 0.25 | 0.30<br>0.19 | 0.2<br>0.1 | 5.1<br>4.9 | 4.5<br>4.3 | 0.65 | 6.6<br>6.2 | 1 | 0.75<br>0.50 | 0.4<br>0.3 | 0.2 | 0.13 | 0.1 | 0.72<br>0.38 | $8^o$<br>$0^o$ |

**Notes**

1. Plastic or metal protrusions of 0.15 mm maximum per side are not included.
2. Plastic interlead protrusions of 0.25 mm maximum per side are not included.

| OUTLINE VERSION | REFERENCES | | | | EUROPEAN PROJECTION | ISSUE DATE |
|---|---|---|---|---|---|---|
| | IEC | JEDEC | JEITA | | | |
| SOT402-1 | | MO-153 | | | | ~~99-12-27~~<br>03-02-18 |

**DHVQFN14: plastic dual in-line compatible thermal enhanced very thin quad flat package; no leads; 14 terminals; body 2.5 x 3 x 0.85 mm** **SOT762-1**




**DIMENSIONS (mm are the original dimensions)**

| UNIT | $A^{(1)}$ max. | $A_1$ | b | c | $D^{(1)}$ | $D_h$ | $E^{(1)}$ | $E_h$ | e | $e_1$ | L | v | w | y | $y_1$ |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| mm | 1 | 0.05<br>0.00 | 0.30<br>0.18 | 0.2 | 3.1<br>2.9 | 1.65<br>1.35 | 2.6<br>2.4 | 1.15<br>0.85 | 0.5 | 2 | 0.5<br>0.3 | 0.1 | 0.05 | 0.05 | 0.1 |

**Note**

1. Plastic or metal protrusions of 0.075 mm maximum per side are not included.

| OUTLINE VERSION | REFERENCES | | | | EUROPEAN PROJECTION | ISSUE DATE |
|---|---|---|---|---|---|---|
| | IEC | JEDEC | JEITA | | | |
| SOT762-1 | - - - | MO-241 | - - - | | | ~~02-10-17~~<br>03-01-27 |

**DATA SHEET STATUS**

| LEVEL | DATA SHEET STATUS(1) | PRODUCT STATUS(2)(3) | DEFINITION |
|---|---|---|---|
| I | Objective data | Development | This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice. |
| II | Preliminary data | Qualification | This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product. |
| III | Product data | Production | This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). |

**Notes**

1. Please consult the most recently issued data sheet before initiating or completing a design.
2. The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL http://www.semiconductors.philips.com.
3. For data sheets describing multiple type numbers, the highest-level product status determines the data sheet status.

**DEFINITIONS**

**Short-form specification** — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

**Limiting values definition** — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

**Application information** — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

**DISCLAIMERS**

**Life support applications** — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

**Right to make changes** — Philips Semiconductors reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. When the product is in full production (status ‘Production’), relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no licence or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

# *Philips Semiconductors – a worldwide company*

**Contact information**

For additional information please visit **http://www.semiconductors.philips.com**. Fax: **+31 40 27 24825**
For sales offices addresses send e-mail to: **sales.addresses@www.semiconductors.philips.com**.

© Koninklijke Philips Electronics N.V. 2003 SCA75

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Printed in The Netherlands 613508/03/pp23 Date of release: 2003 Oct 30 Document order number: 9397 750 10497

Let's make things better.

Philips
Semiconductors

PHILIPS

TradeElectronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

## О компании

ООО "ТрейдЭлектроникс" - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Наличие собственной эффективной системы логистики обеспечивает надежную поставку продукции по конкурентным ценам в точно указанные сроки.

Срок поставки со стоков в **Европе и Америке – от 3 до 14 дней.**

Срок поставки из **Азии – от 10 дней.**

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Предоставляем спец цены на элементы для создания инженерных сэмплов.

**Упорный труд, качественный результат дают нам право быть уверенными в себе и надежными для наших клиентов.**

## Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование

Наша организация особенно сильна в поставках модулей, микросхем, пассивных компонентов, ксайленсах (XC), EPF, EPM и силовой электроники.

Большой выбор предлагаемой продукции, различные виды оплаты и доставки, позволят Вам сэкономить время и получить максимум выгоды от сотрудничества с нами!

Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

## Перечень производителей, продукцию которых мы поставляем на российский рынок



Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

С удовольствием будем прорабатывать для Вас поставки всех необходимых компонентов по текущим запросам для скорейшего выявления групп элементов, по которым сотрудничество именно с нашей компанией будет для Вас максимально выгодным!

С уважением,

Менеджер отдела продаж ООО

«Трейд Электроникс»

Шишлаков Евгений

8 (495)668-30-28 доб 169

manager28@tradeelectronics.ru

http://www.tradeelectronics.ru/