

# 74AC573, 74ACT573

## Octal Latch with 3-STATE Outputs

### Features

- $I_{CC}$  and  $I_{OZ}$  reduced by 50%
- Inputs and outputs on opposite sides of package allowing easy interface with microprocessors
- Useful as input or output port for microprocessors
- Functionally identical to 74AC373 and 74ACT373
- 3-STATE outputs for bus interfacing
- Outputs source/sink 24mA
- 74ACT573 has TTL-compatible inputs

### General Description

The 74AC573 and 74ACT573 are high-speed octal latches with buffered common Latch Enable (LE) and buffered common Output Enable ( $\overline{OE}$ ) inputs.

The 74AC573 and 74ACT573 are functionally identical to the 74AC373 and 74ACT373 but with inputs and outputs on opposite sides.

### Ordering Information

| Order Number                  | Package Number | Package Description                                                         |
|-------------------------------|----------------|-----------------------------------------------------------------------------|
| 74AC573SC                     | M20B           | 20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide  |
| 74AC573SJ                     | M20D           | 20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide               |
| 74AC573MTC                    | MTC20          | 20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide |
| 74ACT573SC                    | M20B           | 20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide  |
| 74ACT573SCX_NL <sup>(1)</sup> | M20B           | 20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide  |
| 74ACT573SJ                    | M20D           | 20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide               |
| 74ACT573MTC                   | MTC20          | 20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide |
| 74ACT573PC                    | N20A           | 20-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide      |



Device also available in Tape and Reel. Specify by appending suffix letter "X" to the ordering number.

Pb-Free package per JEDEC J-STD-020B.


#### Note:

1. Device available in Tape and Reel only.

## Logic Symbols



## Connection Diagram



## Pin Descriptions

| Pin Names                      | Description                 |
|--------------------------------|-----------------------------|
| D <sub>0</sub> –D <sub>7</sub> | Data Inputs                 |
| LE                             | Latch Enable Input          |
| $\overline{OE}$                | 3-STATE Output Enable Input |
| O <sub>0</sub> –O <sub>7</sub> | 3-STATE Latch Outputs       |

## Truth Table

| Inputs          |    |   | Outputs        |
|-----------------|----|---|----------------|
| $\overline{OE}$ | LE | D | O <sub>n</sub> |
| L               | H  | H | H              |
| L               | H  | L | L              |
| L               | L  | X | O <sub>0</sub> |
| H               | X  | X | Z              |

H = HIGH Voltage

L = LOW Voltage

Z = High Impedance


X = Immaterial

O<sub>0</sub> = Previous O<sub>0</sub> before HIGH-to-LOW transition of Latch Enable

## Functional Description

The 74AC573 and 74ACT573 contain eight D-type latches with 3-STATE output buffers. When the Latch Enable (LE) input is HIGH, data on the D<sub>n</sub> inputs enters the latches. In this condition the latches are transparent, i.e., a latch output will change state each time its D-type input changes. When LE is LOW the latches store the information that was present on the D-type inputs a setup time preceding the HIGH-to-LOW transition of LE. The 3-STATE buffers are controlled by the Output Enable ( $\overline{OE}$ ) input. When  $\overline{OE}$  is LOW, the buffers are enabled. When  $\overline{OE}$  is HIGH the buffers are in the high impedance mode but this does not interfere with entering new data into the latches.

# Logic Diagram



Please note that this diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

## Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

| Symbol                | Parameter                                                         | Rating                   |
|-----------------------|-------------------------------------------------------------------|--------------------------|
| $V_{CC}$              | Supply Voltage                                                    | −0.5V to +7.0V           |
| $I_{IK}$              | DC Input Diode Current<br>$V_I = -0.5V$<br>$V_I = V_{CC} + 0.5V$  | −20mA<br>+20mA           |
| $V_I$                 | DC Input Voltage                                                  | −0.5V to $V_{CC} + 0.5V$ |
| $I_{OK}$              | DC Output Diode Current<br>$V_O = -0.5V$<br>$V_O = V_{CC} + 0.5V$ | −20mA<br>+20mA           |
| $V_O$                 | DC Output Voltage                                                 | −0.5V to $V_{CC} + 0.5V$ |
| $I_O$                 | DC Output Source or Sink Current                                  | ±50mA                    |
| $I_{CC}$ or $I_{GND}$ | DC $V_{CC}$ or Ground Current per Output Pin                      | ±50mA                    |
| $T_{STG}$             | Storage Temperature                                               | −65°C to +150°C          |
| $T_J$                 | Junction Temperature                                              | 140°C                    |

## Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. Fairchild does not recommend exceeding them or designing to absolute maximum ratings.

| Symbol                | Parameter                                                                                                  | Rating                       |
|-----------------------|------------------------------------------------------------------------------------------------------------|------------------------------|
| $V_{CC}$              | Supply Voltage<br>AC<br>ACT                                                                                | 2.0V to 6.0V<br>4.5V to 5.5V |
| $V_I$                 | Input Voltage                                                                                              | 0V to $V_{CC}$               |
| $V_O$                 | Output Voltage                                                                                             | 0V to $V_{CC}$               |
| $T_A$                 | Operating Temperature                                                                                      | −40°C to +85°C               |
| $\Delta V / \Delta t$ | Minimum Input Edge Rate, AC Devices:<br>$V_{IN}$ from 30% to 70% of $V_{CC}$ , $V_{CC}$ @ 3.0V, 4.5V, 5.5V | 125mV/ns                     |
| $\Delta V / \Delta t$ | Minimum Input Edge Rate, ACT Devices:<br>$V_{IN}$ from 0.8V to 2.0V, $V_{CC}$ @ 4.5V, 5.5V                 | 125mV/ns                     |

## DC Electrical Characteristics for AC

| Symbol                         | Parameter                                     | V <sub>CC</sub> (V) | Conditions                                                                                                                                     | T <sub>A</sub> = +25°C |                   | T <sub>A</sub> = −40°C to +85°C |      | Units |
|--------------------------------|-----------------------------------------------|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|-------------------|---------------------------------|------|-------|
|                                |                                               |                     |                                                                                                                                                | Typ.                   | Guaranteed Limits |                                 |      |       |
| V <sub>IH</sub>                | Minimum HIGH Level Input Voltage              | 3.0                 | V <sub>OUT</sub> = 0.1V or V <sub>CC</sub> − 0.1V                                                                                              | 1.5                    | 2.1               | 2.1                             |      | V     |
|                                |                                               | 4.5                 |                                                                                                                                                | 2.25                   | 3.15              | 3.15                            |      |       |
|                                |                                               | 5.5                 |                                                                                                                                                | 2.75                   | 3.85              | 3.85                            |      |       |
| V <sub>IL</sub>                | Maximum LOW Level Input Voltage               | 3.0                 | V <sub>OUT</sub> = 0.1V or V <sub>CC</sub> − 0.1V                                                                                              | 1.5                    | 0.9               | 0.9                             |      | V     |
|                                |                                               | 4.5                 |                                                                                                                                                | 2.25                   | 1.35              | 1.35                            |      |       |
|                                |                                               | 5.5                 |                                                                                                                                                | 2.75                   | 1.65              | 1.65                            |      |       |
| V <sub>OH</sub>                | Minimum HIGH Level Output Voltage             | 3.0                 | I <sub>OUT</sub> = −50μA                                                                                                                       | 2.99                   | 2.9               | 2.9                             |      | V     |
|                                |                                               | 4.5                 |                                                                                                                                                | 4.49                   | 4.4               | 4.4                             |      |       |
|                                |                                               | 5.5                 |                                                                                                                                                | 5.49                   | 5.4               | 5.4                             |      |       |
|                                |                                               | 3.0                 | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> :<br>I <sub>OH</sub> = −12mA                                                              |                        |                   | 2.56                            | 2.46 | V     |
|                                |                                               | 4.5                 | I <sub>OH</sub> = −24mA                                                                                                                        |                        |                   | 3.86                            | 3.76 |       |
|                                |                                               | 5.5                 | I <sub>OH</sub> = −24mA <sup>(2)</sup>                                                                                                         |                        |                   | 4.86                            | 4.76 |       |
|                                |                                               |                     |                                                                                                                                                |                        |                   |                                 |      |       |
| V <sub>OL</sub>                | Maximum LOW Level Output Voltage              | 3.0                 | I <sub>OUT</sub> = 50μA                                                                                                                        | 0.002                  | 0.1               | 0.1                             |      | V     |
|                                |                                               | 4.5                 |                                                                                                                                                | 0.001                  | 0.1               | 0.1                             |      |       |
|                                |                                               | 5.5                 |                                                                                                                                                | 0.001                  | 0.1               | 0.1                             |      |       |
|                                |                                               | 3.0                 | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> :<br>I <sub>OL</sub> = 12mA                                                               |                        |                   | 0.36                            | 0.44 |       |
|                                |                                               | 4.5                 | I <sub>OL</sub> = 24mA                                                                                                                         |                        |                   | 0.36                            | 0.44 |       |
|                                |                                               | 5.5                 | I <sub>OL</sub> = 24mA <sup>(2)</sup>                                                                                                          |                        |                   | 0.36                            | 0.44 |       |
| I <sub>IN</sub> <sup>(3)</sup> | Maximum Input Leakage Current                 | 5.5                 | V <sub>I</sub> = V <sub>CC</sub> , GND                                                                                                         |                        | ±0.1              | ±1.0                            |      | μA    |
| I <sub>OLD</sub>               | Minimum Dynamic Output Current <sup>(4)</sup> | 5.5                 | V <sub>OLD</sub> = 1.65V Max.                                                                                                                  |                        |                   | 75                              |      | mA    |
| I <sub>OHD</sub>               |                                               | 5.5                 | V <sub>OHD</sub> = 3.85V Min.                                                                                                                  |                        |                   | −75                             |      | mA    |
| I <sub>CC</sub> <sup>(3)</sup> | Maximum Quiescent Supply Current              | 5.5                 | V <sub>IN</sub> = V <sub>CC</sub> or GND                                                                                                       |                        | 4.0               | 40.0                            |      | μA    |
| I <sub>OZ</sub>                | Maximum 3-STATE Leakage Current               | 5.5                 | V <sub>I</sub> (OE) = V <sub>IL</sub> , V <sub>IH</sub> ;<br>V <sub>I</sub> = V <sub>CC</sub> , GND;<br>V <sub>O</sub> = V <sub>CC</sub> , GND |                        | ±0.25             | ±2.5                            |      | μA    |

## Notes:

2. All outputs loaded; thresholds on input associated with output under test.
3.  $I_{IN}$  and  $I_{CC}$  @ 3.0V are guaranteed to be less than or equal to the respective limit @ 5.5V  $V_{CC}$ .
4. Maximum test duration 2.0ms, one output loaded at a time.

**DC Electrical Characteristics for ACT**

| Symbol           | Parameter                                     | V <sub>CC</sub> (V) | Conditions                                                                                     | T <sub>A</sub> = +25°C |                   | T <sub>A</sub> = −40°C to +85°C |  | Units |
|------------------|-----------------------------------------------|---------------------|------------------------------------------------------------------------------------------------|------------------------|-------------------|---------------------------------|--|-------|
|                  |                                               |                     |                                                                                                | Typ.                   | Guaranteed Limits |                                 |  |       |
| V <sub>IH</sub>  | Minimum HIGH Level Input Voltage              | 4.5                 | V <sub>OUT</sub> = 0.1V or V <sub>CC</sub> − 0.1V                                              | 1.5                    | 2.0               | 2.0                             |  | V     |
|                  |                                               | 5.5                 |                                                                                                | 1.5                    | 2.0               | 2.0                             |  |       |
| V <sub>IL</sub>  | Maximum LOW Level Input Voltage               | 4.5                 | V <sub>OUT</sub> = 0.1V or V <sub>CC</sub> − 0.1V                                              | 1.5                    | 0.8               | 0.8                             |  | V     |
|                  |                                               |                     |                                                                                                | 5.5                    | 1.5               | 0.8                             |  |       |
| V <sub>OH</sub>  | Minimum HIGH Level Output Voltage             | 4.5                 | I <sub>OUT</sub> = −50 μA                                                                      | 4.49                   | 4.4               | 4.4                             |  | V     |
|                  |                                               | 5.5                 |                                                                                                | 5.49                   | 5.4               | 5.4                             |  |       |
|                  |                                               | 4.5                 | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> ;<br>I <sub>OH</sub> = −24mA              |                        | 3.86              | 3.76                            |  |       |
|                  |                                               | 5.5                 | I <sub>OH</sub> = −24mA <sup>(5)</sup>                                                         |                        | 4.86              | 4.76                            |  |       |
| V <sub>OL</sub>  | Maximum LOW Level Output Voltage              | 4.5                 | I <sub>OUT</sub> = 50 μA                                                                       | 0.001                  | 0.1               | 0.1                             |  | V     |
|                  |                                               | 5.5                 |                                                                                                | 0.001                  | 0.1               | 0.1                             |  |       |
|                  |                                               | 4.5                 | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> ;<br>I <sub>OL</sub> = 24mA               |                        | 0.36              | 0.44                            |  |       |
|                  |                                               | 5.5                 | I <sub>OL</sub> = 24mA <sup>(5)</sup>                                                          |                        | 0.36              | 0.44                            |  |       |
| I <sub>IN</sub>  | Maximum Input Leakage Current                 | 5.5                 | V <sub>I</sub> = V <sub>CC</sub> , GND                                                         |                        | ±0.1              | ±1.0                            |  | μA    |
| I <sub>OZ</sub>  | Maximum 3-STATE Leakage Current               | 5.5                 | V <sub>I</sub> = V <sub>IL</sub> , V <sub>IH</sub> ;<br>V <sub>O</sub> = V <sub>CC</sub> , GND |                        | ±0.25             | ±2.5                            |  | μA    |
| I <sub>CCT</sub> | Maximum I <sub>CC</sub> /Input                | 5.5                 | V <sub>I</sub> = V <sub>CC</sub> − 2.1V                                                        | 0.6                    |                   | 1.5                             |  | mA    |
| I <sub>OLD</sub> | Minimum Dynamic Output Current <sup>(6)</sup> | 5.5                 | V <sub>OLD</sub> = 1.65V Max.                                                                  |                        |                   | 75                              |  | mA    |
| I <sub>OHD</sub> |                                               | 5.5                 | V <sub>OHD</sub> = 3.85V Min.                                                                  |                        |                   | −75                             |  | mA    |
| I <sub>CC</sub>  | Maximum Quiescent Supply Current              | 5.5                 | V <sub>IN</sub> = V <sub>CC</sub> or GND                                                       |                        | 4.0               | 40.0                            |  | μA    |

**Notes:**

5. All outputs loaded; thresholds on input associated with output under test.  
 6. Maximum test duration 2.0ms, one output loaded at a time.

**AC Electrical Characteristics for AC**

| Symbol           | Parameter                                              | V <sub>CC</sub> (V) <sup>(7)</sup> | T <sub>A</sub> = +25°C,<br>C <sub>L</sub> = 50pF |      |      | T <sub>A</sub> = -40°C to +85°C,<br>C <sub>L</sub> = 50pF |      | Units |
|------------------|--------------------------------------------------------|------------------------------------|--------------------------------------------------|------|------|-----------------------------------------------------------|------|-------|
|                  |                                                        |                                    | Min.                                             | Typ. | Max. | Min.                                                      | Max. |       |
| t <sub>PHL</sub> | Propagation Delay,<br>D <sub>n</sub> to O <sub>n</sub> | 3.3                                | 0.5                                              | 8.5  | 10.5 | 2.5                                                       | 11.0 | ns    |
| t <sub>PLH</sub> |                                                        | 5.0                                | 1.5                                              | 5.5  | 7.0  | 1.5                                                       | 7.5  |       |
| t <sub>PLH</sub> | Propagation Delay,<br>LE to O <sub>n</sub>             | 3.3                                | 2.5                                              | 8.5  | 12.0 | 2.5                                                       | 12.5 | ns    |
| t <sub>PHL</sub> |                                                        | 5.0                                | 2.0                                              | 6.0  | 8.0  | 2.0                                                       | 8.5  |       |
| t <sub>PZL</sub> | Output Enable Time                                     | 3.3                                | 2.5                                              | 8.5  | 13.0 | 2.5                                                       | 13.5 | ns    |
| t <sub>PZH</sub> |                                                        | 5.0                                | 1.5                                              | 6.0  | 8.5  | 1.5                                                       | 9.0  |       |
| t <sub>PHZ</sub> | Output Disable Time                                    | 3.3                                | 1.0                                              | 9.0  | 14.5 | 1.0                                                       | 15.0 | ns    |
| t <sub>PLZ</sub> |                                                        | 5.0                                | 1.0                                              | 6.0  | 9.5  | 1.0                                                       | 10.0 |       |

**Note:**

7. Voltage range 5.0 is 5.0V ± 0.5V. Voltage range 3.3 is 3.3V ± 0.3V.

**AC Operating Requirements for AC**

| Symbol         | Parameter                                        | V <sub>CC</sub> (V) <sup>(8)</sup> | T <sub>A</sub> = +25°C,<br>C <sub>L</sub> = 50pF |                    | T <sub>A</sub> = −40°C to +85°C,<br>C <sub>L</sub> = 50pF | Units |
|----------------|--------------------------------------------------|------------------------------------|--------------------------------------------------|--------------------|-----------------------------------------------------------|-------|
|                |                                                  |                                    | Typ.                                             | Guaranteed Minimum |                                                           |       |
| t <sub>S</sub> | Setup Time, HIGH or LOW,<br>D <sub>n</sub> to LE | 3.3                                | 0                                                | 3.0                | 3.0                                                       | ns    |
|                |                                                  | 5.0                                | 0                                                | 3.0                | 3.0                                                       |       |
| t <sub>H</sub> | Hold Time, HIGH or LOW,<br>D <sub>n</sub> to LE  | 3.3                                | 0                                                | 1.5                | 1.5                                                       | ns    |
|                |                                                  | 5.0                                | 0                                                | 1.5                | 1.5                                                       |       |
| t <sub>W</sub> | LE Pulse Width, HIGH                             | 3.3                                | 2.0                                              | 4.0                | 4.0                                                       | ns    |
|                |                                                  | 5.0                                | 2.0                                              | 4.0                | 4.0                                                       |       |

**Note:**

8. Voltage range 5.0 is 5.0V ± 0.5V. Voltage range 3.3 is 3.3V ± 0.3V.

**AC Electrical Characteristics for ACT**

| Symbol    | Parameter                            | $V_{CC} (V)^{(9)}$ | $T_A = +25^{\circ}C,$<br>$C_L = 50pF$ |      |      | $T_A = -40^{\circ}C \text{ to } +85^{\circ}C,$<br>$C_L = 50pF$ |      | Units |
|-----------|--------------------------------------|--------------------|---------------------------------------|------|------|----------------------------------------------------------------|------|-------|
|           |                                      |                    | Min.                                  | Typ. | Max. | Min.                                                           | Max. |       |
| $t_{PLH}$ | Propagation Delay,<br>$D_n$ to $O_n$ | 5.0                | 2.5                                   | 6.0  | 10.5 | 2.0                                                            | 12.0 | ns    |
| $t_{PHL}$ |                                      |                    |                                       |      |      |                                                                |      |       |
| $t_{PLH}$ | Propagation Delay,<br>LE to $O_n$    | 5.0                | 3.0                                   | 6.0  | 10.5 | 2.5                                                            | 12.0 | ns    |
| $t_{PHL}$ | Propagation Delay,<br>LE to $O_n$    | 5.0                | 2.5                                   | 5.5  | 9.5  | 2.0                                                            | 10.5 | ns    |
| $t_{PZH}$ | Output Enable Time                   | 5.0                | 2.0                                   | 5.5  | 10.0 | 1.5                                                            | 11.0 | ns    |
| $t_{PZL}$ | Output Enable Time                   | 5.0                | 1.5                                   | 5.5  | 9.5  | 1.5                                                            | 10.5 | ns    |
| $t_{PHZ}$ | Output Disable Time                  | 5.0                | 2.5                                   | 6.5  | 11.0 | 1.5                                                            | 12.5 | ns    |
| $t_{PLZ}$ | Output Disable Time                  | 5.0                | 1.5                                   | 5.0  | 8.5  | 1.0                                                            | 9.5  | ns    |

**Note:**

9. Voltage range 5.0 is  $5.0V \pm 0.5V$ .

**AC Operating Requirements for ACT**

| Symbol         | Parameter                                        | V <sub>CC</sub> (V) <sup>(10)</sup> | T <sub>A</sub> = +25°C,<br>C <sub>L</sub> = 50pF |                    | T <sub>A</sub> = −40°C to +85°C,<br>C <sub>L</sub> = 50pF | Units |
|----------------|--------------------------------------------------|-------------------------------------|--------------------------------------------------|--------------------|-----------------------------------------------------------|-------|
|                |                                                  |                                     | Typ.                                             | Guaranteed Minimum |                                                           |       |
| t <sub>S</sub> | Setup Time, HIGH or LOW,<br>D <sub>n</sub> to LE | 5.0                                 | 1.5                                              | 3.0                | 3.5                                                       | ns    |
| t <sub>H</sub> | Hold Time, HIGH or LOW,<br>D <sub>n</sub> to LE  | 5.0                                 | −1.5                                             | 0                  | 0                                                         | ns    |
| t <sub>W</sub> | LE Pulse Width, HIGH                             | 5.0                                 | 2.0                                              | 3.5                | 4.0                                                       | ns    |

**Note:**

10. Voltage range 5.0 is  $5.0V \pm 0.5V$ .

**Capacitance**

| Symbol   | Parameter                     | Conditions             | Typ. | Units |
|----------|-------------------------------|------------------------|------|-------|
| $C_{IN}$ | Input Capacitance             | $V_{CC} = \text{OPEN}$ | 5.0  | pF    |
| $C_{PD}$ | Power Dissipation Capacitance | $V_{CC} = 5.0V$        | 25.0 | pF    |
|          | AC<br>ACT                     |                        | 42.0 |       |

## Physical Dimensions

Dimensions are in inches (millimeters) unless otherwise noted.






Figure 1. 20-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-013, 0.300" Wide Package Number M20B

### Physical Dimensions (Continued)



Dimensions are in millimeters unless otherwise noted.



LAND PATTERN RECOMMENDATION



DIMENSIONS ARE IN MILLIMETERS



### DETAIL A

NOTES:



- NOTES:
- A. CONFORMS TO EIAJ EDR-7320 REGISTRATION, ESTABLISHED IN DECEMBER, 1998.
  - B. DIMENSIONS ARE IN MILLIMETERS.
  - C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.

M20DREVC



**Figure 2. 20-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide  
Package Number M20D**

# Physical Dimensions (Continued)

Dimensions are in millimeters unless otherwise noted.



DIMENSIONS ARE IN MILLIMETERS



DETAIL A

## NOTES:


- CONFORMS TO JEDEC REGISTRATION MO-153, VARIATION AC, REF NOTE 6, DATE 7/93.
- DIMENSIONS ARE IN MILLIMETERS.
- DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLDS FLASH, AND TIE BAR EXTRUSIONS.
- DIMENSIONS AND TOLERANCES PER ANSI Y14.5M, 1982.

MTC20REV D1

**Figure 3. 20-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide Package Number MTC20**

**Physical Dimensions (Continued)**

Dimensions are in inches (millimeters) unless otherwise noted.



N20A (REV G)

**Figure 4. 20-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide Package Number N20A**



## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

|                                                   |                                 |                                                                                                 |                              |
|---------------------------------------------------|---------------------------------|-------------------------------------------------------------------------------------------------|------------------------------|
| ACE <sup>x</sup>                                  | HiSeC <sup>TM</sup>             | Programmable Active Droop <sup>TM</sup>                                                         | TinyLogic <sup>®</sup>       |
| Across the board. Around the world. <sup>TM</sup> | <i>i-Lo</i> <sup>TM</sup>       | QFET <sup>®</sup>                                                                               | TINYOPTO <sup>TM</sup>       |
| ActiveArray <sup>TM</sup>                         | ImpliedDisconnect <sup>TM</sup> | QS <sup>TM</sup>                                                                                | TinyPower <sup>TM</sup>      |
| Bottomless <sup>TM</sup>                          | IntelliMAX <sup>TM</sup>        | QT Optoelectronics <sup>TM</sup>                                                                | TinyWire <sup>TM</sup>       |
| Build it Now <sup>TM</sup>                        | ISOPLANAR <sup>TM</sup>         | Quiet Series <sup>TM</sup>                                                                      | TruTranslation <sup>TM</sup> |
| CoolFET <sup>TM</sup>                             | MICROCOUPLER <sup>TM</sup>      | RapidConfigure <sup>TM</sup>                                                                    | μSerDes <sup>TM</sup>        |
| CROSSVOLT <sup>TM</sup>                           | MicroPak <sup>TM</sup>          | RapidConnect <sup>TM</sup>                                                                      | UHC <sup>®</sup>             |
| CTL <sup>TM</sup>                                 | MICROWIRE <sup>TM</sup>         | ScalarPump <sup>TM</sup>                                                                        | UniFET <sup>TM</sup>         |
| Current Transfer Logic <sup>TM</sup>              | MSX <sup>TM</sup>               | SMART START <sup>TM</sup>                                                                       | VCX <sup>TM</sup>            |
| DO <sup>TM</sup>                                  | MSXPro <sup>TM</sup>            | SPM <sup>®</sup>                                                                                | Wire <sup>TM</sup>           |
| E <sup>2</sup> CMOS <sup>TM</sup>                 | OCX <sup>TM</sup>               | STEALTH <sup>TM</sup>                                                                           |                              |
| EcoSPARK <sup>®</sup>                             | OCXPro <sup>TM</sup>            | SuperFET <sup>TM</sup>                                                                          |                              |
| EnSigna <sup>TM</sup>                             | OPTOLOGIC <sup>®</sup>          | SuperSOT <sup>TM</sup> -3                                                                       |                              |
| FACT Quiet Series <sup>TM</sup>                   | OPTOPLANAR <sup>®</sup>         | SuperSOT <sup>TM</sup> -6                                                                       |                              |
| FACT <sup>®</sup>                                 | PACMAN <sup>TM</sup>            | SuperSOT <sup>TM</sup> -8                                                                       |                              |
| FAST <sup>®</sup>                                 | POP <sup>TM</sup>               | SyncFET <sup>TM</sup>                                                                           |                              |
| FASTr <sup>TM</sup>                               | Power220 <sup>®</sup>           | TCM <sup>TM</sup>                                                                               |                              |
| FPS <sup>TM</sup>                                 | Power247 <sup>®</sup>           | The Power Franchise <sup>®</sup>                                                                |                              |
| FRFET <sup>®</sup>                                | PowerEdge <sup>TM</sup>         |  <sup>TM</sup> |                              |
| GlobalOptoisolator <sup>TM</sup>                  | PowerSaver <sup>TM</sup>        | TinyBoost <sup>TM</sup>                                                                         |                              |
| GTO <sup>TM</sup>                                 | PowerTrench <sup>®</sup>        | TinyBuck <sup>TM</sup>                                                                          |                              |

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status         | Definition                                                                                                                                                                                               |
|--------------------------|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                       |
| Preliminary              | First Production       | This datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production        | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.                                                   |
| Obsolete                 | Not In Production      | This datasheet contains specifications on a product that has been discontinued by Fairchild Semiconductor. The datasheet is printed for reference information only.                                      |

Rev. 124



## О компании

ООО "ТрейдЭлектроникс" - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Наличие собственной эффективной системы логистики обеспечивает надежную поставку продукции по конкурентным ценам в точно указанные сроки.

Срок поставки со стоков в **Европе и Америке – от 3 до 14 дней.**

Срок поставки из **Азии – от 10 дней.**

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Предоставляем спец цены на элементы для создания инженерных сэмплов.

**Упорный труд, качественный результат дают нам право быть уверенными в себе и надежными для наших клиентов.**

### Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование

Наша организация особенно сильна в поставках модулей, микросхем, пассивных компонентов, ксайленсах (XC), EPF, EPM и силовой электроники.

Большой выбор предлагаемой продукции, различные виды оплаты и доставки, позволят Вам сэкономить время и получить максимум выгоды от сотрудничества с нами!

## Перечень производителей, продукцию которых мы поставляем на российский рынок





Trade Electronics.ru

гарантия бесперебойности производства и  
качества выпускаемой продукции

С удовольствием будем прорабатывать для Вас поставки всех необходимых компонентов по текущим запросам для скорейшего выявления групп элементов, по которым сотрудничество именно с нашей компанией будет для Вас максимально выгодным!

С уважением,

Менеджер отдела продаж ООО

«Трейд Электроникс»

Шишлаков Евгений

8 (495)668-30-28 доб 169

manager28@tradeelectronics.ru

<http://www.tradeelectronics.ru/>