
74VCX163245

16-BIT DUAL SUPPLY BUS TRANSCEIVER LEVEL TRANSLATOR

TARGET DATA

- HIGH SPEED: t_{PD} = 4.4ns (MAX.) at T_A=85°C
  V_{CCA} = 3.0V V_{CCB} = 2.3V
- LOW POWER DISSIPATION:
  $I_{CCA} = I_{CCB}$ = 20µA(MAX.) at T_A=85°C
- SYMMETRICAL OUTPUT IMPEDANCE:
  $|I_{OHA}| = I_{OLA}$ = 12mA MIN at
  V_{CCA} = 3.0V V_{CCB} = 1.65V or 2.3V
  $|I_{OHA}| = I_{OLA}$ = 8mA MIN at
  V_{CCA} = 2.3V V_{CCB} = 1.65V)
- BALANCED PROPAGATION DELAYS:
  $t_{PLH} \cong t_{PHL}$
- POWER DOWN PROTECTION ON INPUTS AND OUTPUTS
- OPERATING VOLTAGE RANGE:
  V_{CCA}(OPR) = 2.3V to 3.6V (1.2V Data Retention)
  V_{CCB}(OPR) = 1.65V to 2.7V (1.2V Data Retention)
- PIN AND FUNCTION COMPATIBLE WITH 74 SERIES 16245
- LATCH-UP PERFORMANCE EXCEEDS 500mA (JESD 17)
- ESD PERFORMANCE:
  HBM > 2000V (MIL STD 883 method 3015);
  MM > 200V




TSSOP **TFBGA** **µTFBGA**

ORDER CODES

PACKAGE	TRAY	T & R
TSSOP48		74VCX163245TTR
TFBGA54	74VCX163245LB	74VCX163245LBR
µTFBGA42	74VCX163245TB	74VCX163245TBR

LOGIC DIAGRAM



DESCRIPTION


The 74VCX163245 is a dual supply low voltage CMOS 16-BIT BUS TRANSCEIVER fabricated with sub-micron silicon gate and five-layer metal wiring C^2MOS technology. Designed for use as an interface between a 3.3V bus and a 2.5V or 1.8V bus in a mixed 3.3V/1.8V,3.3V/2.5V and 2.5V/1.8V supply systems, it achieves high speed operation while maintaining the CMOS low power dissipation.

This IC is intended for two-way asynchronous communication between data buses and the direction of data transmission is determined by nDIR inputs. The enable inputs $\overline{nOE}$ can be used to disable the device so that the buses are effectively isolated. The A-port interfaces with the 3V bus, the B-port with the 2.5V and 1.8V bus.

All inputs are equipped with protection circuits against static discharge, giving them 2KV ESD immunity and transient excess voltage. All floating bus terminals during High Z State must be held HIGH or LOW.

This is preliminary information on a new product foreseen to be developed. Details are subject to change without notice.


INPUT AND OUTPUT EQUIVALENT CIRCUIT



PIN DESCRIPTION

TFBGA54 PIN N°	μTFBGA42 PIN N°	TSSOP PIN N°	SYMBOL	NAME AND FUNCTION
A3	B3	1	1DIR	Directional Controls
J3	F3	24	2DIR	Directional Controls
A6, B5, B6, C5, C6, D5, D6, E5	A4, A5, A6, B5, B6, C5, C6, D5	47, 46, 44, 43, 41, 40, 38, 37	1A1 to 1A8	Data Inputs/Outputs
E6, F5, F6, G5, G6, H5, H6, J6	D6, E5, E6, F5, F6,G4, G5, G6	36, 35, 33, 32, 30, 29, 27, 26	2A1 to 2A8	Data Inputs/Outputs
A1, B2, B1, C2, C1, D2, D1, E2	A3, A2, A1, B2, B1, C2, C1, D2	2, 3, 5, 6, 8, 9, 11, 12	1B1 to 1B8	Data Inputs/Outputs
E1, F2, F1, G2, G1, H2, H1, J1	D1, E2, E1, F2, F1,G3, G2, G1	13, 14, 16, 17, 19, 20, 22, 23	2B1 to 2B8	Data Inputs/Outputs
J4	F4	25	$\overline{G}2$	Output Enable Inputs
A4	B4	48	$\overline{G}1$	Output Enable Inputs
D3, D4, E3, E4, F3, F4	C3, C4, E3, E4	4,10,15, 21, 28, 34, 39, 45	GND	Ground (0V)
A2, A5, B3, B4, H3, H4, J2, J5	-	-	NC	No Connected
C4, G4	D4	42, 31	V_{CCA}	Positive Supply Voltage
C3, G3	D3	7, 18	V_{CCB}	Positive Supply Voltage

PIN CONNECTION (top view for TSSOP, bottom view for BGA)



TRUTH TABLE

INPUTS		FUNCTION		OUTPUT
$\overline{G}$	DIR	A BUS	B BUS	
L	L	OUTPUT	INPUT	A = B
L	H	INPUT	OUTPUT	B = A
H	X	Z	Z	Z

X=Don't care; Z=High Impedance

ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V_{CCA}	Supply Voltage	-0.5 to +4.6	V
V_{CCB}	Supply Voltage	-0.5 to +4.6	V
V_I	DC Input Voltage	-0.5 to +4.6	V
$V_{I/OA}$	DC I/O Voltage (Output disabled)	-0.5 to +4.6	V
$V_{I/OB}$	DC I/O Voltage (Output disabled)	-0.5 to +4.6	V
$V_{I/OA}$	DC I/O Voltage	-0.5 to V_{CCA} + 0.5	V
$V_{I/OB}$	DC I/O Voltage	-0.5 to V_{CCB} + 0.5	V
I_{IK}	DC Input Diode Current	– 20	mA
I_{OK}	DC Output Diode Current	– 50	mA
I_{OA}	DC Output Current	± 50	mA
I_{OB}	DC Output Current	± 50	mA
I_{CCA}	DC V_{CC} or Ground Current	± 100	mA
I_{CCB}	DC V_{CC} or Ground Current	± 100	mA
P_d	Power Dissipation	400	mW
T_{stg}	Storage Temperature	-65 to +150	°C
T_L	Lead Temperature (10 sec)	300	°C

Absolute Maximum Rating are those value beyond which damage to the device may occur. Functional operation under these condition is not implied
(*) 500mW: ≅ 65°C derated to 300mW by 10mW/°C: 65°C to 85°C

RECOMMENDED OPERATING CONDITIONS

Symbol	Parameter	Value	Unit
V_{CCA}	Supply Voltage	2.3 to 3.6	V
V_{CCB}	Supply Voltage	1.65 to 2.7	V
V_I	Input Voltage (Dir, $\overline{OE}$)	0 to V_{CCB}	V
$V_{I/OA}$	I/O Voltage	0 to V_{CCA}	V
$V_{I/OB}$	I/O Voltage	0 to V_{CCB}	V
T_{op}	Operating Temperature	-40 to 85	°C
dt/dv	Input Rise and Fall Time (note 1)	0 to 10	ns/V

1) V_{IN} from 0.8V to 2.0V at V_{CC} =3.0V

DC SPECIFICATION FOR V_{CCA}

Symbol	Parameter	Test Condition			Value					Unit
		V_{CCB} (*) (V)	V_{CCA} (*) (V)		T_A = 25 °C			-40 to 85 °C		
					Min.	Typ.	Max.	Min.	Max.	
V_{IHA}	High Level Input Voltage (An)	1.8	2.5		1.6			1.6		V
		1.8	3.3		2.0			2.0		
		2.5	3.3		2.0			2.0		
V_{ILA}	Low Level Input Voltage (An)	1.8	2.5				0.7		0.7	V
		1.8	3.3				0.8		0.8	
		2.5	3.3				0.8		0.8	
V_{OHA}	High Level Output Voltage	2.3	3.0	I_O=-100 µA	2.8			2.8		V
		2.3	3.0	I_O=-24 mA	2.2			2.2		
		1.65	3.0	I_O=-24 mA	2.2			2.2		
		1.65	2.3	I_O=-18 mA	1.7			1.7		
V_{OLA}	Low Level Output Voltage	2.3	3.0	I_O=100 µA			0.2		0.2	V
		2.3	3.0	I_O=24 mA			0.55		0.55	
		1.65	3.0	I_O=24 mA			0.55		0.55	
		1.65	2.3	I_O=18 mA			0.60		0.60	
I_{IA}	Input Leakage Current	2.7	3.6	$V_I = V_{CC}$ or GND			± 0.5		± 5	µA
I_{OZA}	High Impedance Output Leakage Current	2.7	3.6	V_{IA} = Gnd or 3.6V $V_{IB} = V_{IHB}$ or V_{ILB} $\overline{OE} = V_{CCB}$			± 1.0		± 10	µA
$I_{IA(HOLD)}$	Input Hold Current	1.65	2.3	V_I = 0.57V	25			25		µA
		1.65	2.3	V_I = 1.07V	-25			-25		
		1.65	3.0	V_I = 0.57V	25			25		µA
		1.65	3.0	V_I = 1.07V	-25			-25		
		2.3	3.0	V_I = 0.7V	45			45		µA
		2.3	3.0	V_I = 1.6V	-45			-45		
		2.7	3.6	V_{IB} = 0 to 2.7V					± 300	
I_{OFF}	Power Off Leakage Current	0	0	V_{IA} = Gnd to 3.6V V_{IB} = Gnd to 3.6V $\overline{G}$, Dir = GND to 3.6V			± 1.0		± 10	µA
I_{CCtA}	Quiescent Supply Current	1.95	3.6	$V_{IA} = V_{CCA}$ or GND $V_{IB} = V_{CCB}$ or GND			2		20	µA
		1.95	2.7							
		2.7	3.6							
ΔI_{CCtA}	Maximum Quiescent Supply Current / Input (An)	2.7	3.6	$V_{IA} = V_{CCA}$ - 0.6V $V_{IB} = V_{CCB}$ or GND					0.75	mA
		1.95	3.6							
		1.95	2.7							

DC SPECIFICATION FOR V_{CCB}

Symbol	Parameter	Test Condition			Value					Unit
		V_{CCB} (V) (*)	V_{CCA} (V) (*)		T_A = 25 °C			-40 to 85 °C		
					Min.	Typ.	Max.	Min.	Max.	
V_{IHB}	High Level Input Voltage (Bn, Dir, $\overline{OE}$)	1.8	2.5		$0.65V_{CCB}$			$0.65V_{CCB}$		V
		1.8	3.3		$0.65V_{CCB}$			$0.65V_{CCB}$		
		2.5	3.3		1.6			1.6		
V_{ILB}	Low Level Input Voltage (Bn, Dir, $\overline{OE}$)	1.8	2.5				$0.35V_{CCB}$		$0.35V_{CCB}$	V
		1.8	3.3				$0.35V_{CCB}$		$0.35V_{CCB}$	
		2.5	3.3				0.7		0.7	
V_{OHB}	High Level Output Voltage	2.3	3.0	I_O=-100 µA	2.8			2.8		V
		2.3	3.0	I_O=-18 mA	1.7			1.7		
		1.65	3.0	I_O=-6 mA	1.25			1.25		
		1.65	2.3	I_O=-6 mA	1.25			1.25		
V_{OLB}	Low Level Output Voltage	2.3	3.0	I_O=100 µA			0.2		0.2	V
		2.3	3.0	I_O=18 mA			0.60		0.60	
		1.65	3.0	I_O=6 mA			0.30		0.30	
		1.65	2.3	I_O=6 mA			0.30		0.30	
I_{IB}	Input Leakage Current	2.7	3.6	$V_I = V_{CC}$ or GND			± 0.5		± 5	µA
I_{OZB}	High Impedance Output Leakage Current	2.7	3.6	$V_{IA} = V_{IHA}$ or V_{ILA} V_{IB} = GND or 2.7V $\overline{G} = V_{CCB}$			± 1.0		± 10	µA
$I_{IB(HOLD)}$	Input Hold Current	1.65	2.3	V_I = 0.57V	25			25		µA
		1.65	2.3	V_I = 1.07V	-25			-25		
		1.65	3.0	V_I = 0.57V	25			25		µA
		1.65	3.0	V_I = 1.07V	-25			-25		
		2.3	3.0	V_I = 0.7V	45			45		µA
		2.3	3.0	V_I = 1.6V	-45			-45		
		2.7	3.6	V_{IB} = 0 to 2.7V					± 300	
I_{CCtB}	Quiescent Supply Current	1.95	3.6	$V_{IA} = V_{CCA}$ or GND $V_{IB} = V_{CCB}$ or GND Dir or $\overline{G} = V_{CCB}$ or GND			2		20	µA
		1.95	2.7							
		2.7	3.6							
ΔI_{CCtB}	Maximum Quiescent Supply Current / Input (Bn, DIR, $\overline{OE}$)	2.7	3.6	$V_{IB} = V_{CCB}$ - 0.6V $V_{IA} = V_{CCA}$ or GND					0.75	mA
		1.95	3.6							
		1.95	2.7							

DYNAMIC SWITCHING CHARACTERISTICS

Symbol	Parameter	Test Condition			Value					Unit
		V_{CCB} (V)	V_{CCA} (V)		T_A = 25 °C			-40 to 85 °C		
					Min.	Typ.	Max.	Min.	Max.	
V_{OLPA}	Dynamic Low Level Quiet An Output	1.8	2.5	C_L =30pF V_{IL} =0V V_{IH} =Vcc		0.25				V
		1.8	3.3			0.25				
		2.5	3.3			0.6				
V_{OLPB}	Dynamic Low Level Quiet Bn Output	1.8	2.5	C_L =30pF V_{IL} =0V V_{IH} =Vcc		0.6				V
		1.8	3.3			0.8				
		2.5	3.3			0.8				
V_{OLVA}	Dynamic Low Level Quiet An Output	1.8	2.5	C_L =30pF V_{IL} =0V V_{IH} =Vcc		-0.6				V
		1.8	3.3			-0.8				
		2.5	3.3			-0.8				
V_{OLVB}	Dynamic Low Level Quiet Bn Output	1.8	2.5	C_L =30pF V_{IL} =0V V_{IH} =Vcc		-0.25				V
		1.8	3.3			-0.25				
		2.5	3.3			-0.6				
V_{OHVA}	Dynamic Low Level Quiet An Output	1.8	2.5	C_L =30pF V_{IL} =0V V_{IH} =Vcc		1.7				V
		1.8	3.3			2.0				
		2.5	3.3			2.0				
V_{OHVB}	Dynamic Low Level Quiet Bn Output	1.8	2.5	C_L =30pF V_{IL} =0V V_{IH} =Vcc		1.3				V
		1.8	3.3			1.3				
		2.5	3.3			1.7				

AC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Test Condition			Value		Unit
		V_{CCB} (V)	V_{CCA} (V)		-40 to 85 °C		
					Min.	Max.	
t_{PLH} t_{PHL}	Propagation Delay Time An to Bn	1.8 ± 0.15	2.5 ± 0.2	C_L = 30 pF R_L = 500 Ω	1.0	5.8	ns
		1.8 ± 0.15	3.3 ± 0.3		1.0	6.2	
		2.5 ± 0.2	3.3 ± 0.3		1.0	4.4	
t_{PLH} t_{PHL}	Propagation Delay Time Bn to An	1.8 ± 0.15	2.5 ± 0.2	C_L = 30 pF R_L = 500 Ω	1.0	5.5	ns
		1.8 ± 0.15	3.3 ± 0.3		1.0	5.1	
		2.5 ± 0.2	3.3 ± 0.3		1.0	4.0	
t_{PZL} t_{PZH}	Output Enable Time $\overline{OE}$ to An	1.8 ± 0.15	2.5 ± 0.2	C_L = 30 pF R_L = 500 Ω	1.0	5.3	ns
		1.8 ± 0.15	3.3 ± 0.3		1.0	5.1	
		2.5 ± 0.2	3.3 ± 0.3		1.0	4.0	
t_{PZL} t_{PZH}	Output Enable Time $\overline{OE}$ to Bn	1.8 ± 0.15	2.5 ± 0.2	C_L = 30 pF R_L = 500 Ω	1.0	8.3	ns
		1.8 ± 0.15	3.3 ± 0.3		1.0	8.2	
		2.5 ± 0.2	3.3 ± 0.3		1.0	4.6	
t_{PLZ} t_{PHZ}	Output Disable Time $\overline{OE}$ to An	1.8 ± 0.15	2.5 ± 0.2	C_L = 30 pF R_L = 500 Ω	1.0	5.2	ns
		1.8 ± 0.15	3.3 ± 0.3		1.0	5.6	
		2.5 ± 0.2	3.3 ± 0.3		1.0	4.5	
t_{PLZ} t_{PHZ}	Output Disable Time $\overline{OE}$ to Bn	1.8 ± 0.15	2.5 ± 0.2	C_L = 30 pF R_L = 500 Ω	1.0	4.6	ns
		1.8 ± 0.15	3.3 ± 0.3		1.0	4.5	
		2.5 ± 0.2	3.3 ± 0.3		1.0	4.4	
t_{OSLH} t_{OSHL}	Output To Output Skew Time (note1, 2)	1.8 ± 0.15	2.5 ± 0.2	C_L = 30 pF R_L = 500 Ω		0.5	ns
		1.8 ± 0.15	3.3 ± 0.3			0.5	
		1.8 ± 0.15	3.3 ± 0.3			0.75	

AC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Test Condition T_A = -40 to 85 °C						Unit
		V_{CCB} = 1.8 ± 0.15V		V_{CCB} = 1.8 ± 0.15V		V_{CCB} = 2.5 ± 0.2V		
		V_{CCA} = 2.5 ± 0.2V		V_{CCA} = 3.3 ± 0.3V		V_{CCA} = 3.3 ± 0.3V		
		Min.	Max.	Min.	Max.	Min.	Max.	
t_{PLH}, t_{PHL}	Propagation Delay Time An to Bn	1.0	5.8	1.0	6.2	1.0	4.4	ns
t_{PLH}, t_{PHL}	Propagation Delay Time Bn to An	1.0	5.5	1.0	5.1	1.0	4.0	
t_{PZL}, t_{PZH}	Output Enable Time $\overline{OE}$ to An	1.0	5.3	1.0	5.1	1.0	4.0	ns
t_{PZL}, t_{PZH}	Output Enable Time $\overline{OE}$ to Bn	1.0	8.3	1.0	8.2	1.0	4.6	
t_{PLZ}, t_{PHZ}	Output Disable Time $\overline{OE}$ to An	1.0	5.2	1.0	5.6	1.0	4.8	ns
t_{PLZ}, t_{PHZ}	Output Disable Time $\overline{OE}$ to Bn	1.0	4.6	1.0	4.5	1.0	4.4	
t_{OSLH} t_{OSHL}	Output To Output Skew Time (note1, 2)		5.0		0.5		0.75	ns


1) Skew is defined as the absolute value of the difference between the actual propagation delay for any two outputs of the same device switching in the same direction, either HIGH or LOW (t_{OSLH} = | t_{PLHm} - t_{PLHn}|, t_{OSHL} = | t_{PHLm} - t_{PHLn}|
2) Parameter guaranteed by design

CAPACITANCE CHARACTERISTICS

Symbol	Parameter	Test Condition			Value					Unit
		V_{CCB} (V)	V_{CCA} (V)		T_A = 25 °C			-40 to 85 °C		
					Min.	Typ.	Max.	Min.	Max.	
C_{INA}	Input Capacitance	open	open			5				V
$C_{I/O}$	Input/Output Capacitance	2.5	3.3			6				V
C_{PD}	Power Dissipation Capacitance	2.5	3.3	f=10MHz		20				V

1) C_{PD} is defined as the value of the IC's internal equivalent capacitance which is calculated from the operating current consumption without load. (Refer to Test Circuit). Average current can be obtained by the following equation. $I_{CC(opr)}$ = C_{PD} x V_{CC} x f_{IN} + I_{CC}/16 (per circuit)

TEST CIRCUIT




TEST	SWITCH
t_{PLH}, t_{PHL}	Open
t_{PZL}, t_{PLZ} (V_{CC} = 3.0 to 3.6V)	6V
t_{PZL}, t_{PLZ} (V_{CC} = 2.3 to 2.7V or V_{CC} = 1.65 to 1.95V)	$2V_{CC}$
t_{PZH}, t_{PHZ}	GND

C_L = 30pF or equivalent (includes jig and probe capacitance)
R_L = R_1 = 500Ω or equivalent
R_T = Z_{OUT} of pulse generator (typically 50Ω)


WAVEFORM SYMBOL VALUE

Symbol	V_{CC}		
	3.0 to 3.6V	2.3 to 2.7V	1.65 to 1.95V
V_{IH}	V_{CC}	V_{CC}	V_{CC}
V_M	1.5V	$V_{CC}/2$	$V_{CC}/2$
V_X	V_{OL} +0.3V	V_{OL} +0.15V	V_{OL} +0.15V
V_Y	V_{OL} -0.3V	V_{OL} -0.15V	V_{OL} -0.15V

WAVEFORM 1: PROPAGATION DELAY (f=1MHz; 50% duty cycle)




WAVEFORM 2: OUTPUT ENABLE AND DISABLE TIME (f=1MHz; 50% duty cycle)



TSSOP48 MECHANICAL DATA


DIM.	mm.			inch		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
A			1.2			0.047
A1	0.05		0.15	0.002		0.006
A2		0.9			0.035	
b	0.17		0.27	0.0067		0.011
c	0.09		0.20	0.0035		0.0079
D	12.4		12.6	0.488		0.496
E		8.1 BSC			0.318 BSC	
E1	6.0		6.2	0.236		0.244
e		0.5 BSC			0.0197 BSC	
K	0°		8°	0°		8°
L	0.50		0.75	0.020		0.030



7065588C


TFBGA54 MECHANICAL DATA

DIM.	mm.			mils		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
A			1.2			47.2
A1	0.25			9.8		
A2	0.85			33.5		
B	0.45		0.55	17.7		21.7
D	7.9		8.1	311.0		318.9
D1		6.4			252.0	
E	5.4	5.5	5.6	212.6	216.5	220.5
E1		4			157.5	
e		0.8			31.5	
SE		0.4			15.7	




µFBGA42 MECHANICAL DATA

DIM.	mm.			mils		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
A	3.90		4.10	153.5		161.4
B	3.40		3.60	133.9		141.7
C		1.07	1.16		42.1	45.6
D		0.3			11.8	
E		0.5			19.7	
F	0.78		0.86	30.7		33.9



Tape & Reel TSSOP48 MECHANICAL DATA

DIM.	mm.			inch		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
A			330			12.992
C	12.8		13.2	0.504		0.519
D	20.2			0.795		
N	60			2.362		
T			30.4			1.197
Ao	8.7		8.9	0.343		0.350
Bo	13.1		13.3	0.516		0.524
Ko	1.5		1.7	0.059		0.067
Po	3.9		4.1	0.153		0.161
P	11.9		12.1	0.468		0.476



Note: Drawing not in scale

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

© The ST logo is a registered trademark of STMicroelectronics

© 2003 STMicroelectronics - Printed in Italy - All Rights Reserved
STMicroelectronics GROUP OF COMPANIES
Australia - Brazil - Canada - China - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco
Singapore - Spain - Sweden - Switzerland - United Kingdom - United States.
© http://www.st.com

TradeElectronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

О компании

ООО "ТрейдЭлектроникс" - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Наличие собственной эффективной системы логистики обеспечивает надежную поставку продукции по конкурентным ценам в точно указанные сроки.

Срок поставки со стоков в **Европе и Америке – от 3 до 14 дней.**

Срок поставки из **Азии – от 10 дней.**

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Предоставляем спец цены на элементы для создания инженерных сэмплов.

Упорный труд, качественный результат дают нам право быть уверенными в себе и надежными для наших клиентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование

Наша организация особенно сильна в поставках модулей, микросхем, пассивных компонентов, ксайленсах (XC), EPF, EPM и силовой электроники.

Большой выбор предлагаемой продукции, различные виды оплаты и доставки, позволят Вам сэкономить время и получить максимум выгоды от сотрудничества с нами!

Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

Перечень производителей, продукцию которых мы поставляем на российский рынок



Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

С удовольствием будем прорабатывать для Вас поставки всех необходимых компонентов по текущим запросам для скорейшего выявления групп элементов, по которым сотрудничество именно с нашей компанией будет для Вас максимально выгодным!

С уважением,

Менеджер отдела продаж ООО

«Трейд Электроникс»

Шишлаков Евгений

8 (495)668-30-28 доб 169

manager28@tradeelectronics.ru

http://www.tradeelectronics.ru/