


## 10-W, 36-V to 75-V INPUT, 1500-V ISOLATION, DC/DC CONVERTERS

### FEATURES

- Input Voltage: 36 V to 75 V
- 10-W Total Output Power
- Output Voltages: 3.3 V, 5 V, and 12 V
- Output Voltage Trim  $\pm 10\%$
- Up To 87% Efficiency
- Overcurrent Protection
- Input Undervoltage Lockout
- Output Overvoltage Protection
- Positive or Negative Logic Enable Control Option
- Synchronization Option
- Space-Saving, Industry Standard Footprint (1.1 in x 1.0 in) / (27.94 mm x 24.38 mm)
- Industry Standard Pinout
- Surface Mount Package
- 1500-Vdc Isolation
- Agency Approvals:  
UL/IEC/CSA-C22.2 60950-1

### APPLICATIONS

- Intermediate Bus Architectures
- Telecom, High-End Computing Platforms
- Power Over Ethernet Applications
- Multi-Rail Power Systems




### DESCRIPTION

The PTMA40XX is a series of 10-W rated isolated dc/dc converters, designed to operate from a standard -48-V telecom central office supply. Housed in an industry standard 1.1 in x 1.0 in (27.94 mm x 24.38 mm) package, this series of isolated modules is set to one of the common intermediate bus voltages of 3.3 V, 5 V, or 12 V.

The PTMA40XX series includes many features expected of high-performance dc/dc converter modules. Operational features include an input undervoltage lockout (UVLO) and a dual-logic output enable control or synchronization option. Overcurrent protection ensures survival against load faults.

Typical applications include distributed power architectures in both telecom and computing environments, power over ethernet, and particularly complex digital systems requiring multiple power supply rails.

### TYPICAL APPLICATION



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

## ORDERING INFORMATION

For the most current package and ordering information, see the Package Option Addendum at the end of this datasheet, or see the TI website at [www.ti.com](http://www.ti.com).

## PART NUMBERING SCHEME

|             | Input Voltage | Output Current                   | Output Voltage                             | Enable                                   | Electrical Options                                                 |          | Pin Style                                                                             | Shipping Package                  |
|-------------|---------------|----------------------------------|--------------------------------------------|------------------------------------------|--------------------------------------------------------------------|----------|---------------------------------------------------------------------------------------|-----------------------------------|
| <b>PTMA</b> | <b>4</b>      | <b>02</b>                        | <b>050</b>                                 | <b>P</b>                                 | <b>2</b>                                                           | <b>A</b> | <b>D</b>                                                                              | <b>T</b>                          |
|             | 4 = 48 V      | 01 = 1 A<br>02 = 2 A<br>03 = 3 A | 033 = 3.3 V<br>050 = 5.0 V<br>120 = 12.0 V | A = None<br>N = Negative<br>P = Positive | 1 = None<br>2 = $V_O$ Adjust<br>3 = $V_O$ Adjust & Synchronization |          | D = Through-hole, Pb-free<br>S = SMD, SnPb solder ball<br>Z = SMD, SnAgCu solder ball | Blank = Tray<br>T = Tape and Reel |

## ABSOLUTE MAXIMUM RATINGS

|              |                             |                                                       | UNIT                              |
|--------------|-----------------------------|-------------------------------------------------------|-----------------------------------|
| $V_I$        | Input Voltage               | Continuous                                            | 75 V                              |
|              |                             | Surge, 1 s max                                        | 100 V <sup>(1)</sup>              |
| $T_A$        | Operating temperature range | Over $V_I$ range                                      | –40°C to 85°C                     |
| $T_{WAVE}$   | Wave solder temperature     | Surface temperature of module or pins<br>(20 seconds) | AD suffix<br>260°C <sup>(2)</sup> |
| $T_{REFLOW}$ | Solder reflow temperature   | Surface temperature of module or pins<br>(20 seconds) | AS suffix<br>235°C <sup>(2)</sup> |
|              |                             |                                                       | AZ suffix<br>260°C <sup>(2)</sup> |
| $T_{STG}$    | Storage temperature         |                                                       | –55°C to 125°C                    |
| $P_O$        | Output Power                |                                                       | 10 W                              |

- (1) The converter's internal protection circuitry may cause the output to turn off when the applied input voltage is greater than 75 V.  
(2) During solder reflow of SMD package version, do not elevate the module PCB, pins, or internal component temperatures beyond this peak temperature.

## PACKAGE SPECIFICATIONS

|                      |                                                                       |                                 | UNITS                  |
|----------------------|-----------------------------------------------------------------------|---------------------------------|------------------------|
| Weight               |                                                                       |                                 | 6.5 grams              |
| Flammability         | Meets UL94V-O                                                         |                                 |                        |
| Mechanical shock     | Per Mil-STD-883D, Method 2002.3, 1 ms, 1/2 Sine, mounted              | Horizontal T/H (Suffix AD)      | 500 G <sup>(1)</sup>   |
|                      |                                                                       | Horizontal SMD (Suffix AS & AZ) | 500 G <sup>(1)</sup>   |
| Mechanical vibration | Mil-STD-883D, Method 2007.2, 20-2000 Hz, PCB mounted                  | Horizontal T/H (Suffix AD)      | 20 G <sup>(1)</sup>    |
|                      |                                                                       | Horizontal SMD (Suffix AS & AZ) | 10 G <sup>(1)</sup>    |
| Reliability          | Telcordia SR-332 50% stress, $T_A = 40^\circ\text{C}$ , ground benign | MTBF                            | 7.3 10 <sup>6</sup> Hr |

- (1) Qualification limit.

## PTMA403033 ELECTRICAL CHARACTERISTICS

$T_A = 25^\circ\text{C}$ ,  $V_I = 48\text{ V}$ ,  $V_O = 3.3\text{ V}$ ,  $C_I = 0\text{ }\mu\text{F}$ ,  $C_O = 0\text{ }\mu\text{F}$ , and  $I_O = I_{O\text{max}}$  (Unless otherwise stated)

| PARAMETER        |                                | TEST CONDITIONS                                                                    | PTMA403033                      |                        |                     | UNIT             |
|------------------|--------------------------------|------------------------------------------------------------------------------------|---------------------------------|------------------------|---------------------|------------------|
|                  |                                |                                                                                    | MIN                             | TYP                    | MAX                 |                  |
| $P_O$            | Output power                   | Over $V_I$ range                                                                   |                                 |                        | 10                  | W                |
| $I_O$            | Output current                 | Over $V_I$ range                                                                   | 0.1 <sup>(1)</sup>              |                        | 3 <sup>(2)</sup>    | A                |
| $I_{\text{LIM}}$ | Current Limit Threshold        | Shutdown, followed by autorecovery                                                 |                                 | 4.25                   |                     | A                |
| $V_I$            | Input voltage range            | Over $I_O$ range                                                                   | 36                              | 48                     | 75                  | V                |
| $V_O$            | Set-point voltage tolerance    |                                                                                    |                                 | $\pm 2$ <sup>(3)</sup> |                     | % $V_O$          |
|                  | Temperature variation          | $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$                                 |                                 | $\pm 1$                |                     | % $V_O$          |
|                  | Line regulation                | Over $V_I$ range                                                                   |                                 | $\pm 3$                |                     | mV               |
|                  | Load regulation                | Over $I_O$ range                                                                   |                                 | $\pm 10$               |                     | mV               |
|                  | Total output voltage variation | Includes set-point, line, load, $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ |                                 | 3                      | 5 <sup>(3)</sup>    | % $V_O$          |
|                  | Trim adjust range              | Over $V_I$ range                                                                   | 3.0                             |                        | 3.6                 | V                |
| $\eta$           | Efficiency                     | $P_O = P_{O\text{max}}$                                                            |                                 | 82%                    |                     |                  |
|                  | $V_O$ Ripple (peak-to-peak)    | 20-MHz bandwidth                                                                   |                                 | 65                     |                     | mV <sub>pp</sub> |
|                  | Transient response             | 0.1 A/ $\mu\text{s}$ load step, 50% to 100% $I_{O\text{max}}$                      | Recovery time                   |                        | 750                 | $\mu\text{s}$    |
|                  |                                |                                                                                    | $V_O$ over/undershoot           |                        | $\pm 150$           | mV               |
|                  | Output enable input (pin 3)    | Referenced to $V_I^-$                                                              | Input high voltage ( $V_{IH}$ ) | 4.5                    | Open <sup>(4)</sup> | V                |
|                  |                                |                                                                                    | Input low voltage ( $V_{IL}$ )  | –0.2                   | 0.8                 |                  |
|                  |                                |                                                                                    | Input low current ( $I_{IL}$ )  | 1                      |                     | mA               |
|                  | Standby input current          | Pin 3 open                                                                         |                                 | 8                      |                     | mA               |
| UVLO             | Undervoltage lockout           |                                                                                    | 32                              |                        | 34                  | V                |
| OVP              | Output Overvoltage Protection  |                                                                                    | 3.7                             |                        | 5.4                 | V                |
| $f_S$            | Switching frequency            | Over $V_I$ and $I_O$ ranges (non-Sync option)                                      | 250                             | 300                    | 350                 | kHz              |
| SYNC             | Sync switching frequency       | Free-running                                                                       | 180                             | 215 <sup>(5)</sup>     | 250                 | kHz              |
|                  |                                | Synchronization range                                                              | 250 <sup>(5)</sup>              |                        | 350 <sup>(5)</sup>  |                  |
|                  | high-level input voltage       |                                                                                    | 3.5                             |                        | 6                   | V                |
|                  | low-level input voltage        |                                                                                    | –0.3                            |                        | 0.5                 | V                |
|                  | clock duty cycle               |                                                                                    | 25                              |                        | 75                  | %                |
| $C_I$            | External input capacitance     |                                                                                    | 0                               | 47                     |                     | $\mu\text{F}$    |
| $C_O$            | External output capacitance    |                                                                                    | 0                               | 47 <sup>(6)</sup>      | 1000                | $\mu\text{F}$    |
| $V_{\text{ISO}}$ | Isolation voltage              | Primary-Secondary                                                                  | 1,500                           |                        |                     | Vdc              |
| $C_{\text{ISO}}$ | Isolation capacitance          |                                                                                    |                                 | 1,100                  |                     | pF               |
| $R_{\text{ISO}}$ | Isolation resistance           |                                                                                    | 10                              |                        |                     | M $\Omega$       |

- (1) The converter requires a minimum load current for proper operation. However, the converter is not damaged when operated under a no-load condition.
- (2) See temperature derating curves for safe operating area (SOA), to determine output current derating at elevated ambient temperatures.
- (3) The set-point voltage tolerance is affected by the tolerance and stability of  $R_{\text{TRIM}}$ . The stated limit is unconditionally met if  $R_{\text{TRIM}}$  has a tolerance of  $\leq 1\%$ , with  $\leq 100\text{ ppm}/^\circ\text{C}$  temperature stability.
- (4) The Enable input (pin 3) has an internal pullup resistor. Do not place an external pullup resistor on this input pin. If the enable feature is not used, for a positive enable device this input should be left open circuit and a negative enable device should be permanently connected to  $V_I^-$  (pin 2). A discrete MOSFET or bipolar transistor is recommended for the enable control. The open-circuit voltage is typically less than 5 V. See the *Application Information* for a more detailed description.
- (5) A device with the synchronization option has a reduced switching frequency of 215 kHz typical. The synchronization frequency can only be adjusted to a higher frequency, up to 350 kHz maximum.
- (6) An output capacitor is not required for proper operation. However, additional capacitance at the load improves the transient response.

## PTMA402050 ELECTRICAL CHARACTERISTICS

$T_A = 25^\circ\text{C}$ ,  $V_I = 48\text{ V}$ ,  $V_O = 5\text{ V}$ ,  $C_I = 0\text{ }\mu\text{F}$ ,  $C_O = 0\text{ }\mu\text{F}$ , and  $I_O = I_{O\text{max}}$  (Unless otherwise stated)

| PARAMETER |                                | TEST CONDITIONS                                                                    | PTMA402050                      |                        |                     | UNIT             |
|-----------|--------------------------------|------------------------------------------------------------------------------------|---------------------------------|------------------------|---------------------|------------------|
|           |                                |                                                                                    | MIN                             | TYP                    | MAX                 |                  |
| $P_O$     | Output power                   | Over $V_I$ range                                                                   |                                 |                        | 10                  | W                |
| $I_O$     | Output current                 | Over $V_I$ range                                                                   | 0.1 <sup>(1)</sup>              |                        | 2 <sup>(2)</sup>    | A                |
| $I_{LIM}$ | Current Limit Threshold        | Shutdown, followed by autorecovery                                                 |                                 | 3                      |                     | A                |
| $V_I$     | Input voltage range            | Over $I_O$ range                                                                   | 36                              | 48                     | 75                  | V                |
| $V_O$     | Set-point voltage tolerance    |                                                                                    |                                 | $\pm 2$ <sup>(3)</sup> |                     | % $V_O$          |
|           | Temperature variation          | $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$                                 |                                 | $\pm 1$                |                     | % $V_O$          |
|           | Line regulation                | Over $V_I$ range                                                                   |                                 | 5                      |                     | mV               |
|           | Load regulation                | Over $I_O$ range                                                                   |                                 | 10                     |                     | mV               |
|           | Total output voltage variation | Includes set-point, line, load, $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ |                                 | 3                      | 5 <sup>(3)</sup>    | % $V_O$          |
|           | Trim adjust range              | Over $V_I$ range                                                                   | 4.5                             |                        | 5.5                 | V                |
| $\eta$    | Efficiency                     | $P_O = P_{O\text{max}}$                                                            |                                 | 85%                    |                     |                  |
|           | $V_O$ Ripple (peak-to-peak)    | 20-MHz bandwidth                                                                   |                                 | 55                     |                     | mV <sub>pp</sub> |
|           | Transient response             | 0.1 A/ $\mu\text{s}$ load step,<br>50% to 100%<br>$I_{O\text{max}}$                | Recovery time                   |                        | 250                 | $\mu\text{s}$    |
|           |                                |                                                                                    | $V_O$ over/undershoot           |                        | $\pm 150$           | mV               |
|           | Output enable input (pin 3)    | Referenced to $V_{I-}$                                                             | Input high voltage ( $V_{IH}$ ) | 4.5                    | Open <sup>(4)</sup> | V                |
|           |                                |                                                                                    | Input low voltage ( $V_{IL}$ )  | -0.2                   | 0.8                 |                  |
|           |                                |                                                                                    | Input low current ( $I_{IL}$ )  | 1                      |                     | mA               |
|           | Standby input current          | Pin 3 open                                                                         |                                 | 8                      |                     | mA               |
| UVLO      | Undervoltage lockout           |                                                                                    | 32                              |                        | 34                  | V                |
| OVP       | Output Overvoltage Protection  |                                                                                    | 5.6                             |                        | 7.9                 | V                |
| $f_S$     | Switching frequency            | Over $V_I$ range                                                                   | 250                             | 300                    | 350                 | kHz              |
| SYNC      | Sync switching frequency       | Free-running                                                                       | 180                             | 215 <sup>(5)</sup>     | 250                 | kHz              |
|           |                                | Synchronization range                                                              | 250 <sup>(5)</sup>              |                        | 350 <sup>(5)</sup>  |                  |
|           | high-level input voltage       |                                                                                    | 3.5                             |                        | 6                   | V                |
|           | low-level input voltage        |                                                                                    | -0.3                            |                        | 0.5                 | V                |
|           | clock duty cycle               |                                                                                    | 25                              |                        | 75                  | %                |
| $C_I$     | External input capacitance     |                                                                                    | 0                               | 47                     |                     | $\mu\text{F}$    |
| $C_O$     | External output capacitance    |                                                                                    | 0                               | 47 <sup>(6)</sup>      | 1000                | $\mu\text{F}$    |
| $V_{ISO}$ | Isolation voltage              | Primary-Secondary                                                                  | 1,500                           |                        |                     | Vdc              |
| $C_{ISO}$ | Isolation capacitance          |                                                                                    |                                 | 1,100                  |                     | pF               |
| $R_{ISO}$ | Isolation resistance           |                                                                                    | 10                              |                        |                     | M $\Omega$       |

- (1) The converter requires a minimum load current for proper operation. However, the converter is not damaged when operated under a no-load condition.
- (2) See temperature derating curves for safe operating area (SOA), to determine output current derating at elevated ambient temperatures.
- (3) The set-point voltage tolerance is affected by the tolerance and stability of  $R_{TRIM}$ . The stated limit is unconditionally met if  $R_{TRIM}$  has a tolerance of  $\leq 1\%$ , with  $\leq 100\text{ ppm}/^\circ\text{C}$  temperature stability.
- (4) The Enable input (pin 3) has an internal pullup resistor. Do not place an external pullup resistor on this input pin. If the enable feature is not used, for a positive enable device this input should be left open circuit and a negative enable device should be permanently connected to  $V_{I-}$  (pin 2). A discrete MOSFET or bipolar transistor is recommended for the enable control. The open-circuit voltage is typically less than 5 V. See the *Application Information* for a more detailed description.
- (5) A device with the synchronization option has a reduced switching frequency of 215 kHz typical. The synchronization frequency can only be adjusted to a higher frequency, up to 350 kHz maximum.
- (6) An output capacitor is not required for proper operation. However, additional capacitance at the load will improve the transient response.

## PTMA401120 ELECTRICAL CHARACTERISTICS

$T_A = 25^\circ\text{C}$ ,  $V_I = 48\text{ V}$ ,  $V_O = 12\text{ V}$ ,  $C_I = 0\text{ }\mu\text{F}$ ,  $C_O = 0\text{ }\mu\text{F}$ , and  $I_O = I_{O\text{max}}$  (Unless otherwise stated)

| PARAMETER                   |                                | TEST CONDITIONS                                                                    | PTMA401120                      |                        |                     | UNIT             |
|-----------------------------|--------------------------------|------------------------------------------------------------------------------------|---------------------------------|------------------------|---------------------|------------------|
|                             |                                |                                                                                    | MIN                             | TYP                    | MAX                 |                  |
| $P_O$                       | Output power                   | Over $V_I$ range                                                                   |                                 |                        | 12                  | W                |
| $I_O$                       | Output current                 | Over $V_I$ range                                                                   | 0.1 <sup>(1)</sup>              |                        | 1 <sup>(2)</sup>    | A                |
| $I_{\text{LIM}}$            | Current Limit Threshold        | Shutdown, followed by autorecovery                                                 |                                 | 1.5                    |                     | A                |
| $V_I$                       | Input voltage range            | Over $I_O$ range                                                                   | 36                              | 48                     | 75                  | V                |
| $V_O$                       | Set-point voltage tolerance    |                                                                                    |                                 | $\pm 2$ <sup>(3)</sup> |                     | % $V_O$          |
|                             | Temperature variation          | $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$                                 |                                 | $\pm 1$                |                     | % $V_O$          |
|                             | Line regulation                | Over $V_I$ range                                                                   |                                 | 10                     |                     | mV               |
|                             | Load regulation                | Over $I_O$ range                                                                   |                                 | 3                      |                     | mV               |
|                             | Total output voltage variation | Includes set-point, line, load, $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$ |                                 | 3                      | 5 <sup>(3)</sup>    | % $V_O$          |
|                             | Trim adjust range              | Over $V_I$ range                                                                   | 10.8                            |                        | 13.2                | V                |
| $\eta$                      | Efficiency                     | $P_O = P_{O\text{max}}$                                                            |                                 | 87%                    |                     |                  |
|                             | $V_O$ Ripple (peak-to-peak)    | 20-MHz bandwidth                                                                   |                                 | 85                     |                     | mV <sub>pp</sub> |
| Transient Response          |                                | 0.1 A/ $\mu\text{s}$ load step, 50% to 100% $I_{O\text{max}}$                      | Recovery time                   |                        | 400                 | $\mu\text{s}$    |
|                             |                                |                                                                                    | $V_O$ over/undershoot           |                        | $\pm 250$           | mV               |
| Output enable input (pin 3) |                                | Referenced to $V_I^-$                                                              | Input high voltage ( $V_{IH}$ ) | 4.5                    | Open <sup>(4)</sup> | V                |
|                             |                                |                                                                                    | Input low voltage ( $V_{IL}$ )  | –0.2                   | 0.8                 |                  |
|                             |                                |                                                                                    | Input low current ( $I_{IL}$ )  | 1                      |                     | mA               |
|                             | Standby input current          | Pin 3 open                                                                         |                                 | 8                      |                     | mA               |
| UVLO                        | Undervoltage lockout           |                                                                                    | 32                              |                        | 34                  | V                |
| OVP                         | Output Overvoltage Protection  |                                                                                    | 13.5                            |                        | 17.5                | V                |
| $f_S$                       | Switching frequency            | Over $V_I$ range                                                                   | 250                             | 300                    | 350                 | kHz              |
| SYNC                        | Sync switching frequency       | Free-running                                                                       | 180                             | 215 <sup>(5)</sup>     | 250                 | kHz              |
|                             |                                | Synchronization range                                                              | 250 <sup>(5)</sup>              |                        | 350 <sup>(5)</sup>  |                  |
|                             | high-level input voltage       |                                                                                    | 3.5                             |                        | 6                   | V                |
|                             | low-level input voltage        |                                                                                    | –0.3                            |                        | 0.5                 | V                |
|                             | clock duty cycle               |                                                                                    | 25                              |                        | 75                  | %                |
| $C_I$                       | External input capacitance     |                                                                                    | 0                               | 47                     |                     | $\mu\text{F}$    |
| $C_O$                       | External output capacitance    |                                                                                    | 0                               | 47 <sup>(6)</sup>      | 220                 | $\mu\text{F}$    |
| $V_{\text{ISO}}$            | Isolation voltage              | Primary-Secondary                                                                  | 1,500                           |                        |                     | Vdc              |
| $C_{\text{ISO}}$            | Isolation capacitance          |                                                                                    |                                 | 1,100                  |                     | pF               |
| $R_{\text{ISO}}$            | Isolation resistance           |                                                                                    | 10                              |                        |                     | M $\Omega$       |

- (1) The converter requires a minimum load current for proper operation. The converter is not damaged when operated under a no-load condition.
- (2) See temperature derating curves for safe operating area (SOA), to determine output current derating at elevated ambient temperatures.
- (3) The set-point voltage tolerance is affected by the tolerance and stability of  $R_{\text{TRIM}}$ . The stated limit is unconditionally met if  $R_{\text{TRIM}}$  has a tolerance of 1%, with 100 ppm/ $^\circ\text{C}$  temperature stability.
- (4) The Enable input (pin 3) has an internal pullup resistor. Do not place an external pullup resistor on this input pin. If the enable feature is not used, for a positive enable device this input should be left open circuit and a negative enable device should be permanently connected to  $V_I^-$  (pin 2). A discrete MOSFET or bipolar transistor is recommended for the enable control. The open-circuit voltage is typically less than 5 V. See the *Application Information* for a more detailed description.
- (5) A device with the synchronization option has a reduced switching frequency of 215 kHz typical. The synchronization frequency can only be adjusted to a higher frequency, up to 350 kHz maximum.
- (6) An output capacitor is not required for proper operation. However, additional capacitance at the load will improve the transient response.

TERMINAL FUNCTIONS

| TERMINAL                   |     | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|----------------------------|-----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NAME                       | NO. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Enable/Sync <sup>(1)</sup> | 3   | The Enable input is an open-base logic input that is referenced to $V_{I-}$ . Two ON/OFF enable options are available, positive logic and negative logic. Positive logic devices are enabled by applying a logic high voltage (Open) and are disabled by applying a logic low voltage ( $V_{I-}$ ). Negative logic devices are enabled by applying a logic low voltage ( $V_{I-}$ ) and are disabled by applying a logic high voltage (Open). See the Application Information section for more detailed information.<br>This pin also has the option of a synchronization input. A module that has the synchronization option does not have ON/OFF enable control. A 5-V logic signal greater than the free-running frequency but $\leq 350$ kHz is required for synchronization control. See the Application Information section for more detailed information. |
| $V_{I-}^{(1)}$             | 2   | The negative input supply for the module, and the 0-V reference for the Enable/Sync inputs. When powering the module from a positive source, this input is connected to the input source return.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| $V_{I+}^{(1)}$             | 1   | The positive input for the module with respect to $V_{I-}$ . When powering the module from a negative input voltage, this input is connected to the input source ground.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| $V_{O+}$                   | 4   | This is the positive power output with respect to $V_{O-}$ . It is dc isolated from the input power pins.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Trim                       | 5   | This pin allows the output voltage set point of the module to be increased or decreased up to $\pm 10\%$ . Connecting a resistor between this terminal and $V_{O+}$ decreases the output voltage set point. Connecting a resistor between this terminal and $V_{O-}$ increases the output voltage set point. A 0.05-W rated resistor may be used, with tolerance and temperature stability of 1% and 100 ppm/ $^{\circ}$ C, respectively. If left open circuit, the converter output voltage defaults to its nominal value. The specification table gives the standard resistor values for the most common output voltages.                                                                                                                                                                                                                                      |
| $V_{O-}$                   | 6   | This is the output power return for the $V_{O+}$ bus. This terminal should be connected to the common of the load circuit.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

(1) These functions indicate signals electrically common with the input.



## TYPICAL CHARACTERISTICS

### PTMA403033 Characteristic Data ( $V_O = 3.3\text{ V}$ ) <sup>(1)(2)</sup>




Figure 1.




Figure 2.




Figure 3.








Figure 4.

- (1) All data listed in [Figure 1](#), [Figure 2](#), and [Figure 3](#) have been developed from actual products tested at  $25^{\circ}\text{C}$ . This data is considered typical data for the dc-dc converter.
- (2) The temperature derating curves represent operating conditions at which internal components are at or below manufacturer's maximum rated operating temperature. Derating limits apply to modules soldered directly to a 100-mm  $\times$  100-mm, double-sided PCB with 2 oz. copper. For surface mount packages, multiple vias (plated through holes) are required to add thermal paths around the power pins. Please refer to the mechanical specification for more information. Applies to [Figure 4](#).

## TYPICAL CHARACTERISTICS (continued)

### PTMA402050 Characteristic Data ( $V_O = 5\text{ V}$ ) <sup>(3)(4)</sup>



- (3) All data listed in [Figure 5](#), [Figure 7](#), and [Figure 6](#) have been developed from actual products tested at 25°C. This data is considered typical data for the dc-dc converter.
- (4) The temperature derating curves represent operating conditions at which internal components are at or below manufacturer's maximum rated operating temperature. Derating limits apply to modules soldered directly to a 100-mm × 100-mm, double-sided PCB with 2 oz. copper. For surface mount packages, multiple vias (plated through holes) are required to add thermal paths around the power pins. Please refer to the mechanical specification for more information. Applies to [Figure 8](#).



## TYPICAL CHARACTERISTICS (continued)

### PTMA401120 Characteristic Data ( $V_O = 12\text{ V}$ ) <sup>(5)(6)</sup>




Figure 9.




Figure 10.




Figure 11.




Figure 12.

- (5) All data listed in [Figure 9](#), [Figure 10](#), and [Figure 11](#) have been developed from actual products tested at 25°C. This data is considered typical data for the dc-dc converter.
- (6) The temperature derating curves represent operating conditions at which internal components are at or below manufacturer's maximum rated operating temperature. Derating limits apply to modules soldered directly to a 100-mm × 100-mm, double-sided PCB with 2 oz. copper. For surface mount packages, multiple vias (plated through holes) are required to add thermal paths around the power pins. Please refer to the mechanical specification for more information. Applies to [Figure 12](#).

## APPLICATION INFORMATION

### Operating Features and System Considerations for the PTMA40XX DC/DC Converters

#### Primary-Secondary Isolation

These converters incorporate electrical isolation between the input terminals (primary) and the output terminals (secondary). All converters are tested to a withstand voltage of 1500 Vdc. This complies with UL/cUL 60950 and EN 60950 and the requirements for functional isolation. It allows the converter to be configured for either a positive or negative input voltage source. The data sheet *Terminal Functions* table provides guidance as to the correct reference that must be used for the external control signals.

#### Undervoltage Lockout

The undervoltage lockout (UVLO) is designed to prevent the operation of the converter until the input voltage is close to the minimum operating voltage. The converter is held off when the input voltage is below the UVLO threshold, and turns on when the input voltage rises above the threshold. This prevents high start-up current during normal power up of the converter, and minimizes the current drain from the input source during low input voltage conditions. The converter meets full specifications when the minimum specified input voltage is reached. The UVLO circuitry also overrides the operation of the enable or synchronization controls. Only when the input voltage is above the UVLO threshold does this input become functional.

#### Output Overvoltage Clamp

The module is protected from an overvoltage on the output using an internal clamp. This protects against a break in the feedback path as well as a ground fault on the external Trim resistor, which would cause the output voltage to increase.

#### Overcurrent Protection

To protect against load faults, these converters incorporate output overcurrent protection. Applying a load to the output that exceeds the converter overcurrent threshold (see applicable specification) causes the output voltage to momentarily fold back, and then shut down. Following shutdown, the module periodically attempts to automatically recover by initiating a soft-start power up. This is often described as a *hiccup* mode of operation, whereby the module continues in the cycle of successive shutdown and power up until the load fault is removed. Once the fault is removed, the converter automatically recovers and returns to normal operation.

#### Soft-Start Power Up

When the converter is first powered, the internal soft-start circuit limits how fast the output voltage can rise. The soft-start circuit functions after a valid input source is applied and the output is enabled, after the converter output is enabled using the Enable input, or on a recovery from a load fault. The purpose of the soft-start feature is to limit the surge of current drawn from the input source when the converter begins to operate. By limiting the rate at which the output voltage rises, the magnitude of current required to charge up the load circuit capacitance is significantly reduced.

**Figure 13** shows the power-up characteristic of a PTMA403033 converter. The output voltage is 3.3 V. The soft-start circuit causes a slow, soft rise of the output voltage. The output voltage will begin to rise after a time delay (typically 85 ms-100 ms) once a valid input voltage is applied. The output then progressively rises to the voltage set-point. The waveforms were recorded with a resistive load of 3 A.

## APPLICATION INFORMATION (continued)




Figure 13. Power-up Waveforms

### Output Voltage Trim Adjustment

An external resistor is required to increase or decrease the output voltage set point of the module by  $\pm 10\%$ . The resistor,  $R_{TRIM}$ , must be connected between the TRIM pin (pin 5) and  $V_{O+}$  (pin 4) to decrease the output voltage, or between the TRIM pin and  $V_{O-}$  (pin 6) to increase the output voltage. A 0.05-W rated resistor can be used. The tolerance should be 1%, with a temperature stability of 100 ppm/°C (or better). Place the resistor close to the converter and connect it using dedicated PCB traces (see Figure 14). Table 1 gives the nearest standard value of external resistor for the common voltages within each model's adjust range.

Table 1. Standard Values of  $R_{TRIM}$  for Common Output Voltages

| PTMA403033          |                          |      | PTMA402050          |                          |      | PTMA401120          |                          |      |
|---------------------|--------------------------|------|---------------------|--------------------------|------|---------------------|--------------------------|------|
| $V_O$<br>(required) | $R_{TRIM}$ (k $\Omega$ ) |      | $V_O$<br>(required) | $R_{TRIM}$ (k $\Omega$ ) |      | $V_O$<br>(required) | $R_{TRIM}$ (k $\Omega$ ) |      |
|                     | down                     | up   |                     | down                     | up   |                     | down                     | up   |
| 3.0 V               | 118                      | —    | 4.5 V               | 18.7                     | —    | 10.8 V              | 64.9                     | —    |
| 3.1 V               | 187                      | —    | 4.6 V               | 24.9                     | —    | 11.0 V              | 80.6                     | —    |
| 3.2 V               | 392                      | —    | 4.7 V               | 35.7                     | —    | 11.2 V              | 105                      | —    |
| 3.3 V               | open                     | open | 4.8 V               | 57.6                     | —    | 11.4 V              | 143                      | —    |
| 3.4 V               | —                        | 249  | 4.9 V               | 121                      | —    | 11.6 V              | 221                      | —    |
| 3.5 V               | —                        | 124  | 5.0 V               | open                     | open | 11.8 V              | 464                      | —    |
| 3.6 V               | —                        | 82.5 | 5.1 V               | —                        | 124  | 12.0 V              | open                     | open |
| —                   | —                        | —    | 5.2 V               | —                        | 61.9 | 12.2 V              | —                        | 118  |
| —                   | —                        | —    | 5.3 V               | —                        | 40.2 | 12.4 V              | —                        | 57.6 |
| —                   | —                        | —    | 5.4 V               | —                        | 29.4 | 12.6 V              | —                        | 36.5 |
| —                   | —                        | —    | 5.5 V               | —                        | 23.2 | 12.8 V              | —                        | 26.1 |
| —                   | —                        | —    | —                   | —                        | —    | 13.0 V              | —                        | 19.6 |
| —                   | —                        | —    | —                   | —                        | —    | 13.2 V              | —                        | 15.8 |

For other output voltages, the value of the required trim resistor may be calculated using [Equation 1](#) to adjust the voltage up or [Equation 2](#) to adjust the voltage down.


$$R_{\text{TRIM(up)}} = \frac{R_O \times V_R}{(V_O - V_{\text{SET}})} - R_P \text{ (k}\Omega\text{)} \quad (1)$$

$$R_{\text{TRIM(dwn)}} = \frac{R_O \times (V_O - V_R)}{(V_{\text{SET}} - V_O)} - R_P \text{ (k}\Omega\text{)} \quad (2)$$

[Table 2](#) gives the required  $R_{\text{TRIM}}$  equation constants for the converter model selected. To calculate the required value of  $R_{\text{TRIM}}$ , simply locate the applicable constants and substitute these into the formula along with the desired output voltage.

**Table 2. Trim Adjust Equation Constants**

| Constants            | PTMA403033             | PTMA402050             | PTMA401120             |
|----------------------|------------------------|------------------------|------------------------|
| $V_R$ (V)            | 1.24                   | 2.50                   | 2.50                   |
| $R_O$ ( $\Omega$ )   | 20                     | 5.11                   | 10                     |
| $R_P$ ( $\Omega$ )   | 1.0                    | 2.05                   | 5.11                   |
| $V_{\text{SET}}$ (V) | 3.3                    | 5.0                    | 12.0                   |
| $V_O$ (V)            | Desired Output Voltage | Desired Output Voltage | Desired Output Voltage |



**Figure 14. Output Voltage Adjustment**

## Thermal Considerations

Airflow may be necessary to ensure that the module can supply the desired load current in environments with elevated ambient temperatures. The required airflow rate is determined from the safe operating area (SOA). The SOA is the area beneath the applicable airflow rate curve on the graph of temperature derating vs output current. (See the Typical Characteristics.) Operating the converter within the SOA limits ensures that all the internal components are at or below their stated maximum operating temperatures.

## On/Off Enable Controls

On/Off enable options include positive logic or negative logic. A positive logic device enables the module's output when a logic high voltage is present on the Enable pin (pin 3) and disables the output with a logic low voltage. A negative logic device disables the output when a logic high voltage is present on the Enable pin and enables the output during a logic low voltage. See the Electrical Characteristics table for logic high and logic low limits. The Enable pin is ideally controlled with an open-collector (or open-drain) discrete transistor. See [Figure 15](#) below for a typical On/Off Enable control circuit. For automatic start-up, the Enable pin should be left open for a positive logic module and should be shorted to  $V_{I-}$  (pin 2) for a negative logic module. Both inputs are electrically referenced to  $V_{I-}$  on the primary (input) side of the converter. Do not place an external pull-up resistor on this input pin.

## Enable Control Schematic




Figure 15. Typical On/Off Enable Control Circuit

## On/Off Enable Turn-On Time

Once enabled, the converter executes a soft-start power up. The converter exhibits a short delay of approximately 100  $\mu$ s, measured from the transition of the enable signal to the instance the  $V_O$  Bus output begins to rise. The output is in regulation within 1.5 ms.




Figure 16. Output Enable Power-Up Characteristic

## Synchronization

The Synchronization option allows multiple power modules to be synchronized to a common frequency. Driving the Sync pin (pin 3) with an external clock set to the desired frequency, synchronizes all connected modules to that frequency. Modules with the synchronization option have a reduced free-running switching frequency of 215 kHz typical. The synchronization frequency can only be adjusted to a higher frequency, up to 350 kHz. A 5-V logic signal is recommended for control. See [Figure 17](#). See the Electrical Characteristics table for synchronization limits.





Figure 17. Synchronization Control


## MECHANICALS

### Tape and Reel



## MECHANICALS (continued)

## Tray



**PACKAGING INFORMATION**

| Orderable Device | Status <sup>(1)</sup> | Package Type         | Package Drawing | Pins | Package Qty | Eco Plan <sup>(2)</sup> | Lead/<br>Ball Finish | MSL Peak Temp <sup>(3)</sup>               | Samples<br>(Requires Login) |
|------------------|-----------------------|----------------------|-----------------|------|-------------|-------------------------|----------------------|--------------------------------------------|-----------------------------|
| PTMA401120A1AD   | ACTIVE                | Through-Hole Module  | EEP             | 4    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA401120A1AS   | ACTIVE                | Surface Mount Module | EET             | 4    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA401120A1AST  | ACTIVE                | Surface Mount Module | EET             | 4    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA401120A1AZ   | ACTIVE                | Surface Mount Module | BET             | 4    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA401120A1AZT  | ACTIVE                | Surface Mount Module | BET             | 4    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA401120A2AD   | ACTIVE                | Through-Hole Module  | EEV             | 5    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA401120A2AS   | ACTIVE                | Surface Mount Module | EEW             | 5    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA401120A2AST  | ACTIVE                | Surface Mount Module | EEW             | 5    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA401120A2AZ   | ACTIVE                | Surface Mount Module | BEW             | 5    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA401120A2AZT  | ACTIVE                | Surface Mount Module | BEW             | 5    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA401120A3AD   | ACTIVE                | Through-Hole Module  | EEP             | 6    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA401120A3AS   | ACTIVE                | Surface Mount Module | EET             | 6    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA401120A3AST  | ACTIVE                | Surface Mount Module | EET             | 6    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA401120A3AZ   | ACTIVE                | Surface Mount Module | BET             | 6    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA401120A3AZT  | ACTIVE                | Surface Mount Module | BET             | 6    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA401120N1AD   | ACTIVE                | Through-Hole Module  | EEP             | 5    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA401120N1AS   | ACTIVE                | Surface Mount Module | EET             | 5    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |



| Orderable Device | Status <sup>(1)</sup> | Package Type         | Package Drawing | Pins | Package Qty | Eco Plan <sup>(2)</sup> | Lead/<br>Ball Finish | MSL Peak Temp <sup>(3)</sup>               | Samples<br>(Requires Login) |
|------------------|-----------------------|----------------------|-----------------|------|-------------|-------------------------|----------------------|--------------------------------------------|-----------------------------|
| PTMA401120N1AST  | ACTIVE                | Surface Mount Module | EET             | 5    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA401120N1AZ   | ACTIVE                | Surface Mount Module | BET             | 5    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA401120N1AZT  | ACTIVE                | Surface Mount Module | BET             | 5    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA401120N2AD   | ACTIVE                | Through-Hole Module  | EEP             | 6    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA401120N2AS   | ACTIVE                | Surface Mount Module | EET             | 6    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA401120N2AST  | ACTIVE                | Surface Mount Module | EET             | 6    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA401120N2AZ   | ACTIVE                | Surface Mount Module | BET             | 6    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA401120N2AZT  | ACTIVE                | Surface Mount Module | BET             | 6    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA401120P1AD   | ACTIVE                | Through-Hole Module  | EEP             | 5    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA401120P1AS   | ACTIVE                | Surface Mount Module | EET             | 5    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA401120P1AST  | ACTIVE                | Surface Mount Module | EET             | 5    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA401120P1AZ   | ACTIVE                | Surface Mount Module | BET             | 5    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA401120P1AZT  | ACTIVE                | Surface Mount Module | BET             | 5    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA401120P2AD   | ACTIVE                | Through-Hole Module  | EEP             | 6    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA401120P2AS   | ACTIVE                | Surface Mount Module | EET             | 6    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA401120P2AST  | ACTIVE                | Surface Mount Module | EET             | 6    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA401120P2AZ   | ACTIVE                | Surface Mount Module | BET             | 6    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA401120P2AZT  | ACTIVE                | Surface Mount Module | BET             | 6    | 250         | TBD                     | Call TI              | Call TI                                    |                             |

| Orderable Device | Status <sup>(1)</sup> | Package Type         | Package Drawing | Pins | Package Qty | Eco Plan <sup>(2)</sup> | Lead/<br>Ball Finish | MSL Peak Temp <sup>(3)</sup>               | Samples<br>(Requires Login) |
|------------------|-----------------------|----------------------|-----------------|------|-------------|-------------------------|----------------------|--------------------------------------------|-----------------------------|
| PTMA402050A1AD   | ACTIVE                | Through-Hole Module  | EEP             | 4    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA402050A1AS   | ACTIVE                | Surface Mount Module | EET             | 4    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA402050A1AST  | ACTIVE                | Surface Mount Module | EET             | 4    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA402050A1AZ   | ACTIVE                | Surface Mount Module | BET             | 4    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA402050A1AZT  | ACTIVE                | Surface Mount Module | BET             | 4    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA402050A2AD   | ACTIVE                | Through-Hole Module  | EEV             | 5    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA402050A2AS   | ACTIVE                | Surface Mount Module | EEW             | 5    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA402050A2AST  | ACTIVE                | Surface Mount Module | EEW             | 5    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA402050A2AZ   | ACTIVE                | Surface Mount Module | BEW             | 5    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA402050A2AZT  | ACTIVE                | Surface Mount Module | BEW             | 5    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA402050A3AD   | ACTIVE                | Through-Hole Module  | EEP             | 6    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA402050A3AS   | ACTIVE                | Surface Mount Module | EET             | 6    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA402050A3AST  | ACTIVE                | Surface Mount Module | EET             | 6    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA402050A3AZ   | ACTIVE                | Surface Mount Module | BET             | 6    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA402050A3AZT  | ACTIVE                | Surface Mount Module | BET             | 6    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA402050N1AD   | ACTIVE                | Through-Hole Module  | EEP             | 5    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA402050N1AS   | ACTIVE                | Surface Mount Module | EET             | 5    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA402050N1AST  | ACTIVE                | Surface Mount Module | EET             | 5    | 250         | TBD                     | Call TI              | Call TI                                    |                             |

| Orderable Device | Status <sup>(1)</sup> | Package Type         | Package Drawing | Pins | Package Qty | Eco Plan <sup>(2)</sup> | Lead/<br>Ball Finish | MSL Peak Temp <sup>(3)</sup>               | Samples<br>(Requires Login) |
|------------------|-----------------------|----------------------|-----------------|------|-------------|-------------------------|----------------------|--------------------------------------------|-----------------------------|
| PTMA402050N1AZ   | ACTIVE                | Surface Mount Module | BET             | 5    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA402050N1AZT  | ACTIVE                | Surface Mount Module | BET             | 5    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA402050N2AD   | ACTIVE                | Through-Hole Module  | EEP             | 6    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA402050N2AS   | ACTIVE                | Surface Mount Module | EET             | 6    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA402050N2AST  | ACTIVE                | Surface Mount Module | EET             | 6    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA402050N2AZ   | ACTIVE                | Surface Mount Module | BET             | 6    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA402050N2AZT  | ACTIVE                | Surface Mount Module | BET             | 6    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA402050P1AD   | ACTIVE                | Through-Hole Module  | EEP             | 5    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA402050P1AS   | ACTIVE                | Surface Mount Module | EET             | 5    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA402050P1AST  | ACTIVE                | Surface Mount Module | EET             | 5    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA402050P1AZ   | ACTIVE                | Surface Mount Module | BET             | 5    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA402050P1AZT  | ACTIVE                | Surface Mount Module | BET             | 5    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA402050P2AD   | ACTIVE                | Through-Hole Module  | EEP             | 6    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA402050P2AS   | ACTIVE                | Surface Mount Module | EET             | 6    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA402050P2AST  | ACTIVE                | Surface Mount Module | EET             | 6    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA402050P2AZ   | ACTIVE                | Surface Mount Module | BET             | 6    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA402050P2AZT  | ACTIVE                | Surface Mount Module | BET             | 6    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA403033A1AD   | ACTIVE                | Through-Hole Module  | EEP             | 4    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |

| Orderable Device | Status <sup>(1)</sup> | Package Type         | Package Drawing | Pins | Package Qty | Eco Plan <sup>(2)</sup> | Lead/<br>Ball Finish | MSL Peak Temp <sup>(3)</sup>               | Samples<br>(Requires Login) |
|------------------|-----------------------|----------------------|-----------------|------|-------------|-------------------------|----------------------|--------------------------------------------|-----------------------------|
| PTMA403033A1AS   | ACTIVE                | Surface Mount Module | EET             | 4    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA403033A1AST  | ACTIVE                | Surface Mount Module | EET             | 4    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA403033A1AZ   | ACTIVE                | Surface Mount Module | BET             | 4    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA403033A1AZT  | ACTIVE                | Surface Mount Module | BET             | 4    | 200         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA403033A2AD   | ACTIVE                | Through-Hole Module  | EEV             | 5    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA403033A2AS   | ACTIVE                | Surface Mount Module | EEW             | 5    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA403033A2AST  | ACTIVE                | Surface Mount Module | EEW             | 5    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA403033A2AZ   | ACTIVE                | Surface Mount Module | BEW             | 5    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA403033A2AZT  | ACTIVE                | Surface Mount Module | BEW             | 5    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA403033A3AD   | ACTIVE                | Through-Hole Module  | EEP             | 6    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA403033A3AS   | ACTIVE                | Surface Mount Module | EET             | 6    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA403033A3AST  | ACTIVE                | Surface Mount Module | EET             | 6    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA403033A3AZ   | ACTIVE                | Surface Mount Module | BET             | 6    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA403033A3AZT  | ACTIVE                | Surface Mount Module | BET             | 6    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA403033N1AD   | ACTIVE                | Through-Hole Module  | EEP             | 5    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA403033N1AS   | ACTIVE                | Surface Mount Module | EET             | 5    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA403033N1AST  | ACTIVE                | Surface Mount Module | EET             | 5    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA403033N1AZ   | ACTIVE                | Surface Mount Module | BET             | 5    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |

| Orderable Device | Status <sup>(1)</sup> | Package Type         | Package Drawing | Pins | Package Qty | Eco Plan <sup>(2)</sup> | Lead/<br>Ball Finish | MSL Peak Temp <sup>(3)</sup>               | Samples<br>(Requires Login) |
|------------------|-----------------------|----------------------|-----------------|------|-------------|-------------------------|----------------------|--------------------------------------------|-----------------------------|
| PTMA403033N1AZT  | ACTIVE                | Surface Mount Module | BET             | 5    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA403033N2AD   | ACTIVE                | Through-Hole Module  | EEP             | 6    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA403033N2AS   | ACTIVE                | Surface Mount Module | EET             | 6    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA403033N2AST  | ACTIVE                | Surface Mount Module | EET             | 6    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA403033N2AZ   | ACTIVE                | Surface Mount Module | BET             | 6    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA403033N2AZT  | ACTIVE                | Surface Mount Module | BET             | 6    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA403033P1AD   | ACTIVE                | Through-Hole Module  | EEP             | 5    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA403033P1AS   | ACTIVE                | Surface Mount Module | EET             | 5    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA403033P1AST  | ACTIVE                | Surface Mount Module | EET             | 5    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA403033P1AZ   | ACTIVE                | Surface Mount Module | BET             | 5    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA403033P1AZT  | ACTIVE                | Surface Mount Module | BET             | 5    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA403033P2AD   | ACTIVE                | Through-Hole Module  | EEP             | 6    | 30          | Pb-Free (RoHS)          | SN                   | N / A for Pkg Type                         |                             |
| PTMA403033P2AS   | ACTIVE                | Surface Mount Module | EET             | 6    | 30          | TBD                     | SNPB                 | Level-1-235C-UNLIM/<br>Level-3-260C-168HRS |                             |
| PTMA403033P2AST  | ACTIVE                | Surface Mount Module | EET             | 6    | 250         | TBD                     | Call TI              | Call TI                                    |                             |
| PTMA403033P2AZ   | ACTIVE                | Surface Mount Module | BET             | 6    | 30          | Pb-Free (RoHS)          | SNAGCU               | Level-3-260C-168 HR                        |                             |
| PTMA403033P2AZT  | ACTIVE                | Surface Mount Module | BET             | 6    | 250         | TBD                     | Call TI              | Call TI                                    |                             |

<sup>(1)</sup> The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

---

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSELETE:** TI has discontinued the production of the device.

<sup>(2)</sup> Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

**TBD:** The Pb-Free/Green conversion plan has not been defined.

**Pb-Free (RoHS):** TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.


**Pb-Free (RoHS Exempt):** This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

**Green (RoHS & no Sb/Br):** TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)


<sup>(3)</sup> MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.


In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.



TOP VIEW



SIDE VIEW




PC LAYOUT

4207367-4/C 02/06


- NOTES:
- |                                                              |                                           |
|--------------------------------------------------------------|-------------------------------------------|
| A. All linear dimensions are in inches (mm).                 | F. Pins are 0.040" (1,02) diameter with   |
| B. This drawing is subject to change without notice.         | 0.070" (1,78) diameter standoff shoulder. |
| C. 2 place decimals are $\pm 0.030$ ( $\pm 0,76\text{mm}$ ). | G. All pins: Material – Copper Alloy      |
| D. 3 place decimals are $\pm 0.010$ ( $\pm 0,25\text{mm}$ ). | Finish – Tin (100%) over Nickel plate     |
| E. Recommended keep out area for user components.            |                                           |

## EET (R-PDSS-B6)


## DOUBLE SIDED MODULE




TOP VIEW



SIDE VIEW



PC LAYOUT




4207368-4/C 02/06


- NOTES:
- All linear dimensions are in inches (mm).
  - This drawing is subject to change without notice.
  - 2 place decimals are  $\pm 0.030$  ( $\pm 0,76$ mm).
  - 3 place decimals are  $\pm 0.010$  ( $\pm 0,25$ mm).
  - Recommended keep out area for user components.
  - Power pin connection should utilize four or more vias to the interior power plane of 0.025 (0,63) I.D. per input, ground and output pin (or the electrical equivalent).

- Paste screen opening: 0.080 (2,03) to 0.085 (2,16).  
Paste screen thickness: 0.006 (0,15).
- Pad type: Solder mask defined.
- All pins: Material – Copper Alloy  
Finish – Tin (100%) over Nickel plate  
Solder Ball – See product data sheet.
- Dimension prior to reflow solder.






TOP VIEW



SIDE VIEW




PC LAYOUT

4207367-2/C 02/06


- NOTES:
- |                                                              |                                           |
|--------------------------------------------------------------|-------------------------------------------|
| A. All linear dimensions are in inches (mm).                 | F. Pins are 0.040" (1,02) diameter with   |
| B. This drawing is subject to change without notice.         | 0.070" (1,78) diameter standoff shoulder. |
| C. 2 place decimals are $\pm 0.030$ ( $\pm 0,76\text{mm}$ ). | G. All pins: Material – Copper Alloy      |
| D. 3 place decimals are $\pm 0.010$ ( $\pm 0,25\text{mm}$ ). | Finish – Tin (100%) over Nickel plate     |
| E. Recommended keep out area for user components.            |                                           |

## EEP (R-PDSS-T5)


## DOUBLE SIDED MODULE



TOP VIEW



SIDE VIEW



PC LAYOUT


4207367-3/C 02/06

- NOTES:
- All linear dimensions are in inches (mm).
  - This drawing is subject to change without notice.
  - 2 place decimals are  $\pm 0.030$  ( $\pm 0,76$ mm).
  - 3 place decimals are  $\pm 0.010$  ( $\pm 0,25$ mm).
  - Recommended keep out area for user components.


- Pins are 0.040" (1,02) diameter with 0.070" (1,78) diameter standoff shoulder.
- All pins: Material – Copper Alloy  
Finish – Tin (100%) over Nickel plate

EET (R-PDSS-B5)


DOUBLE SIDED MODULE




TOP VIEW



SIDE VIEW



PC LAYOUT




4207368-3/C 02/06

- NOTES:
- All linear dimensions are in inches (mm).
  - This drawing is subject to change without notice.
  - 2 place decimals are  $\pm 0.030$  ( $\pm 0,76$ mm).
  - 3 place decimals are  $\pm 0.010$  ( $\pm 0,25$ mm).
  - Recommended keep out area for user components.
  - Power pin connection should utilize four or more vias to the interior power plane of 0.025 (0,63) I.D. per input, ground and output pin (or the electrical equivalent).


- Paste screen opening: 0.080 (2,03) to 0.085 (2,16).  
Paste screen thickness: 0.006 (0,15).
- Pad type: Solder mask defined.
- All pins: Material – Copper Alloy  
Finish – Tin (100%) over Nickel plate  
Solder Ball – See product data sheet.
- Dimension prior to reflow solder.

## EET (R-PDSS-B4)


## DOUBLE SIDED MODULE




TOP VIEW



SIDE VIEW



PC LAYOUT




4207368-2/C 02/06

- NOTES:
- All linear dimensions are in inches (mm).
  - This drawing is subject to change without notice.
  - 2 place decimals are  $\pm 0.030$  ( $\pm 0,76\text{mm}$ ).
  - 3 place decimals are  $\pm 0.010$  ( $\pm 0,25\text{mm}$ ).
  - Recommended keep out area for user components.
  - Power pin connection should utilize four or more vias to the interior power plane of 0.025 (0,63) I.D. per input, ground and output pin (or the electrical equivalent).

- Paste screen opening: 0.080 (2,03) to 0.085 (2,16).  
Paste screen thickness: 0.006 (0,15).
- Pad type: Solder mask defined.
- All pins: Material – Copper Alloy  
Finish – Tin (100%) over Nickel plate  
Solder Ball – See product data sheet.
- Dimension prior to reflow solder.

## EEV (R-PDSS-T5)


## DOUBLE SIDED MODULE




4207709/A 02/06

- NOTES:
- All linear dimensions are in inches (mm).
  - This drawing is subject to change without notice.
  - 2 place decimals are  $\pm 0.030$  ( $\pm 0,76$ mm).
  - 3 place decimals are  $\pm 0.010$  ( $\pm 0,25$ mm).
  - Recommended keep out area for user components.

- Pins are 0.040" (1,02) diameter with 0.070" (1,78) diameter standoff shoulder.
- All pins: Material – Copper Alloy  
Finish – Tin (100%) over Nickel plate



SIDE VIEW




4207710/A 02/06


- NOTES:
- |                                                              |                                                        |
|--------------------------------------------------------------|--------------------------------------------------------|
| A. All linear dimensions are in inches (mm).                 | G. Paste screen opening: 0.080 (2,03) to 0.085 (2,16). |
| B. This drawing is subject to change without notice.         | Paste screen thickness: 0.006 (0,15).                  |
| C. 2 place decimals are $\pm 0.030$ ( $\pm 0,76\text{mm}$ ). | H. Pad type: Solder mask defined.                      |
| D. 3 place decimals are $\pm 0.010$ ( $\pm 0,25\text{mm}$ ). | I. All pins: Material – Copper Alloy                   |
| E. Recommended keep out area for user components.            | Finish – Tin (100%) over Nickel plate                  |
| F. Power pin connection should utilize four or more vias     | Solder Ball – See product data sheet.                  |
| to the interior power plane of 0.025 (0,63) I.D. per input,  | J. Dimension prior to reflow solder.                   |
| ground and output pin (or the electrical equivalent).        |                                                        |

## BET (R-PDSS-B4)


## DOUBLE SIDED MODULE




TOP VIEW



SIDE VIEW



PC LAYOUT




4207711-2/B 02/06

- NOTES:
- All linear dimensions are in inches (mm).
  - This drawing is subject to change without notice.
  - 2 place decimals are  $\pm 0.030$  ( $\pm 0,76$ mm).
  - 3 place decimals are  $\pm 0.010$  ( $\pm 0,25$ mm).
  - Recommended keep out area for user components.
  - Power pin connection should utilize four or more vias to the interior power plane of 0.025 (0,63) I.D. per input, ground and output pin (or the electrical equivalent).


- Paste screen opening: 0.080 (2,03) to 0.085 (2,16).  
Paste screen thickness: 0.006 (0,15).
- Pad type: Solder mask defined.
- This is a lead-free solder ball design.  
Finish: Tin (100%) over Nickel plate  
Solder ball: 96.5 Sn/3.0 Ag/0.5 Cu
- Dimension prior to reflow solder.

## BET (R-PDSS-B5)


## DOUBLE SIDED MODULE




TOP VIEW



SIDE VIEW



PC LAYOUT



4207711-3/B 02/06


- NOTES:
- All linear dimensions are in inches (mm).
  - This drawing is subject to change without notice.
  - 2 place decimals are  $\pm 0.030$  ( $\pm 0,76$ mm).
  - 3 place decimals are  $\pm 0.010$  ( $\pm 0,25$ mm).
  - Recommended keep out area for user components.
  - Power pin connection should utilize four or more vias to the interior power plane of 0.025 (0,63) I.D. per input, ground and output pin (or the electrical equivalent).

- Paste screen opening: 0.080 (2,03) to 0.085 (2,16).  
Paste screen thickness: 0.006 (0,15).
- Pad type: Solder mask defined.
- This is a lead-free solder ball design.  
Finish: Tin (100%) over Nickel plate  
Solder ball: 96.5 Sn/3.0 Ag/0.5 Cu
- Dimension prior to reflow solder.




## BET (R-PDSS-B6)


## DOUBLE SIDED MODULE




TOP VIEW



SIDE VIEW



PC LAYOUT




4207711-4/B 02/06

- NOTES:
- All linear dimensions are in inches (mm).
  - This drawing is subject to change without notice.
  - 2 place decimals are  $\pm 0.030$  ( $\pm 0,76$ mm).
  - 3 place decimals are  $\pm 0.010$  ( $\pm 0,25$ mm).
  - Recommended keep out area for user components.
  - Power pin connection should utilize four or more vias to the interior power plane of 0.025 (0,63) I.D. per input, ground and output pin (or the electrical equivalent).


- Paste screen opening: 0.080 (2,03) to 0.085 (2,16).  
Paste screen thickness: 0.006 (0,15).
- Pad type: Solder mask defined.
- This is a lead-free solder ball design.  
Finish: Tin (100%) over Nickel plate  
Solder ball: 96.5 Sn/3.0 Ag/0.5 Cu
- Dimension prior to reflow solder.

BEW (R-PDSS-B5)


## DOUBLE SIDED MODULE




TOP VIEW



SIDE VIEW



## PC LAYOUT



4207712/B 02/06

- NOTES:
- |                                                                                                                                                                                  |                                                                                                                          |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| A. All linear dimensions are in inches (mm).                                                                                                                                     | G. Paste screen opening: 0.080 (2,03) to 0.085 (2,16).<br>Paste screen thickness: 0.006 (0,15).                          |
| B. This drawing is subject to change without notice.                                                                                                                             | H. Pad type: Solder mask defined.                                                                                        |
| C. 2 place decimals are $\pm 0.030$ ( $\pm 0,76\text{mm}$ ).                                                                                                                     | I. This is a lead-free solder ball design.<br>Finish: Tin (100%) over Nickel plate<br>Solder ball: 96.5 Sn/3.0 Ag/0.5 Cu |
| D. 3 place decimals are $\pm 0.010$ ( $\pm 0,25\text{mm}$ ).                                                                                                                     | J. Dimension prior to reflow solder.                                                                                     |
| E. Recommended keep out area for user components.                                                                                                                                |                                                                                                                          |
| F. Power pin connection should utilize four or more vias<br>to the interior power plane of 0.025 (0,63) I.D. per input,<br>ground and output pin (or the electrical equivalent). |                                                                                                                          |

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

### Products

|                        |                                                                                      |
|------------------------|--------------------------------------------------------------------------------------|
| Audio                  | <a href="http://www.ti.com/audio">www.ti.com/audio</a>                               |
| Amplifiers             | <a href="http://amplifier.ti.com">amplifier.ti.com</a>                               |
| Data Converters        | <a href="http://dataconverter.ti.com">dataconverter.ti.com</a>                       |
| DLP® Products          | <a href="http://www.dlp.com">www.dlp.com</a>                                         |
| DSP                    | <a href="http://dsp.ti.com">dsp.ti.com</a>                                           |
| Clocks and Timers      | <a href="http://www.ti.com/clocks">www.ti.com/clocks</a>                             |
| Interface              | <a href="http://interface.ti.com">interface.ti.com</a>                               |
| Logic                  | <a href="http://logic.ti.com">logic.ti.com</a>                                       |
| Power Mgmt             | <a href="http://power.ti.com">power.ti.com</a>                                       |
| Microcontrollers       | <a href="http://microcontroller.ti.com">microcontroller.ti.com</a>                   |
| RFID                   | <a href="http://www.ti-rfid.com">www.ti-rfid.com</a>                                 |
| OMAP Mobile Processors | <a href="http://www.ti.com/omap">www.ti.com/omap</a>                                 |
| Wireless Connectivity  | <a href="http://www.ti.com/wirelessconnectivity">www.ti.com/wirelessconnectivity</a> |

### Applications

|                               |                                                                                          |
|-------------------------------|------------------------------------------------------------------------------------------|
| Automotive and Transportation | <a href="http://www.ti.com/automotive">www.ti.com/automotive</a>                         |
| Communications and Telecom    | <a href="http://www.ti.com/communications">www.ti.com/communications</a>                 |
| Computers and Peripherals     | <a href="http://www.ti.com/computers">www.ti.com/computers</a>                           |
| Consumer Electronics          | <a href="http://www.ti.com/consumer-apps">www.ti.com/consumer-apps</a>                   |
| Energy and Lighting           | <a href="http://www.ti.com/energy">www.ti.com/energy</a>                                 |
| Industrial                    | <a href="http://www.ti.com/industrial">www.ti.com/industrial</a>                         |
| Medical                       | <a href="http://www.ti.com/medical">www.ti.com/medical</a>                               |
| Security                      | <a href="http://www.ti.com/security">www.ti.com/security</a>                             |
| Space, Avionics and Defense   | <a href="http://www.ti.com/space-avionics-defense">www.ti.com/space-avionics-defense</a> |
| Video and Imaging             | <a href="http://www.ti.com/video">www.ti.com/video</a>                                   |

TI E2E Community Home Page

[e2e.ti.com](http://e2e.ti.com)

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2012, Texas Instruments Incorporated



## О компании

ООО "ТрейдЭлектроникс" - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Наличие собственной эффективной системы логистики обеспечивает надежную поставку продукции по конкурентным ценам в точно указанные сроки.

Срок поставки со стоков в **Европе и Америке – от 3 до 14 дней.**

Срок поставки из **Азии – от 10 дней.**

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Предоставляем спец цены на элементы для создания инженерных сэмплов.

**Упорный труд, качественный результат дают нам право быть уверенными в себе и надежными для наших клиентов.**



### Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование

Наша организация особенно сильна в поставках модулей, микросхем, пассивных компонентов, ксайленсах (XC), EPF, EPM и силовой электроники.

Большой выбор предлагаемой продукции, различные виды оплаты и доставки, позволят Вам сэкономить время и получить максимум выгоды от сотрудничества с нами!

## Перечень производителей, продукцию которых мы поставляем на российский рынок





Trade Electronics.ru

гарантия бесперебойности производства и  
качества выпускаемой продукции

С удовольствием будем прорабатывать для Вас поставки всех необходимых компонентов по текущим запросам для скорейшего выявления групп элементов, по которым сотрудничество именно с нашей компанией будет для Вас максимально выгодным!

С уважением,

Менеджер отдела продаж ООО

«Трейд Электроникс»

Шишлаков Евгений

8 (495)668-30-28 доб 169

manager28@tradeelectronics.ru

<http://www.tradeelectronics.ru/>