74LVXC4245

OCTAL DUAL SUPPLY BUS TRANSCEIVER

- HIGH SPEED:
  t_{PD} = 6.5ns (MAX.) at
  V_{CCA} = 5.0V, V_{CCB} = 5.0V
- LOW POWER DISSIPATION:
  I_{CCA} = I_{CCB} = 5µA(MAX.) at T_A=25°C
- LOW NOISE: V_{OLP} =0.3V (TYP.) at
  V_{CCA}=5.0V V_{CCB} =3.3V
- SYMMETRICAL OUTPUT IMPEDANCE:
  $|I_{OH}| = I_{OL}$ = 24mA (MIN)
- BALANCED PROPAGATION DELAYS:
  $t_{PLH} \cong t_{PHL}$
- OPERATING VOLTAGE RANGE:
  V_{CCA}(OPR) = 4.5V to 5.5V (1.2V Data Retention)
  V_{CCB}(OPR) = 2.7V to 5.5V (1.2V Data Retention)
  PIN AND FUNCTION COMPATIBLE WITH
  74 SERIES C4245
- IMPROVED LATCH-UP IMMUNITY

SOP TSSOP

Table 1: Order Codes

PACKAGE	T & R
SOP	74LVXC4245MTR
TSSOP	74LVXC4245TTR

DESCRIPTION

The 74LVXC4245 is a dual supply 8 bit configurable low voltage CMOS OCTAL BUS TRANSCEIVER fabricated with sub-micron silicon gate and double-layer metal wiring C^2MOS technology. Designed for use as an interface between a 5V bus and a 3.3V to 5V bus in a mixed 5V/3.3V supply systems, it achieves high speed operation while maintaining the CMOS low power dissipation.

This IC is intended for two-way asynchronous communication between data buses and the direction of data transmission is determined by DIR input. The enable input $\overline{G}$ can be used to disable the device so that the buses are effectively isolated.

The A-port interfaces with the 5V bus, the B-port with the 3.3V to 5V bus.

All inputs are equipped with protection circuits against static discharge, giving them 2KV ESD immunity and transient excess voltage.

Figure 1: Pin Connection And IEC Logic Symbols



Figure 2: Input And Output Equivalent Circuit



Table 2: Pin Description

PIN N°	SYMBOL	NAME AND FUNCTION
2	DIR	Directional Control
3, 4, 5, 6, 7, 8, 9, 10	A1 to A8	Data Inputs/Outputs
21, 20, 19, 18, 17, 16, 15, 14	B1 to B8	Data Inputs/Outputs
22	$\overline{G}$	Output Enable Input
11, 12, 13	GND	Ground (0V)
23	NC	Not Connected
1	V_{CCA}	Positive Supply Voltage
24	V_{CCB}	Positive Supply Voltage

Table 3: Truth Table

INPUTS		FUNCTION		OUTPUT
$\overline{G}$	DIR	A BUS	B BUS	
L	L	OUTPUT	INPUT	A = B
L	H	INPUT	OUTPUT	B = A
H	X	Z	Z	Z

X : Don't Care
Z : High Impedance

Table 4: Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{CCA}	Supply Voltage	-0.5 to +7.0	V
V_{CCB}	Supply Voltage	-0.5 to +7.0	V
V_I	DC Input Voltage	-0.5 to V_{CCA} + 0.5	V
$V_{I/OA}$	DC I/O Voltage	-0.5 to V_{CCA} + 0.5	V
$V_{I/OB}$	DC I/O Voltage	-0.5 to V_{CCB} + 0.5	V
I_{IK}	DC Input Diode Current	± 20	mA
I_{OK}	DC Output Diode Current	± 50	mA
I_{OA}	DC Output Current	± 50	mA
I_{OB}	DC Output Current	± 50	mA
I_{CCA}	DC V_{CC} or Ground Current	± 200	mA
I_{CCB}	DC V_{CC} or Ground Current	± 100	mA
P_d	Power Dissipation	180	mW
T_{stg}	Storage Temperature	-65 to +150	°C
T_L	Lead Temperature (10 sec)	300	°C

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied

Table 5: Recommended Operating Conditions

Symbol	Parameter	Value	Unit
V_{CCA}	Supply Voltage (note 1)	4.5 to 5.5	V
V_{CCB}	Supply Voltage (note 1)	2.7 to 5.5	V
V_I	Input Voltage	0 to V_{CCA}	V
$V_{I/OA}$	I/O Voltage	0 to V_{CCA}	V
$V_{I/OB}$	I/O Voltage	0 to V_{CCB}	V
T_{op}	Operating Temperature	-40 to 85	°C
dt/dv	Input Rise and Fall Time (note 2)	0 to 10	ns/V

1) V_{IN} from 30% to 70% of V_{CC}
2) V_{CCA} = 4.5 to 5.5V; V_{CCB} = 2.7 to 3.6V;

Table 6: DC Specifications For V_{CCA}

Symbol	Parameter	Test Condition			Value							Unit
		V_{CCA} (V)	V_{CCB} (V)		T_A = 25 °C			-40 to 85 °C		-55 to 125°C		
					Min.	Typ.	Max.	Min.	Max.	Min.	Max.	
V_{IHA}	High Level Input Voltage	4.5	2.7		2.0			2.0		2.0		V
		4.5	3.6		2.0			2.0		2.0		
		5.5	5.5		2.0			2.0		2.0		
V_{ILA}	Low Level Input Voltage	4.5	2.7				0.8		0.8		0.8	V
		4.5	3.6				0.8		0.8		0.8	
		5.5	5.5				0.8		0.8		0.8	
V_{OHA}	High Level Output Voltage	4.5	3.0	I_O=-100 µA	4.4	4.5		4.4		4.4		V
		4.5	3.0	I_O=-24 mA	3.86			3.76		3.76		
V_{OLA}	Low Level Output Voltage	4.5	3.0	I_O=100 µA		0	0.1		0.1		0.1	V
		4.5	3.0	I_O=24 mA			0.36		0.44		0.44	
I_{IA}	Input Leakage Current	5.5	3.6	V_I = V_{CC} or GND			± 0.1		± 1		± 1	µA
I_{OZA}	High Impedance Output Leakage Current	5.5	3.6	V_{IA} = V_{IHA} or V_{ILA} V_{IB} = V_{IHB} or V_{ILB} $V_{I/OA}$ = V_{CCA} or GND			± 0.5		± 5		± 5	µA
I_{CCtA}	Quiescent Supply Current	5.5	3.6	V_{IA} = V_{CCA} or GND V_{IB} = V_{CCB} or GND			5		50		50	µA
I_{CCtAF}	Quiescent V_{CCA} Supply Current as B Port Floats	5.5	Open	V_{IA} = V_{CCA} or GND $\overline{G}$= DIR = V_{CCA} V_{IB} = Open			5		50		50	µA
ΔI_{CCtA}	Maximum Quiescent Supply Current / Input (An, DIR, $\overline{G}$)	5.5	5.5	V_{IA} = V_{CCA} - 2.1V V_{IB} = V_{CCB} or GND			1.35		1.5		1.5	mA

Table 7: DC Specifications For V_{CCB}

Symbol	Parameter	Test Condition			Value							Unit
		V_{CCA} (V)	V_{CCB} (V)		T_A = 25 °C			-40 to 85 °C		-55 to 125°C		
					Min.	Typ.	Max.	Min.	Max.	Min.	Max.	
V_{IHB}	High Level Input Voltage	4.5	2.7		2.0			2.0		2.0		V
		4.5	3.6		2.0			2.0		2.0		
		4.5	5.5		3.85			3.85		3.85		
V_{ILB}	Low Level Input Voltage	4.5	2.7				0.8		0.8		0.8	V
		4.5	3.6				0.8		0.8		0.8	
		4.5	5.5				1.65		1.65		1.65	
V_{OHB}	High Level Output Voltage	4.5	3.0	I_O=-100 µA	2.9	3.0		2.9		2.9		V
		4.5	3.0	I_O=-12 mA	2.56	2.85		2.46		2.46		
		4.5	3.0	I_O=-24 mA	2.35	2.65		2.25		2.25		
		4.5	2.7	I_O=-12 mA	2.3	2.5		2.2		2.2		
		4.5	2.7	I_O=-24 mA	2.1	2.3		2.0		2.0		
		4.5	4.5	I_O=-24 mA	3.86	4.25		3.76		3.76		
V_{OLB}	Low Level Output Voltage	4.5	3.0	I_O=100 µA		0.0	0.1		0.1		0.1	V
		4.5	3.0	I_O=24 mA		0.21	0.36		0.44		0.44	
		4.5	2.7	I_O=12 mA		0.11	0.36		0.44		0.44	
		4.5	2.7	I_O=24 mA		0.22	0.42		0.50		0.50	
		4.5	4.5	I_O=24 mA		0.18	0.36		0.44		0.44	
I_{IB}	Input Leakage Current	5.5	5.5	$V_I = V_{CCA}$ or GND			± 0.1		± 1		± 1	µA
I_{OZB}	High Impedance Output Leakage Current	5.5	5.5	$V_{IA} = V_{IHA}$ or V_{ILA} $V_{I/Ob} = V_{CCb}$ or GND			± 0.5		± 5		± 5	µA
I_{CCtB}	Quiescent Supply Current	5.5	5.5	$V_{IA} = V_{CCA}$ or GND $V_{IB} = V_{CCB}$ or GND			5		50		50	µA
ΔI_{CCtB}	Maximum Quiescent Supply Current / Input	5.5	3.6	$V_{IA} = V_{CCA}$ or GND $V_{IB} = V_{CCB}$ - 0.6V			0.35		0.5		0.5	mA

Table 8: Dynamic Switching Characteristics

Symbol	Parameter	Test Condition			Value							Unit
		V_{CCA} (V)	V_{CCB} (V)		T_A = 25 °C			-40 to 85 °C		-55 to 125°C		
					Min.	Typ.	Max.	Min.	Max.	Min.	Max.	
V_{OLPA}	Dynamic Low Level Quiet Output (note 1, 2)	5.0	3.3			1.0	1.5					V
		5.0	3.3		-1.2	-0.6						
V_{OLPB}	Dynamic Low Level Quiet Output (note 1, 2)	5.0	3.3			0.8	1.2					V
		5.0	3.3		-0.8	-0.5						
V_{IHDA}	Dynamic High Voltage Input (note 1, 3)	5.0	3.3				2					V
V_{ILDA}	Dynamic Low Voltage Input (note 1, 3)	5.0	3.3		0.8							V
V_{IHDB}	Dynamic High Voltage Input (note 1, 3)	5.0	3.3				2					V
V_{ILDB}	Dynamic Low Voltage Input (note 1, 3)	5.0	3.3		0.8							V

1) Worst case package
2) Max number of output defined as (n). Data inputs are driven 0V to 3.3V, (n-1) outputs switching and one output at GND
3) Max number of data inputs (n) switching. (n-1) switching 0V to 3.3V. Inputs under test switching: 3V to threshold (V_{ILD}). 0V to threshold (V_{IHD}) f = 1MHz

Table 9: AC Electrical Characteristics (C_L = 50pF, Input $t_r = t_f$ = 3ns)

Symbol	Parameter	Test Condition		Value (3)							Unit
		V_{CCB} (V)		T_A = 25°C			-40 to 85°C		-55 to 125°C		
				Min.	Typ.	Max.	Min.	Max.	Min.	Max.	
t_{PLH}	Propagation Delay Time (An to Bn)	2.7 to 3.6		1.0	5.5	7.5	1.0	8.0	1.0	8.5	ns
		5.0(*)		1.0	4.9	6.5	1.0	7.0	1.0	7.5	
t_{PHL}	Propagation Delay Time (An to Bn)	2.7 to 3.6		1.0	5.0	7.0	1.0	7.5	1.0	7.5	
		5.0(*)		1.0	4.0	5.5	1.0	6.0	1.0	6.5	
t_{PZL}	Output Enable Time ($\overline{G}$ to Bn)	2.7 to 3.6		1.0	6.7	9.0	1.0	10.0	1.0	10.5	ns
		5.0(*)		1.0	5.6	7.5	1.0	8.0	1.0	8.5	
t_{PZH}	Output Enable Time ($\overline{G}$ to Bn)	2.7 to 3.6		1.0	6.9	9.5	1.0	10.0	1.0	10.5	
		5.0(*)		1.0	5.7	7.5	1.0	8.0	1.0	8.5	
t_{PLZ}	Output Disable Time ($\overline{G}$ to Bn)	2.7 to 3.6		1.0	6.0	9.0	1.0	9.5	1.0	9.5	ns
		5.0(*)		1.0	4.8	7.0	1.0	7.5	1.0	7.5	
t_{PHZ}	Output Disable Time ($\overline{G}$ to Bn)	2.7 to 3.6		1.0	4.2	6.5	1.0	7.0	1.0	7.5	
		5.0(*)		1.0	3.8	5.5	1.0	6.0	1.0	6.5	
t_{PLH}	Propagation Delay Time (Bn to An)	2.7 to 3.6		1.0	5.6	7.5	1.0	8.0	1.0	8.5	ns
		5.0(*)		1.0	4.7	6.5	1.0	7.0	1.0	7.5	
t_{PHL}	Propagation Delay Time (Bn to An)	2.7 to 3.6		1.0	4.3	6.0	1.0	6.5	1.0	7.0	
		5.0(*)		1.0	3.9	5.0	1.0	5.5	1.0	5.5	
t_{PZL}	Output Enable Time ($\overline{G}$ to An)	2.7 to 3.6		1.0	8.0	10.0	1.0	11.0	1.0	11.5	ns
		5.0(*)		1.0	7.4	9.0	1.0	10.0	1.0	10.5	
t_{PZH}	Output Enable Time ($\overline{G}$ to An)	2.7 to 3.6		1.0	6.3	8.0	1.0	8.5	1.0	8.5	
		5.0(*)		1.0	6.1	7.5	1.0	8.5	1.0	8.5	
t_{PLZ}	Output Disable Time ($\overline{G}$ to An)	2.7 to 3.6		1.0	3.4	5.5	1.0	6.0	1.0	6.5	ns
		5.0(*)		1.0	3.4	5.5	1.0	6.0	1.0	6.5	
t_{PHZ}	Output Disable Time ($\overline{G}$ to An)	2.7 to 3.6		1.0	2.9	5.0	1.0	5.5	1.0	6.0	
		5.0(*)		1.0	2.9	4.5	1.0	5.0	1.0	5.5	
t_{OSLH} t_{OSHL}	Output To Output Skew Time (note1, 2)	2.7 to 3.6			0.5	1.0		1.5		1.5	ns
		5.0(*)			0.5	1.0		1.5		1.5	

1) Skew is defined as the absolute value of the difference between the actual propagation delay for any two outputs of the same device switching in the same direction, either HIGH or LOW ($t_{OSLH} = |t_{PLHm} - t_{PLHn}|$, $t_{OSHL} = |t_{PHLm} - t_{PHLn}|$
2) Parameter guaranteed by design
3) Typical values referred at V_{CCA} = 5.0V, V_{CCB} = 5.0V or V_{CCA} = 5.0V, V_{CCB} = 3.3V
(*) Voltage Range is 5.0V ± 0.5

Table 10: Capacitive Characteristics

Symbol	Parameter	Test Condition			Value							Unit
		V_{CCA} (V)	V_{CCB} (V)		T_A = 25 °C			-40 to 85 °C		-55 to 125°C		
					Min.	Typ.	Max.	Min.	Max.	Min.	Max.	
C_{INA}	Input Capacitance	open	open			4.5	10		10		10	V
$C_{I/O}$	Input/Output Capacitance	5.0	3.3			10						V
C_{PD}	Dynamic Low Level Quiet Output (note 1) A to B	5.0	3.3			55						V
C_{PD}	Dynamic Low Level Quiet Output (note 1) B to A	5.0	3.3			40						V

1) C_{PD} is defined as the value of the IC's internal equivalent capacitance which is calculated from the operating current consumption without load. (Refer to Test Circuit). Average current can be obtained by the following equation. $I_{CC(opr)} = C_{PD} \times V_{CC} \times f_{IN} + I_{CC}/8$ (per circuit)

Figure 3: Test Circuit



TEST	SWITCH
t_{PLH}, t_{PHL}	Open
t_{PZLH}, t_{PLZ}	$2V_{CC}$
t_{PZH}, t_{PHZ}	Open

C_L = 50pF or equivalent (includes jig and probe capacitance)
$R_L = R_1$ = 500Ω or equivalent
$R_T = Z_{OUT}$ of pulse generator (typically 50Ω)

Figure 4: Waveform - Propagation Delays (f=1MHz; 50% duty cycle)



Figure 5: Waveform - Output Enable And Disable Time (f=1MHz; 50% duty cycle)



SO-24 MECHANICAL DATA

DIM.	mm.			inch		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
A	2.35		2.65	0.093		0.104
A1	0.1		0.30	0.004		0.012
B	0.33		0.51	0.013		0.020
C	0.23		0.32	0.009		0.013
D	15.20		15.60	0.598		0.614
E	7.4		7.6	0.291		0.299
e		1.27			0.050	
H	10.00		10.65	0.394		0.419
h	0.25		0.75	0.010		0.030
L	0.4		1.27	0.016		0.050
k	0°		8°	0°		8°
ddd			0.100			0.004



TSSOP24 MECHANICAL DATA

DIM.	mm.			inch		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
A			1.1			0.043
A1	0.05		0.15	0.002		0.006
A2		0.9			0.035	
b	0.19		0.30	0.0075		0.0118
c	0.09		0.20	0.0035		0.0079
D	7.7		7.9	0.303		0.311
E	4.3		4.5	0.169		0.177
e		0.65 BSC			0.0256 BSC	
H	6.25		6.5	0.246		0.256
K	0°		8°	0°		8°
L	0.50		0.70	0.020		0.028



Tape & Reel SO-24 MECHANICAL DATA

DIM.	mm.			inch		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
A			330			12.992
C	12.8		13.2	0.504		0.519
D	20.2			0.795		
N	60			2.362		
T			30.4			1.197
Ao	10.8		11.0	0.425		0.433
Bo	15.7		15.9	0.618		0.626
Ko	2.9		3.1	0.114		0.122
Po	3.9		4.1	0.153		0.161
P	11.9		12.1	0.468		0.476



Note: Drawing not in scale

Tape & Reel TSSOP24 MECHANICAL DATA

DIM.	mm.			inch		
	MIN.	TYP	MAX.	MIN.	TYP.	MAX.
A			330			12.992
C	12.8		13.2	0.504		0.519
D	20.2			0.795		
N	60			2.362		
T			22.4			0.882
Ao	6.8		7	0.268		0.276
Bo	8.2		8.4	0.323		0.331
Ko	1.7		1.9	0.067		0.075
Po	3.9		4.1	0.153		0.161
P	11.9		12.1	0.468		0.476



Note: Drawing not in scale

Table 11: Revision History

Date	Revision	Description of Changes
27-Aug-2004	4	Ordering Codes Revision - pag. 1.

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

All other names are the property of their respective owners

© 2004 STMicroelectronics - All Rights Reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com

TradeElectronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

О компании

ООО "ТрейдЭлектроникс" - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Наличие собственной эффективной системы логистики обеспечивает надежную поставку продукции по конкурентным ценам в точно указанные сроки.

Срок поставки со стоков в **Европе и Америке – от 3 до 14 дней.**

Срок поставки из **Азии – от 10 дней.**

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Предоставляем спец цены на элементы для создания инженерных сэмплов.

Упорный труд, качественный результат дают нам право быть уверенными в себе и надежными для наших клиентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование

Наша организация особенно сильна в поставках модулей, микросхем, пассивных компонентов, ксайленсах (XC), EPF, EPM и силовой электроники.

Большой выбор предлагаемой продукции, различные виды оплаты и доставки, позволят Вам сэкономить время и получить максимум выгоды от сотрудничества с нами!

Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

Перечень производителей, продукцию которых мы поставляем на российский рынок

Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

С удовольствием будем прорабатывать для Вас поставки всех необходимых компонентов по текущим запросам для скорейшего выявления групп элементов, по которым сотрудничество именно с нашей компанией будет для Вас максимально выгодным!

С уважением,

Менеджер отдела продаж ООО

«Трейд Электроникс»

Шишлаков Евгений

8 (495)668-30-28 доб 169

manager28@tradeelectronics.ru

http://www.tradeelectronics.ru/