VVC4

Voltage Controlled Crystal Oscillator



The VVC4 Voltage Controlled Crystal Oscillator


Features

- **Vectron's Smallest VCXO, 5.0 X 3.2 X 1.2 mm**
- High Frequencies to 77.760 MHz
- 5.0 or 3.3 V operation
- Linearity ≤ 10%
- Tri-State Output for testing
- Low jitter < 1ps RMS 12 KHz to 20 MHz
- CMOS output
- 0/70 or –40/85 °C temperature range
- Hermetically sealed ceramic SMD package

Product is compliant to RoHS directive and fully compatible with lead free assembly

Applications

- Home Gateway
- WIMAX
- xDSL/PCMCIA cards
- Digital Video



Description

Vectron's VVC4 Voltage Controlled Crystal Oscillator (VCXO) is a quartz stabilized square wave generator with a CMOS output and is tested at CMOS and TTL (5.0 volt operation) logic levels.

The VVC4 is the smallest available VCXO making it ideally suitable for applications where size is limited but performance is required.

Performance Characteristics

Table 1. Electrical Performance

Parameter	Symbol	Min	Typical	Maximum	Units
Frequency	f_O	3.2500		77.7600	MHz
Supply Voltage [1] (+3.3 V) (+5.0 V)	V_{DD}	2.97 4.5	3.3 5.0	3.63 5.5	V
Supply Current	I_{DD}		8	15	mA
Output Logic Levels Output Logic High[2] Output Logic Low[2]	 V_{OH} V_{OL}	 0.9*V_{DD}		 0.1V_{DD}	 V V
Rise and Fall Time[2] <24 MHz >24 MHz	t_R / t_F			 10 6	 ns ns
Tristate Output Enabled Output Disabled	 V_{IN} V_{IL}	 2.5		 0.7	 V V
Symmetry or Duty Cycle[3] (ordering option)	SYM	40	50	60	%
Operating temperature (*ordering option*)		0/70 or –40/85			°C
Test Conditions for APR (+5V option)	V_C	0.5		4.5	V
Test Conditions for APR (+3.3V option)	V_C	0.3		3.0	V
Absolute Pull Range (*ordering option*)	APR	±50 ±80 ±100			ppm
Gain Transfer		Positive			ppm/V
Input Impedance			160		KOhm
Control Voltage Bandwidth (-3dB)	BW	10			kHz
Phase Noise 10 Hz Offset 100 Hz Offset 1 KHz Offset 10 KHz Offset 100 KHz Offset 1 MHz Offset			 -65 -95 -125 -140 -145 -150		 dBc/Hz dBc/Hz dBc/Hz dBc/Hz dBc/Hz dBc/Hz
Package Size		5.0 x 3.2 x 1.2			mm

1. A 0.01uF and a 0.1uF capacitor should be located as close to the supply as possible (to ground) is recommended.
2. Figure 1 defines these parameters. Figure 2 illustrates the equivalent five gate TTL load and operating conditions under which these parameters are tested and specified.
3. Symmetry is defined as (ON TIME/PERIOD with Vs= 1.4 V for TTL and Vs=2.5 V for CMOS, 5 volt operation, and Vs=1.65V for 3.3 Volt operation.




Figure 1. Output Waveform





Figure 2. Typical Output Test Conditions (25±5°C)


VVC4 Voltage Controlled Crystal Oscillator

Outline Diagram, Pad Layout and Pin Out



Pin #	Symbol	Function
1	V_C	Control Voltage
2	Tri-state	Logic low disables output Logic high or no connection enables output waveform
3	GND	Ground
4	f_O	Output Frequency
5	CMOS/TTL	Logic low for CMOS optimized symmetry Logic high or no connection for TTL optimized symmetry
6	V_{DD}	Supply Voltage

Tape and Reel



Tape and Reel Dimensions (mm)													
Tape Dimensions						Reel Dimensions							# Per
Product	A	B	C	D	E	F	G	H	I	J	K	L	Reel
VVC4	12	5.5	1.5	4	8	1.78	20.6	13	55	6	12.4	178	500

Absolute Maximum Ratings

Stresses in excess of the absolute maximum ratings can permanently damage the device. Functional operation is not implied at these or any other conditions in excess of conditions represented in the operational sections of this data sheet. Exposure to absolute maximum ratings for extended periods may adversely affect device reliability.

Table 2. Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
Power Supply	V_{DD}	6	Vdc
Storage Temperature	Tstorage	-55/125	°C
Voltage Control Range	V_C	0 to V_{DD}	V

Reliability

The VVC4 is capable of meeting the following qualification tests.

Table 3. Environmental Compliance

Parameter	Conditions
Mechanical Shock	MIL-STD-883 Method 2002
Mechanical Vibration	MIL-STD-883 Method 2007
Solderability	MIL-STD-883 Method 2003
Gross and Fine Leak	MIL-STD-883 Method 1014
Resistance to Solvents	MIL-STD-883 Method 2016
Moisture Sensitivity Level	1

Handling Precautions

Although ESD protection circuitry has been designed into the the VVC4, proper precautions should be taken when handling and mounting. VI employs a Human Body Model and a Charged-Device Model (CDM) for ESD susceptibility testing and design protection evaluation. ESD thresholds are dependent on the circuit parameters used to define the model. Although no industry wide standard has been adopted for the CDM, a standard HBM of resistance = 1.5kohms and capacitance = 100pF is widely used and therefore can be used for comparison purposes.

Table 4. ESD Ratings

Model	Minimum	Conditions
Human Body Model	1500	MIL-STD-883 Method 3115
Charged Device Model	1000	JESD 22-C101


The VVC4 is qualified to meet the JEDEC standard for Pb-Free assembly. The temperatures and time intervals listed are based on the Pb-Free small body requirements and parameters are listed in the table below. The contact pads are gold over nickel so lower IR reflow temperatures such as 220°C can be used (device is backwards compatible with a lead solder assembly).

The VVC4 is hermetically sealed so an aqueous wash is not an issue.

Table 5. Reflow Profile (IPC/JEDEC J-STD-020)

Parameter	Symbol	Value
PreHeat Time	t_S	60 sec Min, 180 sec Max
Ramp Up	R_{UP}	3 °C/sec Max
Time Above 217 °C	t_L	60 sec Min, 150 sec Max
Time To Peak Temperature	t_{AMB-P}	480 sec Max
Time At 260 °C	t_P	20 sec Min, 40 sec Max
Ramp Down	R_{DN}	6 °C/sec Max

VVC4 Voltage Controlled Crystal Oscillator



Standard Frequencies (MHz)

3.600	4.096	8.192	10.000	12.960
13.500	16.384	19.440	27.000	28.375
32.768	34.560	38.785	44.736	51.840
74.1758	74.250	77.760		

Other frequencies may be available upon request

Ordering Information

VVC4-BGD-xxMxxx

Product Family
VV = VCXO

Package
5x3.2x1.2

Power Supply/Linearity
A: 5.0V, 20% Linearity
B: 3.3V, 20% Linearity
C: 5.0V, 10% Linearity
D: 3.3V, 10% Linearity

Frequency
ex. 44M736 = 44.736 MHz

Temperature Range
B: 0 to +70°C
D: -40 to +85°C

Absolute Pull Range
G: ±50 ppm APR
N: ±80 ppm APR
H: ±100 ppm APR

For Additional Information, Please Contact:

VECTRON INTERNATIONAL A DOVER COMPANY

USA: Vectron International, 267 Lowell Rd, Hudson, NH 03051 . . . . . **Tel: 1-88-VECTRON-1** **Fax: 1-888-FAX-VECTRON**

EUROPE: . . . . . **Tel: 49 (0) 7268 8010** **Fax: 49 (0) 7268 801281**

ASIA: . . . . . **Tel: 86 21 5048 0777** **Fax: 86 21 5048 1881**

Vectron International reserves the right to make changes to the product(s) and or information contained herein without notice.
No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

TradeElectronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

О компании

ООО "ТрейдЭлектроникс" - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Наличие собственной эффективной системы логистики обеспечивает надежную поставку продукции по конкурентным ценам в точно указанные сроки.

Срок поставки со стоков в **Европе и Америке – от 3 до 14 дней.**

Срок поставки из **Азии – от 10 дней.**

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Предоставляем спец цены на элементы для создания инженерных сэмплов.

Упорный труд, качественный результат дают нам право быть уверенными в себе и надежными для наших клиентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование

Наша организация особенно сильна в поставках модулей, микросхем, пассивных компонентов, ксайленсах (XC), EPF, EPM и силовой электроники.

Большой выбор предлагаемой продукции, различные виды оплаты и доставки, позволят Вам сэкономить время и получить максимум выгоды от сотрудничества с нами!

Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

Перечень производителей, продукцию которых мы поставляем на российский рынок



Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

С удовольствием будем прорабатывать для Вас поставки всех необходимых компонентов по текущим запросам для скорейшего выявления групп элементов, по которым сотрудничество именно с нашей компанией будет для Вас максимально выгодным!

С уважением,

Менеджер отдела продаж ООО

«Трейд Электроникс»

Шишлаков Евгений

8 (495)668-30-28 доб 169

manager28@tradeelectronics.ru

http://www.tradeelectronics.ru/