
AZ164

MINIATURE POWER RELAY

FEATURES

- PC Terminals
- SPDT through 4PDT arrangement
- High switching capacity
- AC and DC coils
- Push To Test lever available on some models
- CE marking
- UL, CUR file E43203
- TÜV pending



CONTACTS

Arrangement	SPDT (1 Form C) DPDT (2 Form C) 3PDT (3 Form C) 4PDT (4 Form C)
Ratings	See chart on page 2
UL, CUR	See chart on page 2
Material	-1CT contact Silver cadmium oxide -2C and 2CT contact Silver cerium -3C contact Silver cerium -4C contact Silver cerium
Resistance	< 50 milliohms initially (24 V, 1 A voltage drop method)

COIL

Power	
At Pickup Voltage (typical)	DC: 576 mW, 6 to 48 VDC 704 mW, 110 VDC AC: .768 VA
Max. Continuous Dissipation	DC: 1.2 W (110 V : 1.5 W) at 20°C (68°F) AC: 1.7 VA at 20°C (68°F)
Temperature	105°C (221°F)

NOTES

1. All values at 20°C (68°F).
2. Relay may pull in with less than “Must Operate” value.
3. Specifications subject to change without notice.

GENERAL DATA

Life Expectancy **Mechanical** **Electrical**	Minimum operations 2 x 10^7 operations See UL/CUR ratings on page 2
Operate Time	25 msec max. at nominal coil voltage
Release Time	25 msec at nominal coil voltage (without suppression)
Dielectric Strength (at sea level for 1 min.)	1500 Vrms coil to contact 1000 Vrms contact to contact 1000 Vrms between contact sets
Insulation Resistance	100 megohms min. at 500 VDC, 20°C, 50% RH
Dropout	DC: > 10% of nominal coil voltage AC: > 30% of nominal coil voltage
Ambient Temperature **Operating** **Storage**	 -55°C (-67°F) to 70°C (158°F) -55°C (-67°F) to 105°C (221°F)
Vibration	0.062" (1.5 mm) DA at 10–55 Hz
Shock	20 g
Enclosure	Polycarbonate
Terminals	PC
Max. Solder Temp.	250°C (482°F)
Max. Solder Time	5 seconds
Weight	37 grams

ZETTLER electronics GmbH
Junkersstrasse 3, D-82178 Puchheim, Germany
Tel. +49 89 800 97 0 office@ZETTLERelectronics.com
Fax +49 89 800 97 200 www.ZETTLERelectronics.com

2003-07-30

AZ164


CONTACT RATINGS

Maximum Ratings	**SPDT Heavy duty, resistive load:** Max. Switched Power: 450 W, 3750 VA Max. Switched Current: 15 A Max. Switched Voltage: 30 VDC, 250 VAC **DPDT Heavy duty, resistive load:** Max. Switched Power: 300 W, 2500 VA Max. Switched Current: 10 A Max. Switched Voltage: 30 VDC, 250 VAC **DPDT Standard duty, resistive load:** Max. Switched Power: 210 W, 1750 VA Max. Switched Current: 7 A Max. Switched Voltage: 30 VDC, 250 VAC **3PDT, 4PDT, Standard duty, resistive load:** Max. Switched Power: 150 W, 1250 VA Max. Switched Current: 5 A Max. Switched Voltage: 30 VDC, 250 VAC


UL/CUR Ratings	**SPDT Heavy duty:** 15 A, 250 VAC 100k, Resistive 15 A, 30 VDC, 100k N.O., 30k N.C., Resistive **DPDT Heavy duty:** 10 A, 250 VAC, 100k, General use 10 A, 30 VDC, 100k, Resistive 1/3 HP, 120/240 VAC, 100k Motor load **DPDT, Standard duty:** 7A, 250 VAC, 100k Resistive 7A, 30 VDC, 100k, Resistive 3A, 240 VAC/30 VDC, 100k, General use **3PDT, 4PDT, Standard duty:** 5A, 250 VAC, 100k, Resistive 5A, 30 VDC, 100k, Resistive 3A, 240 VAC/30 VDC, 100k, General use

MECHANICAL DATA

AZ164-_C




AZ164-_CT




WIRING DIAGRAM

Viewed Towards Terminal



PC BOARD LAYOUTS

Viewed Towards Terminal



ZETTLER electronics GmbH

Junkersstrasse 3, D-82178 Puchheim, Germany

Tel. +49 89 800 97 0 office@ZETTLERelectronics.com
Fax +49 89 800 97 200 www.ZETTLERelectronics.com

2003-07-30

AZ164

RELAY ORDERING DATA

STANDARD RELAYS: DC Coil					
COIL SPECIFICATIONS					ORDER NUMBER*
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Nominal Current mA ± 10%	Coil Resistance Ohm	
5	4.0	5.5	181.0	27.5 ± 10%	AZ164–2C–5D
6	4.8	6.6	150.0	40.0 ± 10%	AZ164–2C–6D
12	9.6	13.2	75.0	160 ± 10%	AZ164–2C–12D
24	19.2	26.4	36.9	650 ± 10%	AZ164–2C–24D
48	38.4	52.8	18.5	2600 ± 15%	AZ164–2C–48D
110	88.0	121.0	10.0	11,000 ± 15%	AZ164–2C–110D

STANDARD RELAYS: AC Coil (50/60 Hz)					
COIL SPECIFICATIONS					ORDER NUMBER*
Nominal Coil VAC	Must Operate VAC	Max. Continuous VAC	Nominal Current mA ± 10%	Coil Resistance Ohm	
6	4.8	7.1	200.0	11.5 ± 10%	AZ164–2C–6A
12	9.6	14.3	100.0	46.0 ± 10%	AZ164–2C–12A
24	19.2	28.6	50.0	184 ± 10%	AZ164–2C–24A
48	38.4	57.1	25.0	735 ± 10%	AZ164–2C–48A
120	96.0	143.0	10.0	4,550 ± 10%	AZ164–2C–120A
220	176.0	261.0	5.5	14,400 ± 15%	AZ164–2C–220A
240	192.0	288.0	5.0	22,000 ± 15%	AZ164–2C–240A

* For 3PDT or 4PDT substitute “-3C” or “-4C” for “-2C”. For LED add “1” to the end of p/n. “-2C” and “-4C” versions are available with a lockable “push to test” lever. Add suffix “P” to part number for “Push to Test” lever.

RELAY ORDERING DATA

HEAVY DUTY RELAYS: DC Coil					
COIL SPECIFICATIONS					ORDER NUMBER*
Nominal Coil VDC	Must Operate VDC	Max. Continuous VDC	Nominal Current mA ± 10%	Coil Resistance Ohm	
5	4.0	5.5	181.0	27.5 ± 10%	AZ164–1CT–5D
6	4.8	6.6	150.0	40.0 ± 10%	AZ164–1CT–6D
12	9.6	13.2	75.0	160 ± 10%	AZ164–1CT–12D
24	19.2	26.4	36.9	650 ± 10%	AZ164–1CT–24D
48	38.4	52.8	18.5	2600 ± 15%	AZ164–1CT–48D
110	88.0	121.0	10.0	11,000 ± 15%	AZ164–1CT–110D

HEAVY DUTY RELAYS: AC Coil (50/60 Hz)					
COIL SPECIFICATIONS					ORDER NUMBER*
Nominal Coil VAC	Must Operate VAC	Max. Continuous VAC	Nominal Current mA ± 10%	Coil Resistance Ohm	
6	4.8	7.1	200.0	11.5 ± 10%	AZ164–1CT–6A
12	9.6	14.3	100.0	46.0 ± 10%	AZ164–1CT–12A
24	19.2	28.6	50.0	184 ± 10%	AZ164–1CT–24A
48	38.4	57.1	25.0	735 ± 10%	AZ164–1CT–48A
120	96.0	143.0	10.0	4,550 ± 10%	AZ164–1CT–120A
220	176.0	261.0	5.5	14,400 ± 15%	AZ164–1CT–220A
240	192.0	288.0	5.0	22,000 ± 15%	AZ164–1CT–240A

* For DPDT substitute “-2CT” for “-1CT”. For LED add “1” to the end of p/n.

ZETTLER electronics GmbH

Junkersstrasse 3, D-82178 Puchheim, Germany

Tel. +49 89 800 97 0 office@ZETTLERelectronics.com
Fax +49 89 800 97 200 www.ZETTLERelectronics.com

2003-07-30

TradeElectronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

О компании

ООО "ТрейдЭлектроникс" - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Наличие собственной эффективной системы логистики обеспечивает надежную поставку продукции по конкурентным ценам в точно указанные сроки.

Срок поставки со стоков в **Европе и Америке – от 3 до 14 дней.**

Срок поставки из **Азии – от 10 дней.**

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Предоставляем спец цены на элементы для создания инженерных сэмплов.

Упорный труд, качественный результат дают нам право быть уверенными в себе и надежными для наших клиентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование

Наша организация особенно сильна в поставках модулей, микросхем, пассивных компонентов, ксайленсах (XC), EPF, EPM и силовой электроники.

Большой выбор предлагаемой продукции, различные виды оплаты и доставки, позволят Вам сэкономить время и получить максимум выгоды от сотрудничества с нами!

Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

Перечень производителей, продукцию которых мы поставляем на российский рынок



Trade Electronics.ru

гарантия бесперебойности производства и качества выпускаемой продукции

С удовольствием будем прорабатывать для Вас поставки всех необходимых компонентов по текущим запросам для скорейшего выявления групп элементов, по которым сотрудничество именно с нашей компанией будет для Вас максимально выгодным!

С уважением,

Менеджер отдела продаж ООО

«Трейд Электроникс»

Шишлаков Евгений

8 (495)668-30-28 доб 169

manager28@tradeelectronics.ru

http://www.tradeelectronics.ru/