

FIBER MANAGEMENT


OFSRG

Optical Fiber Strain Relief Gland



Features

- OFBLT retention: >100N
- Mid point or end termination of OFBLT
- Provides secure fixing



MOUNTING HOLE

Description


The Optical Fiber Strain Relief Gland enables ruggedized patch cords, or fiber bundles, protected in OFBLT to be anchored to a chassis, or distribution trunking system, by the simple provision of a single hole.

The OFBLT is passed through the gland and is secured by the integral Tube Gripper Clip. This ensures a pull out resistance of over 100N while still ensuring a 30mm radius bend control and crush protection.

Miniflex technology manufactured by Richco - Patented						
Material: PVC • Color: Black						
Part No.	Standard Pack: 10/bag					
	Ø "D"	Ø "d1"	Ø "d2"	Ø "A"	"H"	"W"
OFSRG-05-BLK	.59 (15.0)	.20 (5.0)	.47 (12.0)	.43 (11.0)	1.46 (37.0)	0.12 (3.0)

OFD

Optical Fiber Duplexer




Features

- Tube retention: >100N
- For a Development Kit containing all adapters, order: OFD-C-05-19BLK

Description

The Optical Fiber Duplexer enables cables with aramid strands to be broken out and mechanically terminated. It provides an easy-to-use assembly with no crimping, while still retaining a minimum of a 100N pull. Used with the 5mm diameter OFBLT at the output port, it gives full bend control and crush protection for ongoing fibers. The Duplexer gives an easy-to-use lay through facility with internal fiber radius control.

The Duplexer gives a range of input adapters to cover OFBLT, fiber bundles, cable and patch cords from 2.5mm to 7.00mm in diameter. For cables up to 10.8mm in diameter, a rubber sleeve is provided. See cable size chart below.




Part Number	"L"	"W"	"w"	"H"	"d"
OFD series	1.95 (49.6)	0.64 (16.2)	0.52 (13.2)	0.31 (8.0)	0.20 (5.0)

Miniflex technology manufactured by Richco - Patented		
Material: Flame Retardant Nylon, RMS-19 (UL 94V0); Color: Black		
Part Number	Standard Pack: 10/bag	
	Incoming Cable Size Diameter	Adapter Color
OFD-C-1-05-19BLK	.098 - .138 (2.5 - 3.5)	Black
OFD-C-2-05-19BLK	.118 - .157 (3.0 - 4.0)	Blue
OFD-C-3-05-19BLK	.161 - .197 (4.1 - 5.0)	Brown
OFD-C-4-05-19BLK	.200 - .236 (5.1 - 6.0)	Green
OFD-C-5-05-19BLK	.240 - .276 (6.1 - 7.0)	Red
OFD-C-6-05-19BLK	.280 - .335 (7.1 - 8.5)	Black Rubber
OFD-C-9-05-19BLK	.335 - .425 (8.5 - 10.8)	Black Rubber
OFD-C-7-05-19BLK	.197 (5.0) OFBLT	Split Black
OFD-C-8-635-19BLK	.250 (6.35) OFBLT	Split Blue

OFCPA

Optical Fiber Cable and Patch Cord Anchor




Features

- OFBLT retention: >100N
- The OFCPA can also be used as a tube to tube uniter from OFBLT to OFBLT
- For a Development Kit containing all adapters order: OFCPA-05-19BLK

Description

The Optical Fiber Cable and Patch Cord Anchor enables cables with aramid strands or similar strength reinforcement to be mechanically terminated. It provides an easy-to-use assembly with no crimping, while still retaining a minimum of 100N pull out. Up to 4 patch cords Ø2.5mm can be terminated in one anchor.



Part Number	"D" Ø	"A"	"d" Ø	"L"
OFCPA series	.51 (13.0)	.31 (8.0)	.20 (5.0)	1.46 (37.0)

Miniflex Technology manufactured by Richco - Patented		
Material: Flame Retardant Nylon 6/6 UL94 V0, RMS-19; Color: Black		
Part Number	Standard Pack: 10/bag	
	Incoming Cable Size Diameter	Adapter Color
OFCPA-1-05-19BLK	.098 - .137 (2.5 - 3.5)	Black
OFCPA-2-05-19BLK	.118 - .157 (3.0 - 4.0)	Blue
OFCPA-3-05-19BLK	.161 - .196 (4.1 - 5.0)	Brown
OFCPA-4-05-19BLK	.200 - .236 (5.1 - 6.0)	Green
OFCPA-5-05-19BLK	.240 - .275 (6.1 - 7.0)	Red
OFCPA-6-05-19BLK	.280 - .335 (7.1 - 8.5)	Black Rubber
OFCPA-7-05-19BLK	.335 - .425 (8.5 - 10.8)	Black Rubber
OFCPA-T-05-19BLK	.196 (5.0) OFBLT	Split Black
OFCPA-T-635-19BLK	.196-.250 (5.0-6.35) OFBLT	Split Blue



О компании

ООО "ТрейдЭлектроникс" - это оперативные поставки широкого спектра электронных компонентов отечественного и импортного производства напрямую от производителей и с крупнейших мировых складов. Реализуемая нашей компанией продукция насчитывает более полумиллиона наименований.

Благодаря этому наша компания предлагает к поставке практически не ограниченный ассортимент компонентов как оптовыми, мелкооптовыми партиями, так и в розницу.

Наличие собственной эффективной системы логистики обеспечивает надежную поставку продукции по конкурентным ценам в точно указанные сроки.

Срок поставки со стоков в **Европе и Америке – от 3 до 14 дней.**

Срок поставки из **Азии – от 10 дней.**

Благодаря развитой сети поставщиков, помогаем в поиске и приобретении экзотичных или снятых с производства компонентов.

Предоставляем спец цены на элементы для создания инженерных сэмплов.

Упорный труд, качественный результат дают нам право быть уверенными в себе и надежными для наших клиентов.

Наша компания это:

- Гарантия качества поставляемой продукции
- Широкий ассортимент
- Минимальные сроки поставок
- Техническая поддержка
- Подбор комплектации
- Индивидуальный подход
- Гибкое ценообразование

Наша организация особенно сильна в поставках модулей, микросхем, пассивных компонентов, ксайленсах (XC), EPF, EPM и силовой электроники.

Большой выбор предлагаемой продукции, различные виды оплаты и доставки, позволят Вам сэкономить время и получить максимум выгоды от сотрудничества с нами!

Перечень производителей, продукцию которых мы поставляем на российский рынок





Trade Electronics.ru

гарантия бесперебойности производства и
качества выпускаемой продукции

С удовольствием будем прорабатывать для Вас поставки всех необходимых компонентов по текущим запросам для скорейшего выявления групп элементов, по которым сотрудничество именно с нашей компанией будет для Вас максимально выгодным!

С уважением,

Менеджер отдела продаж ООО

«Трейд Электроникс»

Шишлаков Евгений

8 (495)668-30-28 доб 169

manager28@tradeelectronics.ru

<http://www.tradeelectronics.ru/>